

The lpdoc Documentation Generator

An Automatic Documentation Generator for (C)LP Systems

REFERENCE MANUAL

The Ciao Documentation Series

<http://www.ciaohome.org/>

Generated/Printed on: 15 August 2011

Technical Report CLIP 5/97.1-3.0

Version 3.0 (2011/7/7, 16:33:15 CEST)

Edited by:

Manuel Hermenegildo

José Francisco Morales

Copyright © 1996-2011 Manuel Hermenegildo and José Francisco Morales.

This document may be freely read, stored, reproduced, disseminated, translated or quoted by any means and on any medium provided the following conditions are met:

1. Every reader or user of this document acknowledges that is aware that no guarantee is given regarding its contents, on any account, and specifically concerning veracity, accuracy and fitness for any purpose.
2. No modification is made other than cosmetic, change of representation format, translation, correction of obvious syntactic errors, or as permitted by the clauses below.
3. Comments and other additions may be inserted, provided they clearly appear as such; translations or fragments must clearly refer to an original complete version, preferably one that is easily accessed whenever possible.
4. Translations, comments and other additions or modifications must be dated and their author(s) must be identifiable (possibly via an alias).
5. This licence is preserved and applies to the whole document with modifications and additions (except for brief quotes), independently of the representation format.
6. Any reference to the "official version", "original version" or "how to obtain original versions" of the document is preserved verbatim. Any copyright notice in the document is preserved verbatim. Also, the title and author(s) of the original document should be clearly mentioned as such.
7. In the case of translations, verbatim sentences mentioned in (6.) are preserved in the language of the original document accompanied by verbatim translations to the language of the translated document. All translations state clearly that the author is not responsible for the translated work. This license is included, at least in the language in which it is referenced in the original version.
8. Whatever the mode of storage, reproduction or dissemination, anyone able to access a digitized version of this document must be able to make a digitized copy in a format directly usable, and if possible editable, according to accepted, and publicly documented, public standards.
9. Redistributing this document to a third party requires simultaneous redistribution of this licence, without modification, and in particular without any further condition or restriction, expressed or implied, related or not to this redistribution. In particular, in case of inclusion in a database or collection, the owner or the manager of the database or the collection renounces any right related to this inclusion and concerning the possible uses of the document after extraction from the database or the collection, whether alone or in relation with other documents.

Any incompatibility of the above clauses with legal, contractual or judiciary decisions or constraints implies a corresponding limitation of reading, usage, or redistribution rights for this document, verbatim or modified.

Table of Contents

Summary	1
1 Introduction	3
1.1 Overview of this document	3
1.2 lpdoc operation - source and target files	3
1.3 lpdoc usage	5
1.4 Version/Change Log	5
PART I - LPdoc Reference Manual	13
2 Generating Installing and Accessing Manuals ..	15
2.1 Generating a manual from the Ciao Emacs mode	15
2.2 Generating a manual	15
2.3 Working on a manual	17
2.4 Cleaning up the documentation directory	17
2.5 Installing a generated manual in a public area	18
2.6 Enhancing the documentation being generated	18
2.7 Accessing on-line manuals	19
2.7.1 Accessing html manuals	19
2.7.2 Accessing info manuals	19
2.7.3 Accessing man manuals	20
2.7.4 Putting it all together	21
2.8 Some usage tips	21
2.8.1 Ensuring Compatibility with All Supported Target Formats	21
2.8.2 Writing comments which document version/patch changes	21
2.8.3 Documenting Libraries and/or Applications	22
2.8.4 Documenting files which are not modules	22
2.8.5 Splitting large documents into parts	22
2.8.6 Documenting reexported predicates	23
2.8.7 Separating the documentation from the source file	23
2.8.8 Generating auxiliary files (e.g. READMEs)	23
2.9 Troubleshooting	24
3 Documentation Mark-up Language and Declarations	25
3.1 Usage and interface (comments)	25
3.2 Documentation on exports (comments)	25
docstring/1 (prop)	25
stringcommand/1 (prop)	26
version_descriptor/1 (regtype)	32
filetype/1 (regtype)	32
doc_id_type/3 (pred)	32
3.3 Documentation on internals (comments)	32
doc/2 (decl)	32
version_number/1 (regtype)	38
ymd_date/1 (regtype)	38

	time_struct/1 (regtype)	39
	version_maintenance_type/1 (regtype)	39
4	The Ciao assertion package	41
4.1	More info	41
4.2	Some attention points	41
4.3	Usage and interface (<code>assertions_doc</code>)	42
4.4	Documentation on new declarations (<code>assertions_doc</code>)	42
	(pred)/1 (decl)	42
	(pred)/2 (decl)	43
	(texec)/1 (decl)	43
	(texec)/2 (decl)	43
	(calls)/1 (decl)	43
	(calls)/2 (decl)	43
	(success)/1 (decl)	44
	(success)/2 (decl)	44
	(test)/1 (decl)	44
	(test)/2 (decl)	44
	(comp)/1 (decl)	45
	(comp)/2 (decl)	45
	(prop)/1 (decl)	45
	(prop)/2 (decl)	46
	(entry)/1 (decl)	46
	(exit)/1 (decl)	46
	(exit)/2 (decl)	47
	(modedef)/1 (decl)	47
	(decl)/1 (decl)	47
	(decl)/2 (decl)	47
	doc/2 (decl)	47
	comment/2 (decl)	48
4.5	Documentation on exports (<code>assertions_doc</code>)	48
	check/1 (pred)	48
	trust/1 (pred)	48
	true/1 (pred)	49
	false/1 (pred)	49
5	Types and properties related to assertions	51
5.1	Usage and interface (<code>assertions_props</code>)	51
5.2	Documentation on exports (<code>assertions_props</code>)	51
	assrt_body/1 (regtype)	51
	head_pattern/1 (prop)	52
	complex_arg_property/1 (regtype)	52
	property_conjunction/1 (regtype)	53
	property_starterm/1 (regtype)	53
	complex_goal_property/1 (regtype)	53
	nabody/1 (prop)	54
	dictionary/1 (regtype)	54
	c_assrt_body/1 (regtype)	54
	s_assrt_body/1 (regtype)	54
	g_assrt_body/1 (regtype)	55
	assrt_status/1 (regtype)	56
	assrt_type/1 (regtype)	56
	predfunctor/1 (regtype)	56
	propfunctor/1 (regtype)	56
	docstring/1 (prop)	56

6	Declaring regular types	57
6.1	Defining properties	57
6.2	Usage and interface (<code>regtypes_doc</code>)	59
6.3	Documentation on new declarations (<code>regtypes_doc</code>)	60
	(<code>regtype</code>)/1 (decl)	60
	(<code>regtype</code>)/2 (decl)	60
7	Basic data types and properties	61
7.1	Usage and interface (<code>basic_props</code>)	61
7.2	Documentation on exports (<code>basic_props</code>)	61
	<code>term</code> /1 (<code>regtype</code>)	61
	<code>int</code> /1 (<code>regtype</code>)	62
	<code>nnegint</code> /1 (<code>regtype</code>)	62
	<code>flt</code> /1 (<code>regtype</code>)	63
	<code>num</code> /1 (<code>regtype</code>)	63
	<code>atm</code> /1 (<code>regtype</code>)	64
	<code>struct</code> /1 (<code>regtype</code>)	64
	<code>gnd</code> /1 (<code>regtype</code>)	65
	<code>gndstr</code> /1 (<code>regtype</code>)	65
	<code>constant</code> /1 (<code>regtype</code>)	66
	<code>callable</code> /1 (<code>regtype</code>)	66
	<code>operator_specifier</code> /1 (<code>regtype</code>)	67
	<code>list</code> /1 (<code>regtype</code>)	67
	<code>list</code> /2 (<code>regtype</code>)	68
	<code>nlist</code> /2 (<code>regtype</code>)	68
	<code>member</code> /2 (prop)	69
	<code>sequence</code> /2 (<code>regtype</code>)	69
	<code>sequence_or_list</code> /2 (<code>regtype</code>)	70
	<code>character_code</code> /1 (<code>regtype</code>)	70
	<code>string</code> /1 (<code>regtype</code>)	71
	<code>num_code</code> /1 (<code>regtype</code>)	71
	<code>predname</code> /1 (<code>regtype</code>)	71
	<code>atm_or_atm_list</code> /1 (<code>regtype</code>)	72
	<code>compat</code> /2 (prop)	72
	<code>inst</code> /2 (prop)	72
	<code>iso</code> /1 (prop)	73
	<code>deprecated</code> /1 (prop)	73
	<code>not_further_inst</code> /2 (prop)	73
	<code>sideff</code> /2 (prop)	74
	(<code>regtype</code>)/1 (prop)	74
	<code>native</code> /1 (prop)	74
	<code>native</code> /2 (prop)	74
	<code>no_rtcheck</code> /1 (prop)	74
	<code>eval</code> /1 (prop)	75
	<code>equiv</code> /2 (prop)	75
	<code>bind_ins</code> /1 (prop)	75
	<code>error_free</code> /1 (prop)	75
	<code>memo</code> /1 (prop)	75
	<code>filter</code> /2 (prop)	75
	<code>flag_values</code> /1 (<code>regtype</code>)	75
	<code>pe_type</code> /1 (prop)	76

8 Properties which are native to analyzers 77

8.1 Usage and interface (<code>native_props</code>)	77
8.2 Documentation on exports (<code>native_props</code>)	77
<code>clique/1</code> (prop)	77
<code>clique_1/1</code> (prop)	78
<code>constraint/1</code> (prop)	78
<code>covered/1</code> (prop)	78
<code>covered/2</code> (prop)	78
<code>exception/1</code> (prop)	78
<code>exception/2</code> (prop)	78
<code>fails/1</code> (prop)	79
<code>finite_solutions/1</code> (prop)	79
<code>have_choicepoints/1</code> (prop)	79
<code>indep/1</code> (prop)	79
<code>indep/2</code> (prop)	79
<code>is_det/1</code> (prop)	79
<code>linear/1</code> (prop)	80
<code>mshare/1</code> (prop)	80
<code>mut_exclusive/1</code> (prop)	80
<code>no_choicepoints/1</code> (prop)	80
<code>no_exception/1</code> (prop)	81
<code>no_exception/2</code> (prop)	81
<code>no_signal/1</code> (prop)	81
<code>no_signal/2</code> (prop)	81
<code>non_det/1</code> (prop)	81
<code>nonground/1</code> (prop)	81
<code>not_covered/1</code> (prop)	81
<code>not_fails/1</code> (prop)	81
<code>not_mut_exclusive/1</code> (prop)	82
<code>num_solutions/2</code> (prop)	82
<code>solutions/2</code> (prop)	82
<code>possibly_fails/1</code> (prop)	82
<code>possibly_nondet/1</code> (prop)	83
<code>relations/2</code> (prop)	83
<code>sideff_hard/1</code> (prop)	83
<code>sideff_pure/1</code> (prop)	83
<code>sideff_soft/1</code> (prop)	83
<code>signal/1</code> (prop)	83
<code>signal/2</code> (prop)	83
<code>signals/2</code> (prop)	84
<code>size/2</code> (prop)	84
<code>size/3</code> (prop)	84
<code>size_lb/2</code> (prop)	84
<code>size_o/2</code> (prop)	84
<code>size_ub/2</code> (prop)	84
<code>size_metric/3</code> (prop)	84
<code>size_metric/4</code> (prop)	84
<code>steps/2</code> (prop)	85
<code>steps_lb/2</code> (prop)	85
<code>steps_o/2</code> (prop)	85
<code>steps_ub/2</code> (prop)	85
<code>tau/1</code> (prop)	85
<code>terminates/1</code> (prop)	86
<code>test_type/2</code> (prop)	86
<code>throws/2</code> (prop)	86
<code>user_output/2</code> (prop)	86

	instance/2 (prop).....	86
9	Meta-properties	87
9.1	Usage and interface (meta_props)	87
9.2	Documentation on exports (meta_props)	87
	call/2 (prop)	87
	(prop)/2 (prop)	87
	(regtype)/2 (prop).....	88
9.3	Documentation on multifiles (meta_props)	88
	callme/2 (pred)	88
9.4	Documentation on internals (meta_props).....	88
	prop_abs/1 (prop)	88
10	An Example - Documenting a Library Module	
	89
11	Auto Documenter Output for the Example	
	Module	95
11.1	Usage and interface (example_module).....	95
11.2	Documentation on exports (example_module)	95
	bar/1 (regtype)	95
	baz/1 (regtype)	95
	aorb/1 (regtype)	95
	tree_of/2 (regtype)	96
	list_or_aorb/2 (regtype).....	96
	q/2 (pred)	96
	r/1 (pred)	96
	p/1 (pred)	97
	p/5 (pred)	97
	u/3 (pred)	97
	long/1 (prop)	97
	w/1 (pred).....	98
	mytype/1 (pred)	98
	t/5 (pred)	98
	s/1 (pred)	98
	q/1 (pred)	99
	list/1 (regtype).....	99
11.3	Documentation on multifiles (example_module).....	100
	p/3 (pred).....	100
11.4	Documentation on internals (example_module).....	101
	list/2 (regtype).....	101
	og/2 (modedef)	101
	is/2 (pred).....	102
12	Run-time checking of assertions	103
12.1	Usage and interface (rtchecks_doc)	104
13	Unit Testing Library.....	105
13.1	Additional notes	105
13.2	Usage and interface (unittest_doc)	106

14	Installing lpdoc	107
14.1	Installing the source distribution (lpdoc)	107
14.2	Other software packages required (lpdoc)	107
PART II - LPdoc Internals Manual		109
15	Documentation Generation Library	111
15.1	Usage and interface (<code>autodoc</code>)	112
15.2	Documentation on exports (<code>autodoc</code>)	112
	<code>index_comment/2</code> (pred)	112
	<code>reset_output_dir_db/0</code> (pred)	112
	<code>ensure_output_dir_prepared/2</code> (pred)	112
	<code>get_autodoc_opts/3</code> (pred)	113
	<code>autodoc_gen_doctree/5</code> (pred)	113
	<code>fmt_infodir_entry/3</code> (pred)	113
	<code>autodoc_compute_grefs/3</code> (pred)	113
	<code>autodoc_translate_doctree/3</code> (pred)	113
	<code>autodoc_finish/1</code> (pred)	114
	<code>autodoc_gen_alternative/2</code> (pred)	114
15.3	Documentation on multifiles (<code>autodoc</code>)	114
	<code>autodoc_finish_hook/1</code> (pred)	114
	<code>autodoc_gen_alternative_hook/2</code> (pred)	114
16	Internal State for Documentation Generation	115
	115
16.1	Usage and interface (<code>autodoc_state</code>)	115
16.2	Documentation on exports (<code>autodoc_state</code>)	115
	<code>supported_option/1</code> (prop)	115
	<code>option_comment/2</code> (pred)	116
	<code>backend_id/1</code> (regtype)	116
	<code>backend_ignores_components/1</code> (pred)	116
	<code>backend_alt_format/2</code> (pred)	117
	<code>top_suffix/2</code> (pred)	117
	<code>docstate/1</code> (regtype)	117
	<code>docst_backend/2</code> (pred)	117
	<code>docst_currmod/2</code> (pred)	117
	<code>docst_set_currmod/3</code> (pred)	117
	<code>docst_opts/2</code> (pred)	117
	<code>docst_set_opts/3</code> (pred)	117
	<code>docst_inputfile/2</code> (pred)	117
	<code>docst_new_no_src/4</code> (pred)	117
	<code>docst_new_with_src/6</code> (pred)	118
	<code>docst_new_sub/3</code> (pred)	118
	<code>docst_message/2</code> (pred)	118
	<code>docst_message/3</code> (pred)	118
	<code>docst_opt/2</code> (pred)	118
	<code>docst_currmod_is_main/1</code> (pred)	118
	<code>docst_no_components/1</code> (pred)	118
	<code>docst_modname/2</code> (pred)	118
	<code>labgen_init/1</code> (pred)	118
	<code>labgen_clean/1</code> (pred)	118
	<code>labgen_get/2</code> (pred)	118
	<code>docst_mvar_lookup/3</code> (pred)	119
	<code>docst_mvar_replace/4</code> (pred)	119

docst_mvar_get/3 (pred)	119
docst_mdata_clean/1 (pred)	119
docst_mdata_assertz/2 (pred)	119
docst_mdata_save/1 (pred)	119
docst_gdata/3 (pred)	119
docst_gdata_query/2 (pred)	119
docst_gdata_query/3 (pred)	119
docst_gdata_restore/1 (pred)	119
docst_gdata_clean/1 (pred)	119
docst_gvar_save/2 (pred)	120
docst_gvar_restore/2 (pred)	120
docst_has_index/2 (pred)	120
all_indices/2 (pred)	120
get_doc/4 (pred)	120
get_doc_field/3 (pred)	120
get_doc_field_dict/3 (pred)	120
bind_dict_varnames/1 (pred)	120
get_mod_doc/3 (pred)	120
modtype/1 (regtype)	120
docst_modtype/2 (pred)	121
get_first_loc_for_pred/3 (pred)	121
17 Documentation Abstract Syntax Tree	123
17.1 Usage and interface (autodoc_doctree)	123
17.2 Documentation on exports (autodoc_doctree)	123
cmd_type/1 (pred)	123
doctree/1 (regtype)	124
doctree_is_empty/1 (pred)	124
is_nonempty_doctree/1 (pred)	124
empty_doctree/1 (pred)	124
doctree_insert_end/3 (pred)	124
doctree_insert_before_section/3 (pred)	124
doctree_concat/3 (pred)	124
doclink/1 (regtype)	125
doclabel/1 (regtype)	125
doclink_at/2 (pred)	125
doclink_is_local/1 (pred)	125
doctokens/1 (regtype)	125
section_prop/2 (pred)	125
section_select_prop/3 (pred)	125
doctree_save/2 (pred)	125
doctree_restore/2 (pred)	125
doctree_simplify/2 (pred)	125
doctree_putvars/5 (pred)	125
doctree_scan_and_save_refs/2 (pred)	126
doctree_prepare_docst_translate_and_write/3 (pred) ..	126
doctree_to_rawtext/3 (pred)	126
doctree_translate_and_write/3 (pred)	126
escape_string/4 (pred)	126
is_version/1 (pred)	126
version_patch/2 (pred)	127
version_date/2 (pred)	127
version_numstr/2 (pred)	127
version_string/2 (pred)	127
insert_show_toc/3 (pred)	127
17.3 Documentation on multfiles (autodoc_doctree)	127

	autodoc_rw_command_hook/4 (pred)	127
	autodoc_escape_string_hook/5 (pred)	127
18	Handling the Document Structure	129
18.1	Usage and interface (autodoc_structure)	129
18.2	Documentation on exports (autodoc_structure)	129
	docstr_node/4 (pred)	129
	clean_docstr/0 (pred)	129
	parse_structure/0 (pred)	129
	standalone_docstr/1 (pred)	129
	get_mainmod/1 (pred)	129
	get_mainmod_spec/1 (pred)	130
	all_component_specs/1 (pred)	130
19	Access to Default Settings	131
19.1	Usage and interface (autodoc_settings)	131
19.2	Documentation on exports (autodoc_settings)	131
	lpdoc_option/1 (pred)	131
	verify_settings/0 (pred)	131
	check_setting/1 (pred)	131
	setting_value_or_default/2 (pred)	131
	setting_value_or_default/3 (pred)	132
	setting_value/2 (pred)	132
	all_setting_values/2 (pred)	132
	get_command_option/1 (pred)	132
	requested_file_formats/1 (pred)	132
	load_vpaths/0 (pred)	132
	viewer/3 (pred)	132
	xdvi/1 (pred)	132
	xdvisize/1 (pred)	132
	pdfview/1 (pred)	132
	psview/1 (pred)	132
	htmlview/1 (pred)	133
	bibtex/1 (pred)	133
	tex/1 (pred)	133
	texindex/1 (pred)	133
	dvips/1 (pred)	133
	ps2pdf/1 (pred)	133
	makeinfo/1 (pred)	133
	makertf/1 (pred)	133
	rtftohlp/1 (pred)	133
	convertc/1 (pred)	133
	LPdoc Backends	135
20	Texinfo Backend	137
20.1	Usage and interface (autodoc_texinfo)	137
20.2	Documentation on exports (autodoc_texinfo)	137
	infodir_base/2 (pred)	137
20.3	Documentation on multifiles (autodoc_texinfo)	137
	autodoc_escape_string_hook/5 (pred)	137
	autodoc_rw_command_hook/4 (pred)	137
	autodoc_finish_hook/1 (pred)	138
	autodoc_gen_alternative_hook/2 (pred)	138

21	HTML Backend	139
21.1	Usage and interface (<code>autodoc_html</code>)	139
21.2	Documentation on multifiles (<code>autodoc_html</code>)	139
	<code>autodoc_escape_string_hook/5</code> (pred)	139
	<code>autodoc_rw_command_hook/4</code> (pred)	139
	<code>autodoc_finish_hook/1</code> (pred)	139
	<code>autodoc_gen_alternative_hook/2</code> (pred)	140
22	Resource Handling for the HTML Backend ..	141
22.1	Usage and interface (<code>autodoc_html_resources</code>)	141
22.2	Documentation on exports (<code>autodoc_html_resources</code>)	141
	<code>prepare_web_skel/1</code> (pred)	141
	<code>prepare_mathjax/0</code> (pred)	141
	<code>using_mathjax/1</code> (pred)	141
23	Template Support for the HTML Backend ..	143
23.1	Usage and interface (<code>autodoc_html_template</code>)	143
23.2	Documentation on exports (<code>autodoc_html_template</code>)	143
	<code>img_url/2</code> (pred)	143
	<code>fmt_html_template/3</code> (pred)	143
24	Man Pages (man) Backend	145
24.1	Usage and interface (<code>autodoc_man</code>)	145
24.2	Documentation on multifiles (<code>autodoc_man</code>)	145
	<code>autodoc_rw_command_hook/4</code> (pred)	145
	<code>autodoc_finish_hook/1</code> (pred)	145
	<code>autodoc_gen_alternative_hook/2</code> (pred)	145
25	Filesystem Abstraction	147
25.1	Usage and interface (<code>autodoc_filesystem</code>)	147
25.2	Documentation on exports (<code>autodoc_filesystem</code>)	147
	<code>filename/1</code> (regtype)	147
	<code>basename/1</code> (regtype)	147
	<code>subtarget/1</code> (regtype)	147
	<code>file_format_name/2</code> (pred)	148
	<code>supported_file_format/1</code> (pred)	148
	<code>file_format_provided_by_backend/3</code> (pred)	148
	<code>clean_fs_db/0</code> (pred)	148
	<code>get_output_dir/2</code> (pred)	148
	<code>get_cache_dir/2</code> (pred)	148
	<code>ensure_output_dir/1</code> (pred)	148
	<code>ensure_cache_dir/1</code> (pred)	148
	<code>main_absfile_in_format/2</code> (pred)	148
	<code>main_absfile_for_subtarget/3</code> (pred)	149
	<code>absfile_for_aux/3</code> (pred)	149
	<code>absfile_for_subtarget/4</code> (pred)	149
	<code>main_output_name/2</code> (pred)	149
	<code>get_subbase/3</code> (pred)	149
	<code>absfile_to_refile/3</code> (pred)	149
	<code>clean_all/0</code> (pred)	149
	<code>clean_docs_no_texi/0</code> (pred)	149
	<code>clean_all_temporal/0</code> (pred)	149
	<code>clean_intermediate/0</code> (pred)	150
	<code>clean_tex_intermediate/0</code> (pred)	150

26	Indexing Commands (Definition and Formatting)	151
26.1	Usage and interface (<code>autodoc_index</code>)	151
26.2	Documentation on exports (<code>autodoc_index</code>)	151
	<code>get_idxsub/2</code> (pred)	151
	<code>get_idxbase/3</code> (pred)	151
	<code>typeindex/5</code> (pred)	151
	<code>idx_get_indices/3</code> (pred)	152
	<code>is_index_cmd/1</code> (pred)	152
	<code>codetype/1</code> (pred)	152
	<code>normalize_index_cmd/3</code> (pred)	152
	<code>fmt_idx_env/7</code> (pred)	152
	<code>fmt_index/3</code> (pred)	152
27	Database of Documentation References	153
27.1	Usage and interface (<code>autodoc_refsdb</code>)	153
27.2	Documentation on exports (<code>autodoc_refsdb</code>)	153
	<code>compute_refs_and_biblio/1</code> (pred)	153
	<code>prepare_current_refs/1</code> (pred)	153
	<code>clean_current_refs/1</code> (pred)	153
	<code>secttree/1</code> (regtype)	154
	<code>secttree_resolve/3</code> (pred)	154
28	Error Messages	155
28.1	Usage and interface (<code>autodoc_errors</code>)	155
28.2	Documentation on exports (<code>autodoc_errors</code>)	155
	<code>error_text/3</code> (pred)	155
29	Resolution of Bibliographical References	157
29.1	Usage and interface (<code>autodoc_bibrefs</code>)	157
29.2	Documentation on exports (<code>autodoc_bibrefs</code>)	157
	<code>resolve_bibliography/1</code> (pred)	157
30	Auxiliary Definitions	159
30.1	Usage and interface (<code>autodoc_aux</code>)	159
30.2	Documentation on exports (<code>autodoc_aux</code>)	159
	<code>read_file/2</code> (pred)	159
	<code>ascii_blank_lines/2</code> (pred)	159
	<code>sh_exec/2</code> (pred)	159
31	Image Handling	161
31.1	Usage and interface (<code>autodoc_images</code>)	161
31.2	Documentation on exports (<code>autodoc_images</code>)	161
	<code>locate_and_convert_image/4</code> (pred)	161
	<code>clean_image_cache/0</code> (pred)	161
	References	163
	Library/Module Index	165
	Predicate/Method Index	167

Property Index	169
Regular Type Index	171
Declaration Index	173
Concept Index	175
Author Index	177
Global Index	179

Summary

`lpdoc` is an *automatic program documentation generator* for (C)LP systems.

`lpdoc` generates a reference manual automatically from one or more source files for a logic program (including ISO-Prolog, Ciao, many CLP systems, ...). It is particularly useful for documenting library modules, for which it automatically generates a description of the module interface. However, `lpdoc` can also be used quite successfully to document full applications and to generate nicely formatted plain ascii “readme” files. A fundamental advantage of using `lpdoc` to document programs is that it is much easier to maintain a true correspondence between the program and its documentation, and to identify precisely to what version of the program a given printed manual corresponds.

The quality of the documentation generated can be greatly enhanced by including within the program text:

- *assertions* (types, modes, etc. ...) for the predicates in the program, and
- *machine-readable comments* (in the “literate programming” style).

The assertions and comments included in the source file need to be written using the Ciao system *assertion language*. A simple compatibility library is available to make traditional (constraint) logic programming systems ignore these assertions and comments allowing normal treatment of programs documented in this way.

The documentation is currently generated in HTML or `texinfo` format. From the `texinfo` output, printed and on-line manuals in several formats (dvi, ps, info, etc.) can be easily generated automatically, using publicly available tools. `lpdoc` can also generate ‘man’ pages (Unix man page format) as well as brief descriptions in html or emacs info formats suitable for inclusion in an on-line index of applications. In particular, `lpdoc` can create and maintain fully automatically WWW and info sites containing on-line versions of the documents it produces.

The `lpdoc` manual (and the Ciao system manuals) are generated by `lpdoc`.

`lpdoc` is distributed under the GNU general public license.

Note: `lpdoc` is fully supported on Linux, Mac OS X, and other Un*x-like systems. Due to the use of several Un*x-related utilities, some documentation back-ends may require `Cygwin` under Win32.

This documentation corresponds to version 3.0 (2011/7/7, 16:33:15 CEST).

1 Introduction

`lpdoc` is an *automatic program documentation generator* for (C)LP systems.

`lpdoc` generates a reference manual automatically from one or more source files for a logic program (including ISO- Prolog [DEDC96], Ciao [Bue95], many CLP [JM94] systems, ...). It is particularly useful for documenting library modules, for which it automatically generates a description of the module interface. However, `lpdoc` can also be used quite successfully to document full applications and to generate nicely formatted plain ASCII “readme” files. A fundamental advantage of using `lpdoc` to document programs is that it is much easier to maintain a true correspondence between the program and its documentation, and to identify precisely to what version of the program a given printed manual corresponds.

1.1 Overview of this document

This first part of the document provides basic explanations on how to generate a manual from a set of files that already contain assertions and comments. Examples are given using the files in the `examples` directory provided with the `lpdoc` distribution.

These instructions assume that `lpdoc` (at least the executable and the library) is installed somewhere in your system. Installation instructions can be found in Chapter 14 [Installing `lpdoc`], page 107.

Other parts of this document provide:

- Documentation on the syntax and meaning of the *assertions* that `lpdoc` uses (those defined in the Ciao `assertions` library [PBH97,PBH98,Bue98]). These include *comment* assertions (containing basically documentation text), formal assertions (containing properties), and combined assertions.
- Documentation on a basic set of properties, types, etc. which are predefined in the Ciao `basic_props`, `regtypes`, `native_props`, and `meta_props` libraries. These properties, and any others defined by the user or in other Ciao libraries, can be used in program assertions.
- Documentation on the formatting commands that can be embedded in *comments*.

This document is also an internals manual, providing information on how the different internal parts of `lpdoc` are connected, which can be useful if new capabilities need to be added to the system or its libraries are used for other purposes. To this end, the document also provides:

- The documentation for the `autodoc` automatic documentation library, which provides the main functionality of `lpdoc`.
- Documentation on the predicates that define the conversion formats used (`texinfo`, and others), and which are in the `autodocformats` library.

All of the above have been generated automatically from the assertions in the corresponding sources and can also be seen as examples of the use of `lpdoc`.

Some additional information on `lpdoc` can be found in [Her00].

1.2 `lpdoc` operation - source and target files

The main input used by `lpdoc` in order to generate a manual are Prolog source files. Basically, `lpdoc` generates a file in the GNU `texinfo` format (with a `.texi` ending) for each Prolog file (see “The GNU Texinfo Documentation System” manual for more info on this format). The Prolog files must have a `.pl` ending.

If the `.pl` file does not define the predicates `main/0` or `main/1`, it is assumed to be a *library* and it is documented as such: the `.texi` file generated will contain information on the interface (e.g., the predicates exported by the file, the name of the module and usage if it is a module,

etc.), in addition to any other machine readable comments included in the file (see Section 2.6 [Enhancing the documentation being generated], page 18). If, on the contrary, the file defines the predicates `main/0` or `main/1`, it is assumed to be an *application* and no description of the interface is generated (see Section 2.8 [Some usage tips], page 21).

If needed, files written directly in `texinfo` can also be used as input files for `lpdoc`. These files *must have a .src (instead of .texi) ending*. This is needed to distinguish them from any automatically generated `.texi` files. Writing files directly in `texinfo` has the disadvantage that it may be difficult to adhere to all the conventions used by `lpdoc`. For example, these files will be typically used as chapters and must be written as such. Also, the set of indices used must be the same that `lpdoc` is generating automatically. Finally, no bibliographic citations can be used. Because of this, and because in the future `lpdoc` may be able to generate documentation in formats other than `texinfo` directly (in which case these files would not be useful), writing files in `texinfo` directly is discouraged. This facility was added mainly to be able to reuse parts of manuals which were already written in `texinfo`. Note that if a stand-alone file needs to be written (i.e., a piece of documentation that is not associated to any `.pl` file) it can always be written as a “dummy” `.pl` file (i.e., one that is not used as code), but which contains machine readable comments).

A manual can be generated either from a single source file (`.pl` or `.src`) or from a set of source files. In the latter case, then one of these files should be chosen to be the *main file*, and the others will be the *component files*. The main file is the one that will provide the title, author, date, summary, etc. to the entire document. In principle, any set of source files can be documented, even if they contain no assertions or comments. However, the presence of these will greatly improve the documentation (see Section 2.6 [Enhancing the documentation being generated], page 18).

If the manual is generated from a single main file (i.e., `component/1`, defined below, is empty), then the document generated will be a flat document containing no chapters. If the manual is generated from a main file and one or more components, then the document will contain chapters. The comments in the main file will be used to generate the introduction, while each of the component files will be used to generate a separate chapter. The contents of each chapter will be controlled by the contents of the corresponding component file.

As mentioned before, `lpdoc` typically generates `texinfo` files. From the `texinfo` files, `lpdoc` can generate printed and on-line manuals in several formats (`dvi`, `ps`, `ascii`, `html`, `info`, etc.) automatically, using different (publicly available) packages. Documentation in some other formats (e.g., `man1` pages) can be generated directly by `lpdoc`, selecting the appropriate options (see below). `lpdoc` can also generate directly includes generating (parts of) a master index of documents which can be placed in an installation directory and which will provide pointers to the individual manuals generated. Using this feature, `lpdoc` can maintain global `html` and/or `info` documentation sites automatically (see Section 2.5 [Installing a generated manual in a public area], page 18).

Additionally, `lpdoc` can provide some data from the main (prolog) documentation file. For this purpose the option `getinfo` can be used instead of specifying the format. This option reads the asked fields from `getinfo` variable (defined in `SETTINGS.pl` or via arguments with `-d` option). `lpdoc` will generate files with main documentation file-name as base-name, followed by one underscore, the asked field (got from `getinfo`), and the extension. The content of each of these files (so also the extension) is specified by `getinfo_format`, that can take the values `html`, `ascii`, `texic`. For example, to ask for the `summary` and the `author` fields from a prolog file called `file.pl`, with `lpdoc` documentation, we can execute the command `lpdoc -d getinfo=[author,summary] getinfo`. The files `myfile_author.txt` and `myfile_summary.txt` will be created. If also the option `-d getinfo_format=html` is used, the files will have `html` extension (and content).

1.3 lpdoc usage

The following provides the different command line options available when invoking `lpdoc`. This description is intended only for advanced users which might like to use `lpdoc` in custom applications. Note that the normal way to use `lpdoc` is by setting parameters in an `SETTINGS` file (see Section 2.2 [Generating a manual], page 15).

TODO: command line options not available here; need cooperation with `lpmake`

1.4 Version/Change Log

Version 3.0 (2011/7/7, 16:33:15 CEST)

- Major redesign of the documentation generator:
 - LPdoc redesigned to work internally with a 'doctree' representation (a-la Pillow). (Jose Morales)
 - A native HTML backend (not generated from texi). (Jose Morales)
 - Allow custom website generation from LPdoc documents. (Jose Morales)
 - Two passes for document generation, allowing resolution of bibliographical references in all backends (including HTML). (Jose Morales)
 - `doc_structure/1` in `SETTINGS` allows structure in LPdoc documents (sections can really be nested inside parts). (Jose Morales)
 - `:- doc(,_)` is the recommended syntax for documentation comments now.
 - Replacing `:- comment` by `:- doc` in LPdoc code, updated documentation. (Jose Morales)
- General improvements and bug fixes:
 - Designed a logo for LPdoc. (Jose Morales)
 - LPdoc comments can now be written using `%!` style comment syntax. (Manuel Hermenegildo)
 - Now commas etc. are allowed in section names (so that they can be used in other formats). They are eliminated automatically in `texi` and `info`. This avoids wrong section names –and thus dangling pointers– in generated `texinfo` files. (Manuel Hermenegildo)
 - Eliminated superfluous copy of summary in `info` mode. (Manuel Hermenegildo)
 - Eliminated unsupported chars that broke `texi` manual cross-referencing. (Manuel Hermenegildo)
 - Improved treatment of accents (dotless i and dotless j, o, etc.). (Manuel Hermenegildo)
 - Initial size passed to `xdvi` more appropriate for current `xdvis`. (Manuel Hermenegildo)
 - Accents in bibliography fixed. (Manuel Hermenegildo)
 - Now repeated sections are disambiguated. (Manuel Hermenegildo)
 - Eliminated unnecessary escaping (especially for `&`). (Manuel Hermenegildo)
 - Better detection of when version is not available. (Manuel Hermenegildo)
 - Added new `doc(address, _)` comment, which is the right place to put address/contact information in manuals (Jose Morales)

- Added new `@version{}` command (expands to the version of the software to be documented). (Jose Morales)
- Shorter `SETTINGS.pl` files (with some rudimentary, assertion-based checking of options) (Jose Morales)
- Bug fix: `'@@ include'` and `'@@ includeverbatim'` are no longer a problem (space can be omitted) (Jose Morales)
- Added and documented a new `documentation` filetype (for some parts of the manual that contains only documentation). That avoids the old trick of declaring a fake `main/0` predicate. (Jose Morales)
- Style for subtitle added automatically (in texinfo, it is *emph*; in HTML it is normal text with smaller font). The entries in `subtitle_extra` are free-form. (Jose Morales)
- Bugs and changelog appear now in the global links in the HTML backend. (Jose Morales)
- Merged code that documented `.pl` and `.lpdoc` files. (Jose Morales)
- No copyright section if no copyright comment. (Jose Morales)
- Auxiliary documentation files ending in `'_doc'` displayed incorrect names for the module (ending in `'_doc'`). E.g., `use_package(foo_doc)` was displayed instead of `use_package(foo_doc)`. Fixed. (Jose Morales)
- In `verbatim` environments, new-line characters are removed from the beginning. (Jose Morales)
- Fix wrong use of `erase/1` for clauses (which resulted in segmentation fault when documentation generation failed) (Jose Morales)
- Fixed image generation (now uses `.png` files for HTML) (Jose Morales)
- New code for text escape fixed some problems, like `'@/1'` operator not being displayed correctly in Info. (Jose Morales)
- Colors for Prolog variables (in HTML). (Jose Morales)
- Added `@begin{alert}` environment for alert messages (like cartouche, but in red). (Jose Morales)
- Supporting `'@"` command for umlaut, in addition to `'@..'` (Jose Morales)
- Double quotes correctly translated to HTML (Jose Morales)
- `@author` command to reference authors (changed command referring to people by `@author`, in all the documentation) (Jose Morales)
- Simplification of documentation setting files (see the documentation for further details) (Jose Morales)
- Using `open` for `lpdoc htmlview` command in MacOS X (Jose Morales)
- Adding `html` and `pdf` formats as options for emacs customization of LPdoc (`html` is the default one now) (Jose Morales)
- Improved detection of external tools for image conversion. (Manuel Hermenegildo)
- Added section name syntax auto-correction. This avoids wrong section names –and thus dangling pointers– in generated texinfo files. (Manuel Hermenegildo)
- Document size more appropriate for current xdvi versions. (Manuel Hermenegildo)
- Lpdod no longer adds `.info` filename suffix to `.infoindex` entries since it breaks Debian's `install-info –remove` and goes against standard practice anyway. (Jose Luis Gonzalez)

- Added option `-cv`, `-comment-version`, that tells lpdoc if the file has version comment. Formatting of lpdoc version comments completed. (Edison Mera)
- Improved handling of option values. Added `-d` option to lpdoc, that allows defining additional values in the argument. Added options `-l` and `-m` that are similar to the corresponding lpmake options. (Edison Mera)
- Support for in-code sections (experimental):
 - Latex-like font-lock highlight of sectioning documentation comments (`:-doc(C, "...")`, with `C` one of `title`, `section`, and `subsection`). Currently the `section` and `subsection` comments are still ignored by LPdoc. (Jose Morales)
- Support for mathematical notation (experimental):
 - new `@math{...}` and `@begin{displaymath}...@end{displaymath}` environments are supported (see the documentation for more details) (Jose Morales)
 - In documentation strings, single `\` must be escaped (e.g. `'@math{\\\lambda}'`) (Jose Morales)
 - Supported in both the texinfo and HTML (using MathJax) backends. (Jose Morales)
 - Added `@defmathcmd{Cmd}{N}{Def}` and `@defmathcmd{Cmd}{Def}`, both for texinfo and HTML backends. Those LPdoc commands define new mathematical environments (equivalent to `\newcommand`). (Jose Morales)

Version 2.1 (2004/10/28, 16:38:17 CEST)

Last version before moving to subversion. 1.9 and 2.0 were merged. 1.9 (based on makefiles) is deprecated.

- New functionality:
 - Use of `:-doc` declarations (as a shorthand for `comment`) now allowed. (Manuel Hermenegildo)
 - Made `xdvi` viewer, `ps` viewer, and `xdvi` zoom size be parameters (the latter since new versions of `xdvi` display sizes differently than old ones). (Manuel Hermenegildo)
 - Processing options can now be set for each file independently. (Manuel Hermenegildo)
 - Proper pdf generation now achieved in most cases, thanks to newer versions of `dvips`. (Manuel Hermenegildo)
 - Added option `-c Target` in lpdoc, that treats `Target` as a separate component. (Edison Mera)
 - Added option `-f ConfigFile` in lpdoc, that uses the file `ConfigFile` instead the default `LPSETTINGS.pl`. (Edison Mera)
 - Added option `ascii` that generates documentation in `ascii` plain format. (Edison Mera)
 - Added `-help` option. Is equal to `-h`. (Edison Mera)
 - Added option `testsettings` to check that the settings file is correctly specified. (Edison Mera)
 - Changed `generate_html_pointer/5` by `generate_html_pointer/6` to let it work with any given directory, and not only the working directory. (Edison Mera)

Version 2.0 (1999/8/17, 17:28:52 CEST)

Major change to eliminate need for Makefiles: lpdoc is now a standalone command (Manuel Hermenegildo). Proceeds in parallel with further development of 1.9. Merge pending. Previous changes incorporated since 1.8:

- New functionality:
 - A new parameter `PAPERTYPE` can be set in the `SETTINGS` file which controls the format of printed output. (Manuel Hermenegildo)
 - Default pdf viewer is now `ghostview`, since recent versions handle pdf well. (Manuel Hermenegildo)
 - Changed default style sheet in order to show `<PRE>` lines with a monospaced font. (Daniel Cabeza Gras)
 - Mode definitions now documented in a separate section. The way they are documented has been improved. (Manuel Hermenegildo)
 - References in files now updated only if `.refs` file is not empty. (Manuel Hermenegildo)
 - A *copy* of the html style sheet is now included in *distributions*. Also *Copies* of the html and info index head and tail files. (Manuel Hermenegildo)
 - Made pointers relative in library html templates. (Manuel Hermenegildo)
- Bug fixes and other minor improvements:
 - Declarations now documented properly even if they have the same name and arity as a predicate. (Manuel Hermenegildo)
 - Accented i's now translate correctly in html. (Manuel Hermenegildo)
 - Fixed a funny installation quirk: while we want to install LPdoc in the Ciao group, the manuals produced by LPdoc should be installed in the LPdoc group. (Manuel Hermenegildo)
 - Now using `lpdoclib` path alias. (Manuel Hermenegildo)
 - Fixed bug in ordering of html indices in recent Linux versions, related to varying file listing order depending on locale. (Manuel Hermenegildo)

Version 1.9 (1999/7/8, 18:19:43 MEST)

In this release the name of the application has changed to `lpdoc`.

- New commands:
 - `@begin{cartouche}` and `@end{cartouche}` commands now supported.
 - `@foonote` command now supported.
 - New `gmake htmlview` command (makes a running `netscape` visit the generated html manual). Suggested by Per Cederberg.
 - New `gmake distclean` command, intended for software distributions. Leaves the generated documents and eliminates *all* intermediate files (including `.texic/.texi` files).
 - Adobe pdf format now supported as a valid target. Unfortunately, embedded `.eps` figures are not supported at this time in pdf output.
 - The second argument of `:- comment(hide,...)` and `:- comment(doinclude,...)` declarations can now be a list of predicate names.
 - A `-u File` option is now supported so that a file including, e.g., path alias definitions can be included (this has the same functionality as the `-u` option in `ciaoc`).
 - Now typing just `gmake` does nothing. In order to do something at least one target should be specified. This was necessary so that recursive invocations with empty arguments did nothing.

- Added a new filetype: `part`. This allows splitting large documents into parts, each of which groups a series of chapters.
- Other new functionality:
 - A style sheet can now be specified which allows modifying many characteristics of the html output (fonts, colors, background, ...) (thanks to Per Cederberg).
 - Added limited support for changing page numbering (in `SETTINGS` file).
 - The concept indexing commands (`@index`, `@cindex`, and `@concept`) now work somewhat differently, to make them consistent with other indexing commands.
 - The old *usage* index is now called, more appropriately, *global* index. Correspondingly, changed things so that now every definition goes to the global index in addition to its definitional index.
 - Imported files from module `user` are now documented separately.
 - Now a warning is issued if characters unsupported by info are used in section names.
 - Navigation in html docs was improved.
 - The table of contents in printed manuals now contains entries for the individual descriptions of predicates, props, regtypes, declarations, etc. This can be shut off with the `-shorttoc` option.
 - Made more silent in normal conditions: file inclusion is muted now unless `-v` option is selected.
 - A single `.texi` file is now constructed (by grouping the `.texic` files generated for all components) in which the references and menus are resolved. This has the advantage that the process of resolving references and menus has now been sped up very significantly. Also, `texi` is now a valid target (perhaps useful for distributions). The generated files now have `texic` (*texinfo component*).
 - Now, declarations are always documented as long as there is a `decl` assertion. Also, they are now documented in a separate section.
- Bug fixes and other minor improvements:
 - The directory containing html manual is now called `BASENAME_html` instead of just `BASENAME`, which was confusing.
 - Now requesting building a `.ps` only does not leave a `.dvi` behind (useful for distributions).
 - File names can now include the symbol `_` even if they contain figures.
 - TeX-related intermediate files are now cleaned up after each run in order to avoid clutter.
 - Fixed `-modes`, which was broken since going to the new normalizer (was normalizer problem). Fixed problem with no documentation when only modes given.
 - Fixed duplication of documentation for internal predicates when also exported.
 - Minor formatting problem when no documentation nor definition found for a regtype fixed.
 - Determining exports, imports, etc. now done solely by calls to `c_itf` library (and, thus, synchronized with `ciaoc` compiler).

(Manuel Hermenegildo)

Version 1.8 (1999/3/24, 21:15:33 MET)

This version completes the port to using the ciao 0.8 modular assertion processing library. In addition, it includes the following improvements:

- Now, if the name of a file being documented ends in `_doc`, the `_doc` part is left out when referring to the file in the documentation (useful if one would like to place the documentation declarations in different file).
- It is now possible to declare (via a `comment/2` declaration) the intended use of a file which is not a module (i.e. a package, user, or include file), which results in correct documentation of operator definitions, new declarations, etc. The declaration is only needed for 'user' files (i.e., files to be loaded with `ensure_loaded/1`).
- Separated generation of the manuals from their installation. I.e., `gmake install` now does not force a `gmake all`, which has to be done by hand. This was necessary to ensure correct installation of distributed manuals, even if modification dates are changed during installation. Previously, in some cases generation was triggered unnecessarily.
- New `-v` option allows using quieter by default operation when not debugging.
- New option `-propmods` makes the name of the module in which a property is defined appear in front of the property in the places where the property is used.
- New option `-noisoline` makes the textual explanation of the `iso/1` property not appear in the description of the usage (but the `◊ ISO ◊` symbol does appear)
- Two new options, `-nosysmods` and `-noengmods`, selectively avoid listing the system or engine libraries used.
- If there is no declaration for a predicate, now a line is output with the name and arity and a simple comment saying that there is no further documentation available (this has the great advantage that then it goes in the index, and, for example in ciao, they get added to completion commands!).
- Now, if a property or regtype declaration has no textual comment, the actual definition is given (first level only) in the place where it is documented, and a simple generic message where it is used.
- Added `@noindent` and `@iso` commands.
- Nicer spacing now when printing predicate names which are operators, as well as modes, etc.
- Reporting of versions in libraries has been improved: now both the global version and the last version in which the library itself was changed are reported.
- Exported new declarations also documented now for include-type files.
- A module is now documented even if exports nothing at all.
- Engine modules used now documented even if no other modules used (was a reported bug).
- Fixed indexing of names containing `@` etc. for newer versions of texinfo.
- Tabs in verbatim modes now converted to a number of spaces (8). Not perfect, but produces better output than leaving the tabs in.
- Tex is now run in 'nonstopmode' which means it will typically not stop if there are minor errors (but some errors may go unnoticed...).
- The full path of the version maintenance directory is now computed (correctly) using the directory of the `.pl` file being documented as base.
- Notices for missing subtitle, copyright, and summary now only given from main file and not for components.

- Added special handling of regtype and generalized it to handle some props specially if there is a certain comp property present.

(Manuel Hermenegildo)

Version 1.7 (1998/12/2, 17:43:50 MET)

Major port to use the ciao 0.8 modular assertion processing library. (Manuel Hermenegildo)

Version 1.6 (1998/9/8, 12:49:26 MEST)

Added support for inserting images (.eps files) in text via @image command, email addresses via @email command, and url references via @uref command.

Unix 'man' output much improved. Also, it now includes a usage section. The corresponding text must be given in a string contained in the first argument of a fact of the `usage_message/1` predicate which appears in the program. Also, formatting of 'man' pages has been greatly improved.

A new 'ascii' format is now supported: a simple minded ascii manual (basically, an info file without pointers).

(Manuel Hermenegildo)

Version 1.5 (1998/8/23, 20:30:32 EST)

Now supporting a @cite command (YES!). It automatically accesses the bib entries in .bib files (using `bibtex`) and produces a 'References' appendix. @cite can be used in the text strings exactly as ite in LaTeX. The set of bib files to be used is given in the `SETTINGS` file.

Defining the type of version maintenance that should be performed by the `emacs ciao.el` mode (i.e., whether version numbers are in a given directory or in the file itself) is controlled now via a standard `comment/2` declaration. You should now write a declaration such as:

```
:- comment(version_maintenance,dir('../version')).
```

to state that control info is kept in directory `../version`. This has the advantage that it is shorter than the previous solution and that `lpdoc` can read this info easily. Using this guarantees that the version numbers of the manuals always coincide with those of the software.

Generation of indices of manuals (.htmlbullet files): if several manuals are installed in the same directory, an index to them is now generated at the beginning of the html cover page describing the directory.

(Manuel Hermenegildo)

Version 1.4 (1998/8/4, 19:10:35 MET DST)

The set of paths defined in `SETTINGS` for finding the source files are now also used to find 'included' files. As a result, full path is not needed any more in, e.g, @include command.

New @ref command which can be used to refer to chapter, sections, subsections, etc..

Support for recent minor changes in assertion format, including '#' as comment separator.

Used modules are now separated in documentation (in the interface description) by type (user, system, engine..).

Supports new 'hide' option in comments, to prevent an exported predicate from being documented. This is useful for example for avoiding mentioning in the documentation multifile predicates which are not intended to be modified by the user.

(Manuel Hermenegildo)

Version 1.3 (1998/7/10, 16:35:2 MET DST)

Exports are now listed in the chapter header separated by kind (pred, types, properties, ...).

The list of other modules used by a module is now separated in the chapter header into User and System modules (controlled by two sets of paths in `SETTINGS`).

New *hide* option of `comment/2 decl` prevents an exported predicate from being included in the documentation: `:- comment(hide,p/3)`.

(Manuel Hermenegildo)

Version 1.2 (1998/6/4, 9:12:19 MET DST)

Major overall improvements... (Manuel Hermenegildo)

Version 1.1 (1998/3/31)

Incorporated `autodoc` and `autodoformats` library to source in order to make distribution standalone. Improvements to installation and documentation. `Makefiles` now also install documentation in public areas and produce global indices. Several documents can coexist in the same installation directory. (Manuel Hermenegildo)

Version 1.0 (1998/2/24)

First Ciao-native distribution, with installation. (Manuel Hermenegildo)

Version 0.9 (1998/2/24)

Intermediate version, preparing for first major release. Modified `Makefile` and `SETTINGS` to handle installation of manuals. (Manuel Hermenegildo)

Version 0.6 (1998/2/10)

Added new indices and options, as well as more orthogonal handling of files. (Manuel Hermenegildo)

Version 0.4 (1998/2/24)

Added support for `nroff -m` formatting (e.g., for man pages). Added support for optional selection of indices to be generated. Added support for reexported predicates. Added (low level) `ascii` format. Added option handling (`-nbugs -noauthors -noversion -nochangelog -nopatches -modes` and `-headprops ...`). `-literalprops`. Fixed presentation when there are multiple kinds of assertions. Better error checking for `includefact/includedef`. (Manuel Hermenegildo)

Version 0.3 (1998/2/10)

Changed file reader to use Ciao native builtins. As a result, syntax files and full Ciao syntax now supported. Major reorganization of the code to make formatting more orthogonal. Now applications and libraries can be components or main files, standalone or with components interchangeably. `@includefact`, new predicate types, used libraries now precisely detected, `docinclude` option. (Manuel Hermenegildo)

Version 0.2 (1997/12/16)

Ported to native ciao. Version handling, selection of indices, `@include`. Added generation of an html brief description for a global index. Added unix manual page generation. Added support for specifying library paths. `-l` option for `htmlindex` and `man`. Installation improved: now all files for one application in the same directory. (Manuel Hermenegildo)

Version 0.1 (1997/7/30)

First official version (major rewrite from several previous prototypes, autodocumented!). (Manuel Hermenegildo)

Version 0.0 (1996/10/10)

First prototype.

PART I - LPdoc Reference Manual



2 Generating Installing and Accessing Manuals

Author(s): Manuel Hermenegildo.

Note: significant parts of this are obsolete. They must be updated to describe lpdoc version 2.0.

This section describes how to generate a manual (semi-)automatically from a set of source files using `lpdoc`, how to install it in a public area, and how to access it on line. It also includes some recommendations for improving the layout of manuals, usage tips, and troubleshooting advice.

2.1 Generating a manual from the Ciao Emacs mode

If you use the `Emacs` editor (highly recommended in all circumstances), then the simplest way to quickly generate a manual is by doing it from the Ciao Emacs mode (this mode comes with the Ciao Prolog distribution and is automatically installed with Ciao). The Ciao Emacs mode provides menu- and keyboard-binding driven facilities for generating a stand-alone document with the documentation corresponding to the file in the buffer being visited by Emacs. This is specially useful while modifying the source of a file, in order to check the output that will be produced when incorporating this file into a larger document. It is also possible to generate more complex documents, by editing the (automatically provided) `SETTINGS.pl` in the same way as when generating a manual from the command line (see below). However, when generating complex documents, it is best to devote an independent, permanent directory to the manual, and the full procedure described in the rest of this text is preferred.

2.2 Generating a manual

Two possible scenarios are described in this section. The first one is indicated to document quickly a single module and the second one targets the documentation of a larger application or library, in which the settings (which define how the documentation is to be generated, etc.) are read from a file, so that they can be reused as the application / library evolves.

In order to make `lpdoc` generate quickly the documentation of a single file it suffices to execute the command `lpdoc -d doc_structure=modulename dvi`, where `modulename` is the module to be documented (without extension) and (in this example) `dvi` is the desired format of the manual (other accepted formats include `html`, `pdf`, `ps`, etc. – see later). `lpdoc` will generate a manual with the name of the module and the format extension (in the example it would be `modulename.dvi`) in the same directory where it is executed.

For the second scenario, the `lpdoc` library directory includes a generic file which is quite useful for the generation of complete manuals: the `SETTINGS.pl` file. Use of this file is strongly recommended. Generating a manual using this file involves the following steps:

- Create a directory (e.g., `doc`) in which the documentation will be built. The creation of this directory is recommended, as it will be populated with intermediate files which are best kept separate. This directory is typically created in the top directory of the distribution of the application or library to be documented.
- Execute the command `lpdoc lpsettings` in the directory where the documentation is to be created (e.g., `doc` in the previous point). `lpdoc` will create an `SETTINGS.pl.generated` file with the default settings. This file should be renamed to `SETTINGS.pl` once the user agrees with its contents.
- Edit `SETTINGS.pl` to suit your needs. It is recommended that you review, at least, the following points:

- Set the variable `filepath` to include all the directories where the files to be documented can be found.
- Set the variable `systempath` to include all the *system* directories where system files used can be found, regardless whether they are to be documented or not. This will be used to access definitions of types, etc.

It is very important to include *all* related directories either in `filepath` or in `systempath` because on startup `lpdoc` has *no default search paths for files* defined (not even those typically defined by default in the `Prolog` system under which it was compiled! – this allows documenting `Prolog` systems other than that under which `lpdoc` was compiled).

The effect of putting a path in `systempaths` instead of in `filepaths` is that the modules and files in those paths are documented as *system modules* (this is useful when documenting an application to distinguish its parts from those which are in the system libraries).

- Set `doc_structure` to be the *document structure* (`doc_structure/1`).

For the rest of the settings in the `SETTINGS.pl` file you can simply use the default values indicated. You may however want to change several of these:

- `doc_mainopts` can be set to a series of options which allow more detailed control of what is included in the documentation for the main file and how (i.e., including bug information, versions and patches or only patches, authors, changelog, explanation of modes, *one-sided printing* (*two-sided* is the default), etc.). See `option_comment/2` in `autodoc` or type `lpdoc -help` for a list of these options.
- In the same way `doc_compopts` sets options for the component files. Currently these options are common to all component files but they can be different from `doc_mainopts`. The allowable options are the same as above.
- `docformat` determines the set of formats (`dvi`, `ps`, `ascii`, `html`, `info`, `man1`, ...) in which the documentation should be generated by default when typing `lpdoc all`. Selecting `htmlindex` and/or `infoindex` requests the generation of (parts of) a master index to be placed in an installation directory and which provide pointers to the documents generated (see below). If the main file is an **application**, and the `man1` option is selected, then `lpdoc` looks for a `usage_message/1` fact, which should contain a string as argument, and will use that string to document the *usage of the application* (i.e., it will be used to fill in the *synopsis section of the man page*).
- `output_name` determines the base file name of the main documents generated by `lpdoc`. By default it is equal to the main file name, or, if the main file name ends with `_doc`, then it is equal to the name without the `_doc` suffix. This is useful when the name of the documentation file to be produced needs to have a name that is not directly related to the main file being documented.
- `index` determines the list of indices to be included at the end of the document. These can include indices for defined predicates, modules, concepts, etc. For a complete list of the types of indices available see `index_comment/2` in `autodoc` or type `lpdoc -help` for a listing. A setting of `all` generates all the supported indices – but *beware of limitations in the number of simultaneous indices* supported in many `texinfo` installations.
- `bibfile` determines a list of *.bib files* (one file per path), i.e., files containing *bibliographic entries* in `bibtex` format. This is only relevant if you are using citations in the text (using the `@cite` command). In that case those will be the files in which the citations will be searched for. All the references will appear together in a *References* appendix at the end of the manual.

If you are not using citations, then select the `-nobiblio` option on the main file, which will prevent an empty 'References' appendix from appearing in the manual.

- `startpage` (default value 1) allows changing the page number of the first page of the manual. This can be useful if the manual is to be included in a larger document or set of manuals. Typically, this should be an *odd* number.
- `papertype` (default value `afourpaper`) allows select several paper sizes for the printable outputs (`dvi`, `ps`, etc.). The currently supported outputs (most of them inherited from `texinfo`) are:

`afourpaper`

The default, usable for printing on *A4 paper*. Rather busy, but saves trees.

`afourwide`

This one crams even more stuff than `afourpaper` on an A4 page. Useful for generating manuals in the least amount of space. It saves more trees.

`afourlatex`

This one is a little less compressed than `afourpaper`.

`smallbook`

Small pages, like in a handbook.

`letterpaper`

For printing on American *letter size paper*.

`afourthesis`

A *thesis-like style* (i.e., double spaced, wide margins etc.). Useful – for inserting `lpdoc` output as appendices of a thesis or similar document. It does not save trees.

- Type `lpdoc all` to generate all the formats defined. `lpdoc dvi`, `lpdoc html`, `lpdoc ps` or `lpdoc info`, etc. will force the generation of a single target format.

2.3 Working on a manual

In order to speed up processing while developing a manual, it is recommended to work by first generating a `.dvi` version only (i.e., by typing `lpdoc dvi`). The resulting output can be easily viewed by tools such as `xdvi` (which can be started by simply typing `lpdoc view`). Note that once an `xdvi` window is started, it is not necessary to restart it every time the document is reformatted (`lpdoc dvi`), since `xdvi` automatically updates its view every time the `.dvi` file changes. This can also be forced by typing `(R)` in the `xdvi` window. The other formats can be generated later, once the `.dvi` version has the desired contents.

2.4 Cleaning up the documentation directory

`lpdoc` can also take care of tidying up the directory where the documentation is being generated:

- `lpdoc clean` deletes all intermediate files, but leaves the targets (i.e., the `.ps`, `.dvi`, `.ascii`, `.html`, etc. files), as well as all the generated `.texic` files.
- `lpdoc distclean` deletes all intermediate files and the generated `.texic` files, leaving only the targets (i.e., the `.ps`, `.dvi`, `.ascii`, `.html`, etc. files). This is the option normally used when building software distributions in which the manuals come ready made in the distribution itself and will not need to be generated during installation.
- `lpdoc docsclean` deletes all intermediate files and the generated targets, but leaves the `.texic` files. This option can be used in software distributions in which the manuals in the different formats will be generated during installation. This is generally more compact, but requires the presence of several tools, such as `tex`, `Emacs`, etc. (see Section 14.2 [Other software packages required (`lpdoc`)], page 107), in order to generate the manuals in the target formats during installation.

- `lpdoc realclean` performs a complete cleanup, deleting also the `.texic` files, i.e., it typically leaves only the `SETTINGS.pl` file. This is the most compact, but requires the presence of the tools mentioned above, the source files from which the manuals are generated and `lpdoc` in order to re generate the manuals in the target formats during installation.

2.5 Installing a generated manual in a public area

Note: This part is obsolete. It must be updated to describe lpdoc version 2.0. – EMM

Once the manual has been generated in the desired formats, the `Makefile` provided also allows automatic installation in a different area, specified by the `docdir` option in the `SETTINGS.pl` file. This is done by typing `lpdoc install`.

As mentioned above, `lpdoc` can generate directly brief descriptions in `html` or `Emacs` info formats suitable for inclusion in an on-line index of applications. In particular, if the `htmlindex` and/or `infoindex` options are selected, `lpdoc install` will create the installation directory, place the documentation in the desired formats in this directory, and produce and place in the same directory suitable `index.html` and/or `dir` files. These files will contain some basic info on the manual (extracted from the summary and title, respectively) and include pointers to the relevant documents which have been installed. The `infodirheadfile` / `infodirtailfile` (default examples, used in the CLIP group at UPM, are included with the distribution) should point to files which will be used as head and tail templates when generating the `dir` files. Several manuals, coming from different `doc` directories, can be installed in the same `docdir` directory. In this case, the descriptions of and pointers to the different manuals will be automatically combined (appearing in alphabetic order) in the `index.html` and/or `dir` indices, and a *contents area* will appear at the beginning of the *html index page*. **Important Note:** In order for the different components to appear in the correct positions in the index pages mentioned above the traditional ('C') Lexical order must be active. In recent Un*x systems (e.g., in most current Linux systems) this may not be the case. There are several possible fixes:

- For `csh` put `setenv LC_COLLATE C` in your `.cshrc`.
- For `bash` put `export LC_COLLATE=C` in your `.profile`.
- In many systems this can be done globally by the super-user. E.g., in many Linux systems set `LANG="C"` in `/etc/sysconfig/i18n`.

Note that, depending on the structure of the manuals being generated, some formats are not very suitable for public installation. For example, the `.dvi` format has the disadvantage that it is not self contained if images are included in the manual. Typing `lpdoc uninstall` in a `doc` directory will uninstall from `docdir` the manuals corresponding to the `Makefile` in that `doc` directory. If a manual is already installed and changes in the number of formats being installed are desired, `lpdoc uninstall` should be made before changing the `docformats` variable and doing `lpdoc install` again. This is needed in order to ensure that a complete cleanup is performed.

2.6 Enhancing the documentation being generated

The quality of the documentation generated can be greatly enhanced by including within the program text:

- *assertions*, and
- *machine-readable comments*.

Assertions are declarations which are included in the source program and provide the compiler with information regarding characteristics of the program. Typical assertions include type

declarations, modes, general properties (such as *does not fail*), standard compiler directives (such as `dynamic/1`, `op/3`, `meta_predicate/1...`), etc. When documenting a module, `lpdoc` will use the assertions associated with the module interface to construct a textual description of this interface. In principle, only the exported predicates are documented, although any predicate can be included in the documentation by explicitly requesting it (see the documentation for the `doc/2` declaration). Judicious use of these assertions allows at the same time documenting the program code, documenting the external use of the module, and greatly improving the debugging process. The latter is possible because the assertions provide the compiler with information on the intended meaning or behaviour of the program (i.e., the specification) which can be checked at compile-time (by a suitable preprocessor/static analyzer) and/or at run-time (via checks inserted by a preprocessor).

Machine-readable comments are also declarations included in the source program but which contain additional information intended to be read by humans (i.e., this is an instantiation of the *literate programming* style of Knuth [Knu84]). Typical comments include title, author(s), bugs, changelog, etc. Judicious use of these comments allows enhancing at the same time the documentation of the program text and the manuals generated from it.

`lpdoc` requires these assertions and comments to be written using the `Ciao` system *assertion language*. A simple compatibility library is available in order to make it possible to compile programs documented using assertions and comments in traditional (constraint) logic programming systems which lack native support for them (see the `compatibility` directory in the `lpdoc` library). Using this library, such assertions and comments are simply ignored by the compiler. This compatibility library also allows compiling `lpdoc` itself under (C)LP systems other than the `Ciao` system under which it is developed.

2.7 Accessing on-line manuals

As mentioned previously, it is possible to generate on-line manuals automatically from the `.texic` files, essentially `.html`, `.info`, and `man` files. This is done by simply including the corresponding options in the list of `docformats` in the `SETTINGS.pl` file and typing `lpdoc all`. We now address the issue of how the different manuals can be read on-line.

2.7.1 Accessing html manuals

Once generated, the `.html` files can be viewed using any standard WWW browser, e.g., Firefox (a command `lpdoc htmlview` is available which, if there is an instance of a web browser running in the machine, will make that instance visit the manual in `html` format). To make these files publicly readable on the WWW, they should be copied into a directory visible by browsers running in other machines, such as `/home/clip/public_html/lpdoc_docs`, `/usr/home/httpd/htmldocs/lpdoc_docs`, etc. As mentioned before, this is easily done by setting the `docdir` variable in the `SETTINGS.pl` file to this directory and typing `lpdoc install`.

2.7.2 Accessing info manuals

Generated `.info` files are meant to be viewed by the `Emacs` editor or by the standalone `info` application, both publicly available from the GNU project sites. To view the a generated `info` file from `Emacs` manually (i.e., before it is installed in a common area), type `C-u M-x info`. This will prompt for an `info` file name. Input the name of the `info` file generated by `lpdoc` (`main.info`) and `Emacs` will open the manual in `info` mode.

There are several possibilities in order to install an `.info` file so that it is publicly available, i.e., so that it appears automatically with all other `info` manuals when starting `info` or typing `C-u M-x info` in `Emacs`:

- **Installation in the common info directory:**

- Move the `.info` file to the common info directory (typically `/usr/info`, `/usr/local/info`, ..). This can be done automatically by setting the `docdir` variable in the `SETTINGS.pl` file to this directory and typing `lpdoc install`.

Warning: if you are installing in an `info` directory that is not maintained automatically by `lpdoc`, make sure that you have not selected the `infoindex` option in `docformats`, since this will overwrite the existing `dir` file).
- Add an entry to the `info` index in that directory (normally a file in that directory called `dir`). The manual should appear as part of the normal set of manuals available when typing `M-x info` in Emacs or `info` in a shell. See the Emacs manual for details.
- **Installation in a different info directory:** you may want to place one or more manuals generated by `lpdoc` in their own directory. This has the advantage that `lpdoc` will maintain automatically an index for all the `lpdoc` generated manuals installed in that directory. In order for such manuals to appear when typing `M-x info` in Emacs or `info` in a shell there are two requirements:
 - This directory must contain a `dir` index. The first part of the process can all be done automatically by setting the `docdir` variable in the `SETTINGS.pl` file to this directory, including the `infoindex` option in `docformats`, and typing `lpdoc install`. This will install the `info` manual in directory `docdir` and update the `dir` file there. `lpdoc uninstall` does the opposite, eliminating also the manual from the index.
 - The directory must be added to the *info path list*. The easiest way to do this is to set the `INFOPATH` environment variable. For example, assuming that we are installing the `info` manual in `/home/clip/public_html/lpdoc_docs` and that `/usr/info` is the common `info` directory, for `csh` in `.cshrc`:

```
setenv INFOPATH /usr/info:/home/clip/public_html/lpdoc_docs
```

Adding the directory to the `info` path list can also be done within Emacs, by including the following line in the `.Emacs` file:

```
(defun add-info-path (newpath)
  (setq Info-default-directory-list
    (cons (expand-file-name newpath) Info-default-directory-list)))
(add-info-path "/home/clip/public_html/lpdoc_docs")
(add-info-path "/usr/info/")
```

However, this has the disadvantage that it will not be seen by the standalone `info` command.

Automatic, direct on-line access to the information contained in the `info` file (e.g., going automatically to predicate descriptions by clicking on predicate names in programs in an Emacs buffer) can be easily implemented via existing `.el` packages such as `word-help`, written by Jens T. Berger Thielemann (`jensthi@ifi.uio.no`). `word-help` may already be in your Emacs distribution, but for convenience the file `word-help.el` and a `word-help-setup.el` file, providing suitable initialization are included in the `lpdoc` library. A suitable interface for `word-help` is also provided by the `ciao.el` Emacs file that comes with the `Ciao` system distribution (i.e., if `ciao.el` is loaded it is not necessary to load or initialize `word-help`).

2.7.3 Accessing man manuals

The Unix `man` format manuals generated by `lpdoc` can be viewed using the Unix `man` command. In order for `man` to be able to locate the manuals, they should be copied to one of the subdirectories (e.g., `/usr/local/man/man1`) of one of the main `man` directories (in the previous case the main directory would be `/usr/local/man`). As usual, any directory can be used as a `man` main directory, provided it is included in the environment variable `MANPATH`. Again, this process can be performed automatically by setting the `docdir` variable in the `SETTINGS.pl` file to this directory and typing `lpdoc install`.

2.7.4 Putting it all together

A simple, powerful, and very convenient way to use the facilities provided by `lpdoc` for automatic installation of manuals in different formats is to install all manuals in all formats in the same directory `docdir`, and to choose a directory which is also accessible via `WWW`. After setting `docdir` to this directory in the `SETTINGS.pl` file, and selecting `infoindex` and `htmlindex` for the `docformats` variable, `lpdoc install/lpdoc uninstall` will install/uninstall all manuals in all the selected formats in this directory and create and maintain the corresponding `html` and `info` indices. Then, setting the environment variables as follows (e.g., for `cs`h in `.cshrc`):

```
setenv DOCDIR    /home/clip/public_html/lpdoc_docs
setenv INFOPATH /usr/local/info:${DOCDIR}
setenv MANPATH  ${DOCDIR}:${MANPATH}
```

Example files for inclusion in user's or common shell initialization files are included in the `lpdoc` library.

More complex setups can be accommodated, as, for example, installing different types of manuals in different directories. However, this currently requires changing the `docformats` and `docdir` variables and performing `lpdoc install` for each installation format/directory.

2.8 Some usage tips

This section contains additional suggestions on the use of `lpdoc`.

2.8.1 Ensuring Compatibility with All Supported Target Formats

One of the nice things about `lpdoc` is that it allows generating manuals in several formats which are quite different in nature. Because these formats each have widely different requirements it is sometimes a little tricky to get things to work successfully for all formats. The following recommendations are intended to help in achieving useful manuals in all formats:

- The best results are obtained when documenting code organized as a series of libraries, and with a well-designed module structure.
- `texinfo` supports only a limited number of indices. Thus, if you select too many indices in the `SETTINGS.pl` file you may exceed `texinfo`'s capacity (which it will signal by saying something like "No room for a new @write").
- The GNU `info` format requires all *nodes* (chapters, sections, etc.) to have different names. This is ensured by `lpdoc` for the automatically generated sections (by appending the module or file name to all section headings). However, care must be taken when writing section names manually to make them different. For example, use "lpdoc usage" instead of simply "Usage", which is much more likely to be used as a section name in another file being documented.
- Also due to a limitation of the `info` format, do not use `:`, `,`, or `--` in section, chapter, etc. headings.
- The character "`_`" in names may sometimes give problems in indices, since current versions of `texinfo` do not always handle it correctly.

2.8.2 Writing comments which document version/patch changes

When writing version comments (`:- doc(version(...), "...").`), it is useful to keep in mind that the text can often be used to include in the manual a list of improvements made to the software since the last time that it was distributed. For this to work well, the textual comments should describe the significance of the work done for the user. For example, it is more useful to write "added support for `pred` assertions" than "modifying file so `pred` case is also handled".

Sometimes one would like to write version comments which are internal, i.e., not meant to appear in the manual. This can easily be done with standard Prolog comments (which `lpdoc` will not read). An alternative and quite useful solution is to put such internal comments in *patch* changes (e.g., 1.1#2 to 1.1#3), and put the more general comments, which describe major changes to the user and should appear in the manual, in *version* changes (e.g., 1.1#2 to 1.2#0). Selecting the appropriate options in `lpdoc` then allows including in the manual the version changes but not the patch changes (which might on the other hand be included in an *internals manual*).

2.8.3 Documenting Libraries and/or Applications

As mentioned before, for each a `.pl` file, `lpdoc` tries to determine whether it is a library or the main file of an application, and documents it accordingly. Any combination of libraries and/or main files of applications can be used arbitrarily as components or main files of a `lpdoc` manual. Some typical combinations are:

- *Main file is a library, no components:* A manual of a simple library, which appears externally as a single module. The manual describes the purpose of the library and its interface.
- *Main file is an application, no components:* A manual of a simple application.
- *Main file is a library, components are also libraries:* This can be used for example for generating an *internals manual* of a library. The main file describes the purpose and use of the library, while the components describe the internal modules of the library.
- *Main file is an application, components are libraries:* This can be used similarly for generating an *internals manual* of an application. The main file describes the purpose and use of the application, while the components describe the internal modules which compose the application.
- *Main file is a (pseudo-)application, components are libraries:* A manual of a complex library made up of smaller libraries (for example, the `Prolog` library). The (pseudo-)application file contains the introductory material (title, version, etc.). Each chapter describes a particular library.
- *Main file is a (pseudo-)application, components are applications:* This can be used to generate a manual of a set of applications (e.g., a set of utilities). The (pseudo-)application file contains the introductory material (title, version, etc.). Each chapter describes a particular component application.

2.8.4 Documenting files which are not modules

Sometimes it is difficult for `lpdoc` to distinguish include files and Ciao packages from normal *user* files (i.e., normal code files but which are not modules). The distinction is important because the former are quite different in their form of use (they are loaded via `include/1` or `use_package/1` declarations instead of `ensure_loaded/1`) and effect (since they are included, they 'export' operators, declarations, etc.), and should typically be documented differently. There is a special `doc/2` declaration (`:- doc filetype, ...`) which provides a way of defining the intended use of the file. This declaration is normally not needed in modules, include files, or packages, but should be added in user files (i.e., those meant to be loaded using `ensure_loaded/1`). Adding this declaration will, for example, avoid spurious documentation of the declarations in the `assertions` package themselves when this package is included in a user file.

2.8.5 Splitting large documents into parts

As mentioned before, in `lpdoc` each documented file (each component) corresponds to a chapter in the generated manual. In large documents, it is sometimes convenient to build a super-structure of parts, each of which groups several chapters. There is a special value of the

second argument of the `:- doc(filetype,...)` declaration mentioned above designed for this purpose. The special *filetype* value `part` can be used to flag that the file in which it appears should be documented as the start of one of the major *parts in a large document*. In order to introduce such a part, a `.pl` file with a declaration `:- doc(filetype,part)` should be inserted in the sequence of files that make up the `components` variable of the `SETTINGS.pl` file at each point in which a major part starts. The `:- doc(title,...)` declaration of this file will be used as the part title, and the `:- doc(module,...)` declaration text will be used as the introduction to the part.

2.8.6 Documenting reexported predicates

Reexported predicates, i.e., predicates which are exported by a module `m1` but defined in another module `m2` which is used by `m1`, are normally not documented in the original module, but instead a simple reference is included to the module in which it is defined. This can be changed, so that the documentation is included in the original module, by using a `doc/2` declaration with `doinclude` in the first argument (see the `comments` library). This is often useful when documenting a library made of several components. For a simple user's manual, it is often sufficient to include in the `lpdoc SETTINGS.pl` file the principal module, which is the one which users will do a `use_module/1` of, in the manual. This module typically exports or reexports all the predicates which define the library's user interface. Note, however, that currently, due to limitations in the implementation, only the comments inside assertions (but not those in `doc/2` declarations) are included for reexported predicates.

2.8.7 Separating the documentation from the source file

Sometimes one would not like to include long introductory comments in the module itself but would rather have them in a different file. This can be done quite simply by using the `@include` command. For example, the following declaration:

```
:- doc(module,"@include{Intro.lpdoc}").
```

will include the contents of the file `Intro.lpdoc` as the module description.

Alternatively, sometimes one may want to generate the documentation from a completely different file. Assuming that the original module is `m1.pl`, this can be done by calling the module containing the documentation `m1_doc.pl`. This `m1_doc.pl` file is the one that will be included in the `lpdoc SETTINGS.pl` file, instead of `m1.pl`. `lpdoc` recognizes and treats such `_doc` files specially so that the name without the `_doc` part is used in the different parts of the documentation, in the same way as if the documentation were placed in file `m1`.

2.8.8 Generating auxiliary files (e.g. READMEs)

Note: significant parts of this are obsolete. They must be updated to describe `lpdoc` version 2.0.

Using `lpdoc` it is often possible to use a common source for documentation text which should appear in several places. For example, assume a file `INSTALLATION.lpdoc` contains text (with `lpdoc` formatting commands) describing an application. This text can be included in a section of the main file documentation as follows:

```
:- doc(module,"
    ...
    @section{Installation instructions}
    @include{INSTALLATION.lpdoc}
    ...
").
```

At the same time, this text can be used to generate a nicely formatted `INSTALLATION` file in `ascii`, which can perhaps be included in the top level of the source directory of the application. To this end, an `INSTALL.pl` file as follows can be constructed:

```
:- use_package([assertions]).
:- doc filetype, application. %% forces file to be documented as an application
:- doc(title, "Installation instructions").
:- doc(module, "@include{INSTALLATION.lpdoc}").
```

Then, the `ascii` `INSTALLATION` file can be generated by simply running `lpdoc ascii` in a directory with a `SETTINGS.pl` file where `MAIN` is set to `INSTALLATION.pl`.

2.9 Troubleshooting

These are some common errors which may be found using `lpdoc` and the usual fix:

- Sometimes, messages of the type:

```
gmake: *** No rule to make target 'myfile.texic', needed by
'main.texic'. Stop.
```

appear (i.e., in the case above when running `(g)make main.target`). Since `lpdoc` definitely knows how to make a `.texic` file given a `.pl` file, this means (in `make`'s language) that it *cannot find the corresponding .pl file* (`myfile.pl` in the case above). The usual reason for this is that there is no directory path to this file declared in the `SETTINGS.pl` file.

- Messages of the type:

```
! No room for a new @write .
```

while converting from `.texi` to `.dvi` (i.e., while running `tex`). These messages are `tex`'s way of saying that an internal area (typically for an index) is full. This is normally because more indices were selected in the `INDICES` variable of the `SETTINGS.pl` file than the maximum number supported by the installed version of `tex/ texinfo` installations, as mentioned in Section 2.2 [Generating a manual], page 15. The easiest fix is to reduce the number of indices generated. Alternatively, it may be possible to recompile your local `tex/ texinfo` installation with a higher number of indices.

- Missing links in `info` files (a section which exists in the printed document cannot be accessed in the on-line document) can be due to the presence of a colon (:), a comma (,), a double dash (--), or other such separators in a section name. Due to limitations of `info` section names cannot contain these symbols.
- Menu listings in `info` which *do not work* (i.e., the menu listings are there, but they cannot be followed): see if they are indented. In that case it is due to an `itemize` or `enumerate` which was not closed.

3 Documentation Mark-up Language and Declarations

Author(s): Manuel Hermenegildo.

This defines the admissible uses of the `doc/2` declaration (which is used mainly for adding machine readable comments to programs), the formatting commands which can be used in the text strings inside these comments, and some related properties and data types. These declarations are ignored by the compiler in the same way as classical comments. Thus, they can be used to document the program source in place of (or in combination with) the normal comments typically inserted in the code by programmers. However, because they are more structured and they are machine-readable, they can also be used to generate printed or on-line documentation automatically, using the `lpdoc` automatic documentation generator. These *textual comments* are meant to be complementary to the formal statements present in *assertions* (see the `assertions` library).

3.1 Usage and interface (comments)

- **Library usage:**

It is not necessary to use this library in user programs. The recommended procedure in order to make use of the `doc/2` declarations that this library defines is to include instead the `assertions` package, which provides efficient support for all assertion- and comment-related declarations, using one of the following declarations, as appropriate:

```
:- module(...,...,[assertions]).
:- use_package(assertions).
```

- **Exports:**

- *Predicates:*
`doc_id_type/3`.
- *Properties:*
`docstring/1`, `stringcommand/1`.
- *Regular Types:*
`version_descriptor/1`, `filetype/1`.

- **Other modules used:**

- *System library modules:*
`strings`.
- *Internal (engine) modules:*
`term_basic`, `arithmetic`, `atomic_basic`, `attributes`, `basic_props`, `basiccontrol`, `data_facts`, `exceptions`, `io_aux`, `io_basic`, `prolog_flags`, `streams_basic`, `system_info`, `term_compare`, `term_tying`, `hiord_rt`, `debugger_support`.

3.2 Documentation on exports (comments)

docstring/1:

PROPERTY

Defines the format of the character strings which can be used in machine readable comments (`doc/2` declarations) and assertions. These character strings can include certain *formatting commands*.

- All printable characters are admissible in documentation strings except “@”, “{,” and “}”. To produce these characters the following *escape sequences* should be used, respectively: @@, @{, and @}.
- In order to allow better formatting of on-line and printed manuals, in addition to normal text, certain formatting commands can be used within these strings. The syntax of all these commands is:

`@command`

(followed by either a space or { }), or

`@command{body}`

where *command* is the command name and *body* is the (possibly empty) command body.

The set of commands currently admitted can be found in the documentation for the predicate `stringcommand/1`.

Usage: `docstring(Text)`

- *Description:* `Text` is a *documentation string*.

stringcommand/1:

PROPERTY

Defines the set of structures which can result from parsing a formatting command admissible in comment strings inside assertions.

In order to make it possible to produce documentation in a wide variety of formats, the command set is kept small. The names of the commands are intended to be reminiscent of the commands used in the LaTeX text formatting system, except that “@” is used instead of “\.” Note that \ would need to be escaped in ISO-Prolog strings, which would make the source less readable (and, in any case, many ideas in LaTeX were taken from scribe, where the escape character was indeed @!).

The following are the currently admissible commands.

- **Formatting commands:**

The following commands are used to format certain words or sentences in a special font, build itemized lists, introduce sections, include examples, etc.

`@comment{text}`

text will be treated as a *comment* and will be ignored.

`@begin{itemize}`

marks the beginning of an *itemized list*. Each item should be in a separate paragraph and preceded by an `@item` command.

`@item`

marks the beginning of a new *item in an itemized list*.

`@end{itemize}`

marks the end of an itemized list.

`@begin{enumerate}`

marks the beginning of an *enumerated list*. Each item should be in a separate paragraph and preceded by an `@item` command.

`@end{enumerate}`

marks the end of an enumerated list.

`@begin{description}`

marks the beginning of a *description list*, i.e., a list of items and their description (this list describing the different allowable commands is in fact a description list). Each item should be in a separate paragraph and contained in an `@item{itemtext}` command.

- `@item{itemtext}`
marks the beginning of a *new item in description list*, and contains the header for the item.
- `@end{description}`
marks the end of a description list.
- `@begin{verbatim}`
marks the beginning of *fixed format text*, such as a program example. A fixed-width, typewriter-like font is used.
- `@end{verbatim}`
marks the end of formatted text.
- `@begin{cartouche}`
marks the beginning of a section of text in a *framed box*, with round corners.
- `@end{cartouche}`
marks the end of a section of text in a framed box.
- `@begin{alert}`
marks the beginning of a section of text in a *framed box*, for alert messages.
- `@end{alert}`
marks the end of the alert message.
- `@section{text}`
starts a *section* whose title is *text*. Due to a limitation of the `info` format, do not use `:` or `-` or `,` in section, subsection, title (chapter), etc. headings.
- `@subsection{text}`
starts a *subsection* whose title is *text*.
- `@footnote{text}`
places *text* in a *footnote*.
- `@hfill` introduces horizontal filling space (may be ignored in certain formats).
- `@bf{text}` *text* will be formatted in *bold face* or any other *strong face*.
- `@em{text}` *text* will be formatted in *italics face* or any other *emphasis face*.
- `@tt{text}` *text* will be formatted in a *fixed-width font* (i.e., *typewriter-like font*).
- `@key{key}`
key is the identifier of a *keyboard key* (i.e., a letter such as `a`, or a special key identifier such as `RET` or `DEL`) and will be formatted as `LFD` or in a fixed-width, typewriter-like font.
- `@sp{N}` generates *N blank lines* of space. Forces also a paragraph break.
- `@p` forces a *paragraph break*, in the same way as leaving one or more blank lines.
- `@noindent`
used at the beginning of a paragraph, states that the first line of the paragraph should not be indented. Useful, for example, for *avoiding indentation* on paragraphs that are continuations of other paragraphs, such as after a `verbatim`.

- **Indexing commands:**

The following commands are used to mark certain words or sentences in the text as concepts, names of predicates, libraries, files, etc. The use of these commands is highly recommended, since it results in very useful indices with little effort.

@index{*text*}

text will be printed in an emphasized font and will be included in the concept definition index (and also in the usage index). This command should be used for the first or *definitional* appearance(s) of a concept. The idea is that the concept definition index can be used to find the definition(s) of a concept.

@cindex{*text*}

text will be included in the concept index (and also in the usage index), but it is not printed. This is used in the same way as above, but allows sending to the index a different text than the one that is printed in the text.

@concept{*text*}

text will be printed (in a normal font). This command is used to mark that some text is a defined concept. In on-line manuals, a direct access to the corresponding concept definition may also be generated. A pointer to the place in which the @concept command occurs will appear only in the usage index.

@pred{*predname*}

predname (which should be in functor/arity form) is the name of a predicate and will be printed in fixed-width, typewriter-like font. This command should be used when referring to a predicate (or a property or type) in a documentation string. A reference will be included in the usage index. In on-line manuals, a direct access to the corresponding predicate definition may also be generated.

@op{*operatorname*}

operatorname (which should be in functor/arity form) is the name of an operator and will be printed in fixed-width, typewriter-like font. This command should be used when referring to an operator in a documentation string. A reference will be included in the usage index. In on-line manuals, a direct access to the corresponding operator definition may also be generated.

@decl{*declname*}

declname (which should be in functor/arity form) is the name of a declaration and will be printed in fixed-width, typewriter-like font. This command should be used when referring to a declaration in a documentation string. A reference will be included in the usage index. In on-line manuals, a direct access to the corresponding declaration definition may also be generated.

@lib{*libname*}

libname is the name of a library and will be printed in fixed-width, typewriter-like font. This command should be used when referring to a module or library in a documentation string. A reference will be included in the usage index. In on-line manuals, a direct access to the corresponding module definition may also be generated.

@apl{*aplname*}

aplname is the name of an application and will be printed in fixed-width, typewriter-like font. This command should be used when referring to an application in a documentation string. A reference will be included in the usage index.

`@file{filename}`

filename is the name of a file and will be printed in fixed-width, typewriter-like font. This command should be used when referring to a file in a documentation string. A reference will be included in the usage index.

`@var{varname}`

varname is the name of a variable and will be formatted in an emphasized font. Note that when referring to variable names in a `pred/1` declaration, such names should be enclosed in `@var` commands for the automatic documentation system to work correctly.

- **Referencing commands:**

The following commands are used to introduce *bibliographic citations* and *references to sections, urls, email addresses, etc.*

`@cite{keyword}`

keyword is the identifier of a *bibliographic entry*. Such entry is assumed to reside in one of a number of `bibtex` files (*.bib files*). A reference in brackets ([]) is inserted in the text and the full reference is included at the end, with all other references, in an appendix. For example, `@cite{iso-prolog}` will introduce a citation to a bibliographic entry whose keyword is `iso-prolog`. The list of bibliography files which will be searched for a match is determined by the `BIBFILES` variable of the `lpdoc SETTINGS` file.

`@ref{section title}`

introduces at point a reference to the section or node *section title*, where *section title* must be the exact *text* of the section title.

`@uref{URL}`

introduces at point a reference to the *Universal Resource Locator* (i.e., a *WWW address 'URL'*).

`@uref{text}{URL}`

introduces at point a reference to the Universal Resource Locator URL, associated to the text *text*.

`@email{address}`

introduces at point a reference to *email address address*.

`@email{text}{address}`

introduces at point a reference to the email address *address*, associated to the text *text*.

`@author{text}`

text will be printed (in a normal font). This command is used to reference the name of an author (not necessarily establishing the module authorship).

- **Date and Version:**

`@today` prints the current *date*.

`@version` prints the *version* of the current manual.

- **Mathematics:**

The following commands are used to format text in mathematical .

`@math{text}`

in-line typeset the *text* formula.

`@begin{displaymath}`

marks the beginning of a formula (useful for long formulas).

`@end{displaymath}`

marks the end of the (long) formula.

`@defmathcmd{cmd}{n}{def}`

defines the math command *cmd*, taking *n* arguments, which is expanded as *def*. Arguments are denoted as #1, ..., #n inside *def*.

`@defmathcmd{cmd}{def}`

defines the math command *cmd*, which is expanded as *def* (with no arguments).

- **Inclusion commands:**

The following commands are used to include code or strings of text as part of documentation. The latter may reside in external files or in the file being documented. The former must be part of the module being documented. There are also commands for inserting and scaling images.

`@include{filename}`

the contents of *filename* will be included in-line, as if they were part of the string. This is useful for common pieces of documentation or storing in a separate file long explanations if they are perceived to clutter the source file.

`@includeverbatim{filename}`

as above, but the contents of the file are included verbatim, i.e., commands within the file are not interpreted. This is useful for including code examples which may contain @'s, etc. Note that this only means that the file will be included as is. If you want the string to be represented in verbatim mode in the output, you must surround the `@includeverbatim{filename}` with `@begin{verbatim}` and `@end{verbatim}`.

`@includefact{factname}`

it is assumed that the file being documented contains a fact of the predicate *factname/1*, whose argument is a character string. The contents of that character string will be included in-line, as if they were part of the documentation string. This is useful for *sharing pieces of text* between the documentation and the running code. An example is the text which explains the *usage of a command* (options, etc.).

`@includedef{predname}`

it is assumed that the file being documented contains a definition for the predicate *predname*. The clauses defining this predicate will be included in-line, in verbatim mode, as if they were part of the documentation string.

`@image{epsfile}`

including an image at point, contained in file *epsfile*. The *image file* should be in *encapsulated postscript* format.

`@image{epsfile}{width}{height}` same as above, but *width* and *height* should be integers which provide a size (in points) to which the image will be scaled.

- **Accents and special characters:**

The following commands can be used to insert *accents* and *special characters*.

@' {o}	⇒ ò
@' {o}	⇒ ó
@~ {o}	⇒ ô
@. . {o}	⇒ ö
@" {o}	⇒ ö
@~ {o}	⇒ õ
@= {o}	⇒ õ
@. {o}	⇒ ò
@u {o}	⇒ ŏ
@v {o}	⇒ ŏ
@H {o}	⇒ Ǿ
@t {oo}	⇒ ȫ
@c {o}	⇒ ç
@d {o}	⇒ ç
@b {o}	⇒ ç
@oe	⇒ œ
@OE	⇒ Œ
@ae	⇒ æ
@AE	⇒ Æ
@aa	⇒ å
@AA	⇒ Å
@o	⇒ ø
@O	⇒ Ø
@l	⇒ ł
@L	⇒ Ł
@ss	⇒ ß
@?	⇒ ¿
@!	⇒ ¡
@i	⇒ ì
@j	⇒ ð
@copyright	⇒ ©
@iso	⇒ • ISO •
@bullet	⇒ •
@result	⇒ ⇒

Usage: stringcommand(CO)

- *Description:* CO is a structure denoting a command that is admissible in strings inside assertions.

version_descriptor/1: REGTYPE

A structure denoting a complete version description:

```
version_descriptor([]).
version_descriptor(version(Version,Date)) :-
    version_number(Version),
    ymd_date(Date).
version_descriptor(version(Version,Date,Time)) :-
    version_number(Version),
    ymd_date(Date),
    time_struct(Time).
```

Usage: `version_descriptor(Descriptor)`

- *Description:* `Descriptor` is a complete version descriptor.

filetype/1: REGTYPE

Intended uses of a file:

```
filetype(module).
filetype(user).
filetype(include).
filetype(package).
filetype(part).
```

Usage: `filetype(Type)`

- *Description:* `Type` describes the intended use of a file.

doc_id_type/3: PREDICATE

No further documentation available for this predicate.

3.3 Documentation on internals (comments)

doc/2: DECLARATION

This declaration provides one of the main means for adding *machine readable comments* to programs (the other one is adding *documentation strings* to assertions).

Usage 1: `:- doc(CommentType,TitleText).`

- *Description:* Provides a *title* for the module, library, or application. When generating documentation automatically, the text in `TitleText` will be used appropriately (e.g., in the cover page as document title or as chapter title if part of a larger document). This will also be used as a brief description of the manual in on-line indices. There should be at most one of these declarations per module.

- *Example:*

```
:- doc(title,"Documentation-Oriented Assertions").
```

- *The following properties should hold upon exit:*

`CommentType=title`

(= /2)

`TitleText` is a *documentation string*.

(docstring/1)

Usage 2: `:- doc(CommentType,SubtitleText).`

- *Description:* Provides a *subtitle*, an explanatory or alternate *title*. The subtitle will be displayed under the proper title.

- *Example:*

```
:- doc(title,"Dr. Strangelove").
:- doc(subtitle,"How I Learned to Stop Worrying and Love the Bomb").
```

- *The following properties should hold upon exit:*

```
CommentType=subtitle ( = /2)
SubtitleText is a documentation string. ( docstring/1)
```

Usage 3: `:- doc(CommentType,SubtitleText).`

- *Description:* Provides additional *subtitle* lines. This can be, e.g., an explanation of the application to add to the title, the address of the author(s) of the application, etc. When generating documentation automatically, the text in `SubtitleText` will be used accordingly. Several of these declarations can appear per module, which is useful for, e.g., multiple line addresses.

- *Example:*

```
:- doc(subtitle_extra,"A Reference Manual").
:- doc(subtitle_extra,"Technical Report 1/1.0").
```

- *The following properties should hold upon exit:*

```
CommentType=subtitle_extra ( = /2)
SubtitleText is a documentation string. ( docstring/1)
```

Usage 4: `:- doc(CommentType,SubtitleText).`

- *Description:* The name of the logo image for the manual.
- *The following properties should hold upon exit:*

```
CommentType=logo ( = /2)
SubtitleText is any term. ( term/1)
```

Usage 5: `:- doc(CommentType,AuthorText).`

- *Description:* Provides the *author*(s) of the module or application. If present, when generating documentation for the module automatically, the text in `AuthorText` will be placed in the corresponding chapter or front page. There can be more than one of these declarations per module. In order for author indexing to work properly, please use one author declaration per author. If more explanation is needed (who did what when, etc.) use an acknowledgements comment.

- *Example:*

```
:- doc(author,"Alan Robinson").
```

- *The following properties should hold upon exit:*

```
CommentType=author ( = /2)
AuthorText is a documentation string. ( docstring/1)
```

Usage 6: `:- doc(CommentType,Text).`

- *Description:* Provides the physical and electronic *address*, or any other contact information for the authors of the module or application.

- *Example:*

```
:- doc(address,"Syracuse University").
```

- *The following properties should hold upon exit:*

```
CommentType=address ( = /2)
Text is a documentation string. ( docstring/1)
```

Usage 7: `:- doc(CommentType,AckText).`

- *Description:* Provides *acknowledgements* for the module. If present, when generating documentation for the module automatically, the text in `AckText` will be placed in the corresponding chapter or section. There can be only one of these declarations per module.

- *Example:*

```
:- doc(ack,"Module was written by Alan, but others helped.).
```

- *The following properties should hold upon exit:*

```
CommentType=ack                                     (= /2)
AckText is a documentation string.                   ( docstring/1)
```

Usage 8: `:- doc(CommentType,CopyrightText).`

- *Description:* Provides a *copyright* text. This normally appears somewhere towards the beginning of a printed manual. There should be at most one of these declarations per module.

- *Example:*

```
:- doc(copyright,"Copyright © 2001 FSF.).
```

- *The following properties should hold upon exit:*

```
CommentType=copyright                               (= /2)
CopyrightText is a documentation string.              ( docstring/1)
```

Usage 9: `:- doc(CommentType,SummaryText).`

- *Description:* Provides a brief global explanation of the application or library. The text in `SummaryText` will be used as the *abstract* for the whole manual. There should be at most one of these declarations per module.

- *Example:*

```
:- doc(summary,"This is a @bf{very} important library.).
```

- *The following properties should hold upon exit:*

```
CommentType=summary                                 (= /2)
SummaryText is a documentation string.                ( docstring/1)
```

Usage 10: `:- doc(CommentType,CommentText).`

- *Description:* Provides the main comment text for the module or application. When generating documentation automatically, the text in `CommentText` will be used as the *introduction* or *main body* of the corresponding chapter or manual. There should be at most one of these declarations per module. `CommentText` may use **sections** if substructure is needed.

- *Example:*

```
:- doc(module,"This module is the @lib{comments} library.).
```

- *The following properties should hold upon exit:*

```
CommentType=module                                  (= /2)
CommentText is a documentation string.                ( docstring/1)
```

Usage 11: `:- doc(CommentType,CommentText).`

- *Description:* Provides additional comments text for a module or application. When generating documentation automatically, the text in `CommentText` will be used in one of the last sections or appendices of the corresponding chapter or manual. There should be at most one of these declarations per module. `CommentText` may use **subsections** if substructure is needed.

- *Example:*

```
:- doc(appendix,"Other module functionality...").
```

- *The following properties should hold upon exit:*

```
CommentType=appendix ( = /2)
CommentText is a documentation string. ( docstring/1)
```

Usage 12: `:- doc(CommentType,CommentText).`

- *Description:* Provides a description of how the library should be loaded. Normally, this information is gathered automatically when generating documentation automatically. This declaration is meant for use when the module needs to be treated in some special way. There should be at most one of these declarations per module.

- *Example:*

```
:- doc(usage,"Do not use: still in development!").
```

- *The following properties should hold upon exit:*

```
CommentType=usage ( = /2)
CommentText is a documentation string. ( docstring/1)
```

Usage 13: `:- doc(CommentType,Section).`

- *Description:* Insert a *program section* with name `Section`. Sectioning commands allow a structured separation of the program into parts. The division is only for documentation purposes, so visibility and scope of definitions is not affected by sectioning commands.

- *Example:*

```
:- doc(section,"Main Steps of the Algorithm").
```

- *The following properties should hold upon exit:*

```
CommentType=section ( = /2)
Section is a documentation string. ( docstring/1)
```

Usage 14: `:- doc(CommentType,SubSection).`

- *Description:* Insert a *program subsection* with name `SubSection` (see *program section* command for more details).

- *Example:*

```
:- doc(subsection,"Auxiliary Definitions").
```

- *The following properties should hold upon exit:*

```
CommentType=subsection ( = /2)
SubSection is a documentation string. ( docstring/1)
```

Usage 15: `:- doc(PredName,CommentText).`

- *Description:* Provides an introductory comment for a given predicate, function, property, type, etc., denoted by `PredName`. When generating documentation for the module automatically, the text in `Text` will be used as the introduction of the corresponding predicate/function/... description. There should be at most one of these declarations per predicate, function, property, or type.

- *Example:*

```
:- doc(doc/2,"This declaration provides one of the main
means for adding @concept{machine readable comments} to
programs. ").
```

- *The following properties should hold upon exit:*

`PredName` is a Name/Arity structure denoting a predicate name:

```
predname(P/A) :-
    atm(P),
    nnegint(A).
```

(predname/1)

CommentText is a *documentation string*.

(docstring/1)

Usage 16: :- doc(CommentType,CommentText).

- *Description:* Documents a known *bug* or *planned improvement* in the module or application. Several of these declarations can appear per module. When generating documentation automatically, the text in the Text fields will be used as items in an itemized list of module or application bugs.

- *Example:*

```
:- doc(bug,"Comment text still has to be written by user.").
```

- *The following properties should hold upon exit:*

CommentType=bug

(= /2)

CommentText is a *documentation string*.

(docstring/1)

Usage 17: :- doc(Version,CommentText).

- *Description:* Provides a means for keeping a *log of changes*. Version contains the *version number* and date corresponding to the change and CommentText an explanation of the change. Several of these declarations can appear per module. When generating documentation automatically, the texts in the different CommentText fields typically appear as items in an itemized list of changes. The emacs Ciao mode helps tracking version numbers by prompting for version comments when files are saved. This mode requires version comments to appear in reverse chronological order (i.e., the topmost comment should be the most recent one).

- *Example:*

```
:- doc(version(1*1+21,1998/04/18,15:05*01+'EST'), "Added some
missing comments. (Manuel Hermenegildo)").
```

- *The following properties should hold upon exit:*

Version is a complete version descriptor.

(version_descriptor/1)

CommentText is a *documentation string*.

(docstring/1)

Usage 18: :- doc(CommentType,VersionMaintenanceType).

- *Description:* Defines the type of version maintenance that should be performed by the emacs Ciao mode.

- *Example:*

```
:- doc(version_maintenance,dir('../version')).
```

Version control info is kept in directory ../version. See the definition of version_maintenance_type/1 for more information on the different version maintenance modes. See the documentation on the *emacs Ciao mode* in the Ciao manual for information on how to automatically insert version control doc/2 declarations in files. The version maintenance mode can also be set alternatively by inserting a comment such as:

```
%% Local Variables:
%% mode: CIAO
%% update-version-comments: "off"
%% End:
```

The lines above instruct emacs to put the buffer visiting the file in emacs Ciao mode and to turn version maintenance off. Setting the version maintenance mode in this way

has the disadvantage that `lpdoc` will not be aware of the type of version maintenance being performed (the lines above are comments for Prolog). However, this can be useful in fact for setting the *version maintenance mode for packages* and other files meant for inclusion in other files, since that way the settings will not affect the file in which the package is included.

- *The following properties should hold upon exit:*

```
CommentType=version_maintenance                (= /2)
VersionMaintenanceType a type of version maintenance for a file. (
version_maintenance_type/1)
```

Usage 19: `:- doc(CommentType,PredName).`

- *Description:* This is a special case that is used to control which predicates are included in the documentation. Normally, only exported predicates are documented. A declaration `:- doc(doinclude,PredName).` forces documentation for predicate (or type, property, function, ...) `PredName` to be included even if `PredName` is not exported. Also, if `PredName` is reexported from another module, a declaration `:- doc(doinclude,PredName).` will force the documentation for `PredName` to appear directly in this module.

- *Example:*

```
:- doc(doinclude,p/3).
```

- *The following properties should hold upon exit:*

```
CommentType=doinclude                          (= /2)
PredName is a Name/Arity structure denoting a predicate name:
    predname(P/A) :-
        atm(P),
        nnegint(A).
                                                    ( predname/1)
```

Usage 20: `:- doc(CommentType,PredName).`

- *Description:* A different usage which allows the second argument of `:- doc(doinclude,...)` to be a list of predicate names.
- *The following properties should hold upon exit:*

```
CommentType=doinclude                          (= /2)
PredName is a list of prednames.                ( list/2)
```

Usage 21: `:- doc(CommentType,PredName).`

- *Description:* This is similar to the previous usage but has the opposite effect: it signals that an exported predicate should *not* be included in the documentation.

- *Example:*

```
:- doc(hide,p/3).
```

- *The following properties should hold upon exit:*

```
CommentType=hide                              (= /2)
PredName is a Name/Arity structure denoting a predicate name:
    predname(P/A) :-
        atm(P),
        nnegint(A).
                                                    ( predname/1)
```

Usage 22: `:- doc(CommentType,PredName).`

- *Description:* A different usage which allows the second argument of `:- doc(hide, ...)` to be a list of predicate names.

- *The following properties should hold upon exit:*

`CommentType=hide` (= /2)
`PredName` is a list of `prednames`. (list/2)

Usage 23: `:- doc(CommentType,FileType)`.

- *Description:* Provides a way of defining the intended use of the file. This use is normally easily inferred from the contents of the file itself, and therefore such a declaration is in general not needed. The exception is the special case of include files and Ciao packages, which are typically indistinguishable from normal *user* files (i.e., files which are not modules), but are however quite different in their form of use (they are loaded via `include/1` or `use_package/1` declarations instead of `ensure_loaded/1`) and effect (since they are included, they 'export' operators, declarations, etc.). Typically, it is assumed by default that files which are not modules will be used as include files or packages. Thus, a `doc/2` declaration of this kind strictly only needs to be added to user-type files.

Example:

```
:- doc(filetype,user).
```

There is another special case: the value `part`. This *filetype* is used to flag files which serve as introductions to boundaries between major *parts in large documents*. See Section 2.8.5 [Splitting large documents into parts], page 22 for details.

- *The following properties should hold upon exit:*

`CommentType=filetype` (= /2)
`FileType` describes the intended use of a file. (filetype/1)

Usage 24: `:- doc(CommentType,FileName)`.

- *Description:* Do not document anything that comes from a file whose name (after taking away the path and the suffix) is `FileName`. This is used for example when documenting packages to avoid the documenter from including documentation of certain other packages which the package being documented uses.

- *Example:*

```
:- doc(nodoc,assertions).
```

- *The following properties should hold upon exit:*

`CommentType=nodoc` (= /2)
`FileName` is an atom. (atm/1)

version_number/1:

REGTYPE

`Version` is a structure denoting a complete version number (major version, minor version, and patch number):

```
version_number(Major*Minor+Patch) :-
    int(Major),
    int(Minor),
    int(Patch).
```

Usage: `version_number(Version)`

- *Description:* `Version` is a complete version number

ymd_date/1: REGTYPE

A Year/Month/Day structure denoting a date:

```
ymd_date(Y/M/D) :-
    int(Y),
    int(M),
    int(D).
```

Usage: `ymd_date(Date)`

- *Description:* `Date` is a Year/Month/Day structure denoting a date.

time_struct/1: REGTYPE

A structure containing time information:

```
time_struct(Hours:Minutes*Seconds+TimeZone) :-
    int(Hours),
    int(Minutes),
    int(Seconds),
    atm(TimeZone).
```

Usage: `time_struct(Time)`

- *Description:* `Time` contains time information.

version_maintenance_type/1: REGTYPE

Possible kinds of version maintenance for a file:

```
version_maintenance_type(on).
version_maintenance_type(off).
version_maintenance_type(dir(Path)) :-
    atm(Path).
```

- **on:** version numbering is maintained locally in the file in which the declaration occurs, i.e., an independent version number is kept for this file and the current version is given by the most recent `doc(version(...),...)` declaration.
- **off:** no version numbering maintained.
- **dir(Path):** version numbering is maintained (globally) in directory `Path`. This is useful for maintaining a common global version for an application which involves several files.

The automatic maintenance of version numbers is typically done by the Ciao `emacs` mode.

Usage: `version_maintenance_type(Type)`

- *Description:* `Type` a type of version maintenance for a file.

4 The Ciao assertion package

Author(s): Manuel Hermenegildo, Francisco Bueno, German Puebla.

The `assertions` package adds a number of new declaration definitions and new operator definitions which allow including program assertions in user programs. Such assertions can be used to describe predicates, properties, modules, applications, etc. These descriptions can contain formal specifications (such as sets of preconditions, post-conditions, or descriptions of computations) as well as machine-readable textual comments.

This module is part of the `assertions` library. It defines the basic code-related assertions, i.e., those intended to be used mainly by compilation-related tools, such as the static analyzer or the run-time test generator.

Giving specifications for predicates and other program elements is the main functionality documented here. The exact syntax of comments is described in the autodocumenter (`lpdoc` [Knu84,Her99]) manual, although some support for adding machine-readable comments in assertions is also mentioned here.

There are two kinds of assertions: predicate assertions and program point assertions. All predicate assertions are currently placed as directives in the source code, i.e., preceded by “:-”. Program point assertions are placed as goals in clause bodies.

4.1 More info

The facilities provided by the library are documented in the description of its component modules. This documentation is intended to provide information only at a “reference manual” level. For a more tutorial introduction to the subject and some more examples please see [PBH00]. The assertion language implemented in this library is modeled after this design document, although, due to implementation issues, it may differ in some details. The purpose of this manual is to document precisely what the implementation of the library supports at any given point in time.

4.2 Some attention points

- **Formatting commands within text strings:** many of the predicates defined in these modules include arguments intended for providing textual information. This includes titles, descriptions, comments, etc. The type of this argument is a character string. In order for the automatic generation of documentation to work correctly, this character string should adhere to certain conventions. See the description of the `docstring/1` type/grammar for details.
- **Referring to variables:** In order for the automatic documentation system to work correctly, variable names (for example, when referring to arguments in the head patterns of *pred* declarations) must be surrounded by an `@var` command. For example, `@var{VariableName}` should be used for referring to the variable “VariableName”, which will appear then formatted as follows: `VariableName`. See the description of the `docstring/1` type/grammar for details.

4.3 Usage and interface (assertions_doc)

- **Library usage:**

The recommended procedure in order to make use of assertions in user programs is to include the `assertions` syntax library, using one of the following declarations, as appropriate:

```
:- module(...,[assertions]).
:- use_package([assertions]).
```

- **Exports:**

- *Predicates:*
`check/1`, `trust/1`, `true/1`, `false/1`.

- **New operators defined:**

```
=>/2 [975,xfx], ::/2 [978,xfx], decl/1 [1150,fx], decl/2 [1150,xfx], pred/1 [1150,fx], pred/2 [1150,xfx], prop/1 [1150,fx], prop/2 [1150,xfx], modedef/1 [1150,fx], calls/1 [1150,fx], calls/2 [1150,xfx], success/1 [1150,fx], success/2 [1150,xfx], test/1 [1150,fx], test/2 [1150,xfx], texec/1 [1150,fx], texec/2 [1150,xfx], comp/1 [1150,fx], comp/2 [1150,xfx], entry/1 [1150,fx], exit/1 [1150,fx], exit/2 [1150,xfx].
```

- **New declarations defined:**

```
pred/1, pred/2, texec/1, texec/2, calls/1, calls/2, success/1, success/2, test/1, test/2, comp/1, comp/2, prop/1, prop/2, entry/1, exit/1, exit/2, modedef/1, decl/1, decl/2, doc/2, comment/2.
```

- **Other modules used:**

- *System library modules:*
`assertions/assertions_props`.
- *Internal (engine) modules:*
`term_basic`, `arithmetic`, `atomic_basic`, `attributes`, `basic_props`, `basiccontrol`, `data_facts`, `exceptions`, `io_aux`, `io_basic`, `prolog_flags`, `streams_basic`, `system_info`, `term_compare`, `term_tying`, `hiord_rt`, `debugger_support`.

4.4 Documentation on new declarations (assertions_doc)

`pred/1`:

DECLARATION

This assertion provides information on a predicate. The body of the assertion (its only argument) contains properties or comments in the formats defined by `assrt_body/1`.

More than one of these assertions may appear per predicate, in which case each one represents a possible “mode” of use (usage) of the predicate. The exact scope of the usage is defined by the properties given for calls in the body of each assertion (which should thus distinguish the different usages intended). All of them together cover all possible modes of usage.

For example, the following assertions describe (all the and the only) modes of usage of predicate `length/2` (see lists):

```
:- pred length(L,N) : list * var => list * integer
# "Computes the length of L."
:- pred length(L,N) : var * integer => list * integer
# "Outputs L of length N."
:- pred length(L,N) : list * integer => list * integer
```

```
# "Checks that L is of length N."
```

Usage: :- `pred AssertionBody`.

– *The following properties should hold at call time:*

`AssertionBody` is an assertion body. (`assrt_body/1`)

pred/2: DECLARATION

This assertion is similar to a `pred/1` assertion but it is explicitly qualified. Non-qualified `pred/1` assertions are assumed the qualifier `check`.

Usage: :- `AssertionStatus pred AssertionBody`.

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is an assertion body. (`assrt_body/1`)

texec/1: DECLARATION

This assertion is similar to a `calls/1` assertion but it is used to provide input data and execution commands to the unit-test driver.

Usage: :- `texec AssertionBody`.

– *The following properties should hold at call time:*

`AssertionBody` is a call assertion body. (`c_assrt_body/1`)

texec/2: DECLARATION

This assertion is similar to a `texec/1` assertion but it is explicitly qualified with an assertion status. Non-qualified `texec/1` assertions are assumed to have `check` status.

Usage: :- `AssertionStatus texec AssertionBody`.

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is a call assertion body. (`c_assrt_body/1`)

calls/1: DECLARATION

This assertion is similar to a `pred/1` assertion but it only provides information about the calls to a predicate. If one or several calls assertions are given they are understood to describe all possible calls to the predicate.

For example, the following assertion describes all possible calls to predicate `is/2` (see `arithmetic`):

```
:- calls is(term,arithexpression).
```

Usage: :- `calls AssertionBody`.

– *The following properties should hold at call time:*

`AssertionBody` is a call assertion body. (`c_assrt_body/1`)

calls/2: DECLARATION

This assertion is similar to a `calls/1` assertion but it is explicitly qualified with an assertion status. Non-qualified `calls/1` assertions are assumed to have `check` status.

Usage: `:- AssertionStatus calls AssertionBody.`

- *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is a call assertion body. (`c_assrt_body/1`)

success/1: DECLARATION

This assertion is similar to a `pred/1` assertion but it only provides information about the answers to a predicate. The described answers might be conditioned to a particular way of calling the predicate.

For example, the following assertion specifies the answers of the `length/2` predicate *if* it is called as in the first mode of usage above (note that the previous `pred` assertion already conveys such information, however it also compelled the predicate calls, while the `success` assertion does not):

```
:- success length(L,N) : list * var => list * integer.
```

Usage: `:- success AssertionBody.`

- *The following properties should hold at call time:*

`AssertionBody` is a predicate assertion body. (`s_assrt_body/1`)

success/2: DECLARATION

`success` assertion This assertion is similar to a `success/1` assertion but it is explicitly qualified with an assertion status. The status of non-qualified `success/1` assertions is assumed to be `check`.

Usage: `:- AssertionStatus success AssertionBody.`

- *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is a predicate assertion body. (`s_assrt_body/1`)

test/1: DECLARATION

This assertion is similar to a `success` assertion but it specifies a concrete test case to be run in order verify (partially) that the predicate is working as expected. For example, the following test will verify that the `length` predicate works well for the particular list given:

```
:- test length(L,N) : ( L = [1,2,5,2] ) => ( N = 4 ).
```

Usage: `:- test AssertionBody.`

- *The following properties should hold at call time:*

`AssertionBody` is a predicate assertion body. (`s_assrt_body/1`)

test/2: DECLARATION

This assertion is similar to a `test/1` assertion but it is explicitly qualified with an assertion status. Non-qualified `test/1` assertions are assumed to have `check` status. In this context, `check` means that the test should be executed when the developer runs the test battery.

Usage: `:- AssertionStatus test AssertionBody.`

- *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)
`AssertionBody` is a predicate assertion body. (`s_assrt_body/1`)

comp/1: DECLARATION

This assertion is similar to a `pred/1` assertion but it only provides information about the global execution properties of a predicate (note that such kind of information is also conveyed by `pred` assertions). The described properties might be conditioned to a particular way of calling the predicate.

For example, the following assertion specifies that the computation of `append/3` (see `lists`) will not fail *if* it is called as described (but does not compel the predicate to be called that way):

```
:- comp append(Xs,Ys,Zs) : var * var * var + not_fail.
```

Usage: `:- comp AssertionBody.`

- *The following properties should hold at call time:*

`AssertionBody` is a `comp` assertion body. (`g_assrt_body/1`)

comp/2: DECLARATION

This assertion is similar to a `comp/1` assertion but it is explicitly qualified. Non-qualified `comp/1` assertions are assumed the qualifier `check`.

Usage: `:- AssertionStatus comp AssertionBody.`

- *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)
`AssertionBody` is a `comp` assertion body. (`g_assrt_body/1`)

prop/1: DECLARATION

This assertion is similar to a `pred/1` assertion but it flags that the predicate being documented is also a “property.”

Properties are standard predicates, but which are *guaranteed to terminate for any possible instantiation state of their argument(s)*, do not perform side-effects which may interfere with the program behaviour, and do not further instantiate their arguments or add new constraints.

Provided the above holds, properties can thus be safely used as run-time checks. The program transformation used in `ciaopp` for run-time checking guarantees the third requirement. It also performs some basic checks on properties which in most cases are enough for the second requirement. However, it is the user’s responsibility to guarantee termination of the properties defined. (See also Chapter 6 [Declaring regular types], page 57 for some considerations applicable to writing properties.)

The set of properties is thus a strict subset of the set of predicates. Note that properties can be used to describe characteristics of arguments in assertions and they can also be executed (called) as any other predicates.

Usage: `:- prop AssertionBody.`

- *The following properties should hold at call time:*

`AssertionBody` is an assertion body. (`assrt_body/1`)

prop/2: DECLARATION

This assertion is similar to a `prop/1` assertion but it is explicitly qualified. Non-qualified `prop/1` assertions are assumed the qualifier `check`.

Usage: `:- AssertionStatus prop AssertionBody.`

- *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is an assertion body. (`assrt_body/1`)

entry/1: DECLARATION

This assertion provides information about the *external* calls to a predicate. It is identical syntactically to a `calls/1` assertion. However, they describe only external calls, i.e., calls to the exported predicates of a module from outside the module, or calls to the predicates in a non-modular file from other files (or the user).

These assertions are *trusted* by the compiler. As a result, if their descriptions are erroneous they can introduce bugs in programs. Thus, `entry/1` assertions should be written with care.

An important use of these assertions is in providing information to the compiler which it may not be able to infer from the program. The main use is in providing information on the ways in which exported predicates of a module will be called from outside the module. This will greatly improve the precision of the analyzer, which otherwise has to assume that the arguments that exported predicates receive are any arbitrary term.

Usage: `:- entry AssertionBody.`

- *The following properties should hold at call time:*

`AssertionBody` is a call assertion body. (`c_assrt_body/1`)

exit/1: DECLARATION

This type of assertion provides information about the answers that an (exported) predicate provides for *external* calls. It is identical syntactically to a `success/1` assertion. However, it describes only external answers, i.e., answers to the exported predicates of a module from outside the module, or answers to the predicates in a non-modular file from other files (or the user). The described answers may be conditioned to a particular way of calling the predicate. E.g.:

```
:- exit length(L,N) : list * var => list * integer.
```

Usage: `:- exit AssertionBody.`

- *The following properties should hold at call time:*

`AssertionBody` is a predicate assertion body. (`s_assrt_body/1`)

exit/2: DECLARATION

exit assertion This assertion is similar to an `exit/1` assertion but it is explicitly qualified with an assertion status. Non-qualified `exit/1` assertions are assumed the qualifier `check`.

Usage: `:- AssertionStatus exit AssertionBody.`

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is a predicate assertion body. (`s_assrt_body/1`)

modedef/1: DECLARATION

This assertion is used to define modes. A mode defines in a compact way a set of call and success properties. Once defined, modes can be applied to predicate arguments in assertions. The meaning of this application is that the call and success properties defined by the mode hold for the argument to which the mode is applied. Thus, a mode is conceptually a “property macro”.

The syntax of mode definitions is similar to that of `pred` declarations. For example, the following set of assertions:

```
:- modedef +A : nonvar(A) # "A is bound upon predicate entry."
```

```
:- pred p(+A,B) : integer(A) => ground(B).
```

is equivalent to:

```
:- pred p(A,B) : (nonvar(A),integer(A)) => ground(B)
   # "A is bound upon predicate entry."
```

Usage: `:- modedef AssertionBody.`

– *The following properties should hold at call time:*

`AssertionBody` is an assertion body. (`assrt_body/1`)

decl/1: DECLARATION

This assertion is similar to a `pred/1` assertion but it is used for declarations instead than for predicates.

Usage: `:- decl AssertionBody.`

– *The following properties should hold at call time:*

`AssertionBody` is an assertion body. (`assrt_body/1`)

decl/2: DECLARATION

This assertion is similar to a `decl/1` assertion but it is explicitly qualified. Non-qualified `decl/1` assertions are assumed the qualifier `check`.

Usage: `:- AssertionStatus decl AssertionBody.`

– *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is an assertion body. (`assrt_body/1`)

doc/2: DECLARATION

Usage: `:- doc(Pred,Comment).`

- *Description:* Documentation . This assertion provides a text `Comment` for a given predicate `Pred`.
- *The following properties should hold at call time:*

`Pred` is a head pattern. (`head_pattern/1`)

`Comment` is a text comment with admissible documentation commands. The usual formatting commands that are applicable in comment strings are defined by `stringcommand/1`. See the lpdoc manual for documentation on comments. (`docstring/1`)

comment/2: DECLARATION

Usage: `:- comment(Pred,Comment).`

- *Description:* An alias for `doc/2` (deprecated, for compatibility with older versions).
- *The following properties should hold at call time:*

`Pred` is a head pattern. (`head_pattern/1`)

`Comment` is a text comment with admissible documentation commands. The usual formatting commands that are applicable in comment strings are defined by `stringcommand/1`. See the lpdoc manual for documentation on comments. (`docstring/1`)

4.5 Documentation on exports (`assertions_doc`)

check/1: PREDICATE

Usage: `check(PropertyConjunction)`

- *Description:* This assertion provides information on a clause program point (position in the body of a clause). Calls to a `check/1` assertion can appear in the body of a clause in any place where a literal can normally appear. The property defined by `PropertyConjunction` should hold in all the run-time stores corresponding to that program point. See also Chapter 12 [Run-time checking of assertions], page 103.
- *The following properties should hold at call time:*

`PropertyConjunction` is either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. The first argument of each such term is a variable which appears as a head argument. (`property_conjunction/1`)

trust/1: PREDICATE

Usage: `trust(PropertyConjunction)`

- *Description:* This assertion also provides information on a clause program point. It is identical syntactically to a `check/1` assertion. However, the properties stated are not taken as something to be checked but are instead *trusted* by the compiler. While the compiler may in some cases detect an inconsistency between a `trust/1` assertion and the program, in all other cases the information given in the assertion will be taken to be true. As a result, if these assertions are erroneous they can introduce bugs in programs. Thus, `trust/1` assertions should be written with care.

An important use of these assertions is in providing information to the compiler which it may not be able to infer from the program (either because the information is not present or because the analyzer being used is not precise enough). In particular, providing information on external predicates which may not be accessible at the time of compiling the module can greatly improve the precision of the analyzer. This can be easily done with trust assertion.

- *The following properties should hold at call time:*

`PropertyConjunction` is either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. The first argument of each such term is a variable which appears as a head argument. (`property_conjunction/1`)

true/1:

PREDICATE

Usage: `true(PropertyConjunction)`

- *Description:* This assertion is identical syntactically to a `check/1` assertion. However, the properties stated have been proved to hold by the analyzer. Thus, these assertions often represent the analyzer output.
- *The following properties should hold at call time:*

`PropertyConjunction` is either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. The first argument of each such term is a variable which appears as a head argument. (`property_conjunction/1`)

false/1:

PREDICATE

Usage: `false(PropertyConjunction)`

- *Description:* This assertion is identical syntactically to a `check/1` assertion. However, the properties stated have been proved not to hold by the analyzer. Thus, these assertions often represent the analyzer output.
- *The following properties should hold at call time:*

`PropertyConjunction` is either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. The first argument of each such term is a variable which appears as a head argument. (`property_conjunction/1`)

5 Types and properties related to assertions

Author(s): Manuel Hermenegildo.

This module is part of the `assertions` library. It provides the formal definition of the syntax of several forms of assertions and describes their meaning. It does so by defining types and properties related to the assertions themselves. The text describes, for example, the overall fields which are admissible in the bodies of assertions, where properties can be used inside these bodies, how to combine properties for a given predicate argument (e.g., conjunctions), etc. and provides some examples.

5.1 Usage and interface (`assertions_props`)

- **Library usage:**
`:- use_module(library(assertions_props)).`
- **Exports:**
 - *Properties:*
`head_pattern/1, nobody/1, docstring/1.`
 - *Regular Types:*
`assrt_body/1, complex_arg_property/1, property_conjunction/1, property_starterm/1, complex_goal_property/1, dictionary/1, c_assrt_body/1, s_assrt_body/1, g_assrt_body/1, assrt_status/1, assrt_type/1, predfunctor/1, propfunctor/1.`
- **Other modules used:**
 - *Internal (engine) modules:*
`term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol, data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic, system_info, term_compare, term_typing, hiord_rt, debugger_support.`

5.2 Documentation on exports (`assertions_props`)

assrt_body/1: REGTYPE

This predicate defines the different types of syntax admissible in the bodies of `pred/1`, `decl/1`, etc. assertions. Such a body is of the form:

$$\text{Pr} [:: \text{DP}] [:\text{ CP}] [=> \text{AP}] [+ \text{GP}] [\# \text{CO}]$$

where (fields between [...] are optional):

- `Pr` is a head pattern (`head_pattern/1`) which describes the predicate or property and possibly gives some implicit call/answer information.
- `DP` is a (possibly empty) complex argument property (`complex_arg_property/1`) which expresses properties which are compatible with the predicate, i.e., instantiations made by the predicate are *compatible* with the properties in the sense that applying the property at any point would not make it fail.
- `CP` is a (possibly empty) complex argument property (`complex_arg_property/1`) which applies to the *calls* to the predicate.

- AP is a (possibly empty) complex argument property (`complex_arg_property/1`) which applies to the *answers* to the predicate (if the predicate succeeds). These only apply if the (possibly empty) properties given for calls in the assertion hold.
- GP is a (possibly empty) complex goal property (`complex_goal_property/1`) which applies to the *whole execution* of a call to the predicate. These only apply if the (possibly empty) properties given for calls in the assertion hold.
- CO is a comment string (`docstring/1`). This comment only applies if the (possibly empty) properties given for calls in the assertion hold. The usual formatting commands that are applicable in comment strings can be used (see `stringcommand/1`). See the lpdoc manual for documentation on assertion comments.

Usage: `assrt_body(X)`

- *Description:* X is an assertion body.

head_pattern/1:

PROPERTY

A head pattern can be a predicate name (functor/arity) (`predname/1`) or a term. Thus, both `p/3` and `p(A,B,C)` are valid head patterns. In the case in which the head pattern is a term, each argument of such a term can be:

- A variable. This is useful in order to be able to refer to the corresponding argument positions by name within properties and in comments. Thus, `p(Input,Parameter,Output)` is a valid head pattern.
- A variable, as above, but preceded by a “ mode.” This mode determines in a compact way certain call or answer properties. For example, the head pattern `p(Input,+Parameter,Output)` is valid, as long as `+/1` is declared as a mode.

Acceptable

modes

are documented in `library(basicmodes)` and `library(isomodes)`. User defined modes are documented in `modedef/1`.

- Any term. In this case this term determines the instantiation state of the corresponding argument position of the predicate calls to which the assertion applies.
- A ground term preceded by a “ mode.” The ground term determines a property of the corresponding argument. The mode determines if it applies to the calls and/or the successes. The actual property referred to is that given by the term but with one more argument added at the beginning, which is a new variable which, in a rewriting of the head pattern, appears at the argument position occupied by the term. For example, the head pattern `p(Input,+list(int),Output)` is valid for mode `+/1` defined in `library(isomodes)`, and equivalent in this case to having the head pattern `p(Input,A,Output)` and stating that the property `list(A,int)` holds for the calls of the predicate.
- Any term preceded by a “ mode.” In this case, only one variable is admitted, it has to be the first argument of the mode, and it represents the argument position. I.e., it plays the role of the new variable mentioned above. Thus, no rewriting of the head pattern is performed in this case. For example, the head pattern `p(Input,+(Parameter,list(int)),Output)` is valid for mode `+/2` defined in `library(isomodes)`, and equivalent in this case to having the head pattern `p(Input,Parameter,Output)` and stating that the property `list(Parameter,int)` holds for the calls of the predicate.

Usage: `head_pattern(Pr)`

- *Description:* Pr is a head pattern.

complex_arg_property/1: REGTYPE

`complex_arg_property(Props)`

`Props` is a (possibly empty) complex argument property. Such properties can appear in two formats, which are defined by `property_conjunction/1` and `property_starterm/1` respectively. The two formats can be mixed provided they are not in the same field of an assertion. I.e., the following is a valid assertion:

```
:- pred foo(X,Y) : nonvar * var => (ground(X),ground(Y)).
```

Usage: `complex_arg_property(Props)`

- *Description:* `Props` is a (possibly empty) complex argument property

property_conjunction/1: REGTYPE

This type defines the first, unabridged format in which properties can be expressed in the bodies of assertions. It is essentially a conjunction of properties which refer to variables. The following is an example of a complex property in this format:

- `(integer(X),list(Y,integer))`: `X` has the property `integer/1` and `Y` has the property `list/2`, with second argument `integer`.

Usage: `property_conjunction(Props)`

- *Description:* `Props` is either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. The first argument of each such term is a variable which appears as a head argument.

property_starterm/1: REGTYPE

This type defines a second, compact format in which properties can be expressed in the bodies of assertions. A `property_starterm/1` is a term whose main functor is `*/2` and, when it appears in an assertion, the number of terms joined by `*/2` is exactly the arity of the predicate it refers to. A similar series of properties as in `property_conjunction/1` appears, but the arity of each property is one less: the argument position to which they refer (first argument) is left out and determined by the position of the property in the `property_starterm/1`. The idea is that each element of the `*/2` term corresponds to a head argument position. Several properties can be assigned to each argument position by grouping them in curly brackets. The following is an example of a complex property in this format:

- `integer * list(integer)`: the first argument of the procedure (or function, or ...) has the property `integer/1` and the second one has the property `list/2`, with second argument `integer`.
- `{integer,var} * list(integer)`: the first argument of the procedure (or function, or ...) has the properties `integer/1` and `var/1` and the second one has the property `list/2`, with second argument `integer`.

Usage: `property_starterm(Props)`

- *Description:* `Props` is either a term or several terms separated by `*/2`. The main functor of each of those terms corresponds to that of the definition of a property, and the arity should be one less than in the definition of such property. All arguments of each such term are ground.

complex_goal_property/1: REGTYPE

`complex_goal_property(Props)`

`Props` is a (possibly empty) complex goal property. Such properties can be either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. Such properties apply to all executions of all goals of the predicate which comply with the assertion in which the `Props` appear.

The arguments of the terms in `Props` are implicitly augmented with a first argument which corresponds to a goal of the predicate of the assertion in which the `Props` appear. For example, the assertion

```
:- comp var(A) + not_further_inst(A).
```

has property `not_further_inst/1` as goal property, and establishes that in all executions of `var(A)` it should hold that `not_further_inst(var(A),A)`.

Usage: `complex_goal_property(Props)`

- *Description:* `Props` is either a term or a *conjunction* of terms. The main functor and arity of each of those terms corresponds to the definition of a property. A first implicit argument in such terms identifies goals to which the properties apply.

nabody/1: PROPERTY

Usage: `nabody(ABody)`

- *Description:* `ABody` is a normalized assertion body.

dictionary/1: REGTYPE

Usage: `dictionary(D)`

- *Description:* `D` is a dictionary of variable names.

c_assrt_body/1: REGTYPE

This predicate defines the different types of syntax admissible in the bodies of `call/1`, `entry/1`, etc. assertions. The following are admissible:

```
Pr : CP [# C0]
```

where (fields between [...] are optional):

- `CP` is a (possibly empty) complex argument property (`complex_arg_property/1`) which applies to the *calls* to the predicate.
- `C0` is a comment string (`docstring/1`). This comment only applies if the (possibly empty) properties given for calls in the assertion hold. The usual formatting commands that are applicable in comment strings can be used (see `stringcommand/1`).

The format of the different parts of the assertion body are given by `n_assrt_body/5` and its auxiliary types.

Usage: `c_assrt_body(X)`

- *Description:* `X` is a call assertion body.

s_assrt_body/1: REGTYPE

This predicate defines the different types of syntax admissible in the bodies of `pred/1`, `func/1`, etc. assertions. The following are admissible:

```
Pr : CP => AP # CO
Pr : CP => AP
Pr => AP # CO
Pr => AP
```

where:

- `Pr` is a head pattern (`head_pattern/1`) which describes the predicate or property and possibly gives some implicit call/answer information.
- `CP` is a (possibly empty) complex argument property (`complex_arg_property/1`) which applies to the *calls* to the predicate.
- `AP` is a (possibly empty) complex argument property (`complex_arg_property/1`) which applies to the *answers* to the predicate (if the predicate succeeds). These only apply if the (possibly empty) properties given for calls in the assertion hold.
- `CO` is a comment string (`docstring/1`). This comment only applies if the (possibly empty) properties given for calls in the assertion hold. The usual formatting commands that are applicable in comment strings can be used (see `stringcommand/1`).

The format of the different parts of the assertion body are given by `n_assrt_body/5` and its auxiliary types.

Usage: `s_assrt_body(X)`

- *Description:* `X` is a predicate assertion body.

g_assrt_body/1: REGTYPE

This predicate defines the different types of syntax admissible in the bodies of `comp/1` assertions. The following are admissible:

```
Pr : CP + GP # CO
Pr : CP + GP
Pr + GP # CO
Pr + GP
```

where:

- `Pr` is a head pattern (`head_pattern/1`) which describes the predicate or property and possibly gives some implicit call/answer information.
- `CP` is a (possibly empty) complex argument property (`complex_arg_property/1`) which applies to the *calls* to the predicate.
- `GP` contains (possibly empty) complex goal property (`complex_goal_property/1`) which applies to the *whole execution* of a call to the predicate. These only apply if the (possibly empty) properties given for calls in the assertion hold.
- `CO` is a comment string (`docstring/1`). This comment only applies if the (possibly empty) properties given for calls in the assertion hold. The usual formatting commands that are applicable in comment strings can be used (see `stringcommand/1`).

The format of the different parts of the assertion body are given by `n_assrt_body/5` and its auxiliary types.

Usage: `g_assrt_body(X)`

- *Description:* `X` is a comp assertion body.

assrt_status/1: REGTYPE

The types of assertion status. They have the same meaning as the program-point assertions, and are as follows:

```
assrt_status(true).
assrt_status(false).
assrt_status(check).
assrt_status(checked).
assrt_status(trust).
```

Usage: `assrt_status(X)`

- *Description:* `X` is an acceptable status for an assertion.

assrt_type/1: REGTYPE

The admissible kinds of assertions:

```
assrt_type(pred).
assrt_type(prop).
assrt_type(decl).
assrt_type(func).
assrt_type(calls).
assrt_type(success).
assrt_type(comp).
assrt_type(entry).
assrt_type(exit).
assrt_type(test).
assrt_type(texec).
assrt_type(modedef).
```

Usage: `assrt_type(X)`

- *Description:* `X` is an admissible kind of assertion.

predfunctor/1: REGTYPE

Usage: `predfunctor(X)`

- *Description:* `X` is a type of assertion which defines a predicate.

propfunctor/1: REGTYPE

Usage: `propfunctor(X)`

- *Description:* `X` is a type of assertion which defines a *property*.

docstring/1: PROPERTY

Usage: `docstring(String)`

- *Description:* `String` is a text comment with admissible documentation commands. The usual formatting commands that are applicable in comment strings are defined by `stringcommand/1`. See the `lpdoc` manual for documentation on comments.

6 Declaring regular types

Author(s): Manuel Hermenegildo, Pedro López, Francisco Bueno.

This library package adds declarations and new operator definitions which provide simple syntactic sugar to write regular type definitions in source code. Regular types are just properties which have the additional characteristic of being regular types (`basic_props:regtype/1`), defined below.

For example, this library package allows writing:

```
:- regtype tree(X) # "X is a tree."
```

instead of the more cumbersome:

```
:- prop tree(X) + regtype # "X is a tree."
```

Regular types can be used as properties to describe predicates and play an essential role in program debugging (see the Ciao Prolog preprocessor (`ciaopp`) manual).

In this chapter we explain some general considerations worth taking into account when writing properties in general, not just regular types.

6.1 Defining properties

Given the classes of assertions in the Ciao assertion language, there are two fundamental classes of properties. Properties used in assertions which refer to execution states (i.e., `calls/1`, `success/1`, and the like) are called *properties of execution states*. Properties used in assertions related to computations (i.e., `comp/1`) are called *properties of computations*. Different considerations apply when writing a property of the former or of the later kind.

Consider a definition of the predicate `string_concat/3` which concatenates two character strings (represented as lists of ASCII codes):

```
string_concat([],L,L).
string_concat([X|Xs],L,[X|NL]):- string_concat(Xs,L,NL).
```

Assume that we would like to state in an assertion that each argument “is a list of integers.” However, we must decide which one of the following two possibilities we mean exactly: “the argument is *instantiated* to a list of integers” (let us call this property `instantiated_to_intlist/1`), or “if any part of the argument is instantiated, this instantiation must be compatible with the argument being a list of integers” (we will call this property `compatible_with_intlist/1`). For example, `instantiated_to_intlist/1` should be true for the terms `[]` and `[1,2]`, but should not for `X`, `[a,2]`, and `[X,2]`. In turn, `compatible_with_intlist/1` should be true for `[]`, `X`, `[1,2]`, and `[X,2]`, but should not be for `[X|1]`, `[a,2]`, and `1`. We refer to properties such as `instantiated_to_intlist/1` above as *instantiation properties* and to those such as `compatible_with_intlist/1` as *compatibility properties* (corresponding to the traditional notions of “instantiation types” and “compatibility types”).

It turns out that both of these notions are quite useful in practice. In the example above, we probably would like to use `compatible_with_intlist/1` to state that on success of `string_concat/3` all three argument must be compatible with lists of integers in an assertion like:

```
:- success string_concat(A,B,C) => ( compatible_with_intlist(A),
                                   compatible_with_intlist(B),
                                   compatible_with_intlist(C) ).
```

With this assertion, no error will be flagged for a call to `string_concat/3` such as `string_concat([20],L,R)`, which on success produces the resulting atom `string_concat([20],L,[20|L])`, but a call `string_concat([],a,R)` would indeed flag an error.

On the other hand, and assuming that we are running on a Prolog system, we would probably like to use `instantiated_to_intlist/1` for `sumlist/2` as follows:

```
:- calls sumlist(L,N) : instantiated_to_intlist(L).

sumlist([],0).
sumlist([X|R],S) :- sumlist(R,PS), S is PS+X.
```

to describe the type of calls for which the program has been designed, i.e., those in which the first argument of `sumlist/2` is indeed a list of integers.

The property `instantiated_to_intlist/1` might be written as in the following (Prolog) definition:

```
:- prop instantiated_to_intlist/1.

instantiated_to_intlist(X) :-
    nonvar(X), instantiated_to_intlist_aux(X).

instantiated_to_intlist_aux([]).
instantiated_to_intlist_aux([X|T]) :-
    integer(X), instantiated_to_intlist(T).
```

(Recall that the Prolog builtin `integer/1` itself implements an instantiation check, failing if called with a variable as the argument.)

The property `compatible_with_intlist/1` might in turn be written as follows (also in Prolog):

```
:- prop compatible_with_intlist/1.

compatible_with_intlist(X) :- var(X).
compatible_with_intlist(X) :-
    nonvar(X), compatible_with_intlist_aux(X).

compatible_with_intlist_aux([]).
compatible_with_intlist_aux([X|T]) :-
    int_compat(X), compatible_with_intlist(T).

int_compat(X) :- var(X).
int_compat(X) :- nonvar(X), integer(X).
```

Note that these predicates meet the criteria for being properties and thus the `prop/1` declaration is correct.

Ensuring that a property meets the criteria for “not affecting the computation” can sometimes make its coding somewhat tedious. In some ways, one would like to be able to write simply:

```
intlist([]).
intlist([X|R]) :- int(X), intlist(R).
```

(Incidentally, note that the above definition, provided that it suits the requirements for being a property and that `int/1` is a regular type, meets the criteria for being a regular type. Thus, it could be declared `:- regtype intlist/1`.)

But note that (independently of the definition of `int/1`) the definition above is not the correct instantiation check, since it would succeed for a call such as `intlist(X)`. In fact, it is not strictly correct as a compatibility property either, because, while it would fail or succeed as expected, it would perform instantiations (e.g., if called with `intlist(X)` it would bind `X` to `[]`). In practice, it is convenient to provide some run-time support to aid in this task.

The run-time support of the Ciao system (see Chapter 12 [Run-time checking of assertions], page 103) ensures that the execution of properties is performed in such a way that properties written as above can be used directly as instantiation checks. Thus, writing:

```
:- calls sumlist(L,N) : intlist(L).
```

has the desired effect. Also, the same properties can often be used as compatibility checks by writing them in the assertions as `compat(Property)` (`basic_props:compat/1`). Thus, writing:

```
:- success string_concat(A,B,C) => ( compat(intlist(A)),
                                     compat(intlist(B)),
                                     compat(intlist(C)) ).
```

also has the desired effect.

As a general rule, the properties that can be used directly for checking for compatibility should be *downwards closed*, i.e., once they hold they will keep on holding in every state accessible in forwards execution. There are certain predicates which are inherently *instantiation* checks and should not be used as *compatibility* properties nor appear in the definition of a property that is to be used with `compat`. Examples of such predicates (for Prolog) are `==`, `ground`, `nonvar`, `integer`, `atom`, `>`, etc. as they require a certain instantiation degree of their arguments in order to succeed.

In contrast with properties of execution states, *properties of computations* refer to the entire execution of the call(s) that the assertion relates to. One such property is, for example, `not_fail/1` (note that although it has been used as in `:- comp append(Xs,Ys,Zs) + not_fail`, it is in fact read as `not_fail(append(Xs,Ys,Zs))`; see `assertions_props:complex_goal_property/1`). For this property, which should be interpreted as “execution of the predicate either succeeds at least once or loops,” we can use the following predicate `not_fail/1` for run-time checking:

```
not_fail(Goal):-
    if( call(Goal),
        true,           %% then
        warning(Goal) ). %% else
```

where the `warning/1` (library) predicate simply prints a warning message.

In this simple case, implementation of the predicate is not very difficult using the (non-standard) `if/3` builtin predicate present in many Prolog systems.

However, it is not so easy to code predicates which check other properties of the computation and we may in general need to program a meta-interpreter for this purpose.

6.2 Usage and interface (`regtypes_doc`)

- **Library usage:**

```
:- use_package(regtypes).
or
:- module(...,[regtypes]).
```
- **New operators defined:**

```
regtype/1 [1150,fx], regtype/2 [1150,xfx].
```
- **New declarations defined:**

```
regtype/1, regtype/2.
```
- **Other modules used:**
 - *System library modules:*

```
assertions/assertions_props.
```
 - *Internal (engine) modules:*

```
term_basic.
```

6.3 Documentation on new declarations (`regtypes_doc`)

`regtype/1`:

DECLARATION

This assertion is similar to a prop assertion but it flags that the property being documented is also a “regular type.” Regular types are properties whose definitions are *regular programs* (see below). This allows for example checking whether it is in the class of types supported by the regular type checking and inference modules.

A regular program is defined by a set of clauses, each of the form:

$$p(x, v_1, \dots, v_n) \text{ :- } \text{body}_1, \dots, \text{body}_k.$$

where:

1. x is a term whose variables (which are called *term variables*) are unique, i.e., it is not allowed to introduce equality constraints between the variables of x .
For example, $p(f(X, Y)) \text{ :- } \dots$ is valid, but $p(f(X, X)) \text{ :- } \dots$ is not.
2. in all clauses defining $p/n+1$ the terms x do not unify except maybe for one single clause in which x is a variable.
3. $n \geq 0$ and p/n is a *parametric type functor* (whereas the predicate defined by the clauses is $p/n+1$).
4. v_1, \dots, v_n are unique variables, which are called *parametric variables*.
5. Each body_i is of the form:
 1. $t(z)$ where z is one of the *term variables* and t is a *regular type expression*;
 2. $q(y, t_1, \dots, t_m)$ where $m \geq 0$, q/m is a *parametric type functor*, not in the set of functors `=/2, ^/2, ./3`.
 t_1, \dots, t_m are *regular type expressions*, and y is a *term variable*.
6. Each term variable occurs at most once in the clause’s body (and should be as the first argument of a literal).

A *regular type expression* is either a parametric variable or a parametric type functor applied to some of the parametric variables.

A parametric type functor is a regular type, defined by a regular program, or a basic type. Basic types are defined in Chapter 7 [Basic data types and properties], page 61.

The set of regular types is thus a well defined subset of the set of properties. Note that types can be used to describe characteristics of arguments in assertions and they can also be executed (called) as any other predicates.

Usage: `:- regtype AssertionBody`.

- *The following properties should hold at call time:*

`AssertionBody` is an assertion body. (`assrt_body/1`)

`regtype/2`:

DECLARATION

This assertion is similar to a `regtype/1` assertion but it is explicitly qualified. Non-qualified `regtype/1` assertions are assumed the qualifier `check`. Note that checking regular type definitions should be done with the `ciaopp` preprocessor.

Usage: `:- AssertionStatus regtype AssertionBody`.

- *The following properties should hold at call time:*

`AssertionStatus` is an acceptable status for an assertion. (`assrt_status/1`)

`AssertionBody` is an assertion body. (`assrt_body/1`)

7 Basic data types and properties

Author(s): Daniel Cabeza, Manuel Hermenegildo.

This library contains the set of basic properties used by the builtin predicates, and which constitute the basic data types and properties of the language. They can be used both as type testing builtins within programs (by calling them explicitly) and as properties in assertions.

7.1 Usage and interface (basic_props)

- **Library usage:**

These predicates are builtin in Ciao, so nothing special has to be done to use them.

- **Exports:**

- *Properties:*

member/2, compat/2, inst/2, iso/1, deprecated/1, not_further_inst/2, sideff/2, regtype/1, native/1, native/2, no_rtcheck/1, eval/1, equiv/2, bind_ins/1, error_free/1, memo/1, filter/2, pe_type/1.

- *Regular Types:*

term/1, int/1, nnegint/1, flt/1, num/1, atm/1, struct/1, gnd/1, gndstr/1, constant/1, callable/1, operator_specifier/1, list/1, list/2, nlist/2, sequence/2, sequence_or_list/2, character_code/1, string/1, num_code/1, predname/1, atm_or_atm_list/1, flag_values/1.

- **Other modules used:**

- *System library modules:*

assertions/native_props, terms_check.

- *Internal (engine) modules:*

term_basic, arithmetic, atomic_basic, attributes, basiccontrol, data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic, system_info, term_compare, term_typing, hiord_rt, debugger_support.

7.2 Documentation on exports (basic_props)

term/1:

The most general type (includes all possible terms).

REGTYPE

General properties: term(X)

- *The following properties hold globally:*

term(X) is side-effect free.

(sideff/2)

term(X)

- *The following properties hold globally:*

term(X) is evaluable at compile-time.

(eval/1)

term(X)

- *The following properties hold globally:*

term(X) is equivalent to true.

(equiv/2)

Usage: term(X)

- *Description:* X is any term.
- *The following properties hold globally:*
This predicate is understood natively by CiaoPP. (native/1)

int/1: REGTYPE

The type of integers. The range of integers is $[-2^{2147483616}, 2^{2147483616})$. Thus for all practical purposes, the range of integers can be considered infinite.

General properties: `int(T)`

- *The following properties hold globally:*
`int(T)` is side-effect free. (sideeff/2)

`int(T)`

- *If the following properties hold at call time:*
T is currently a term which is not a free variable. (nonvar/1)
then the following properties hold globally:
`int(T)` is evaluable at compile-time. (eval/1)
All calls of the form `int(T)` are deterministic. (is_det/1)

`int(T)`

- *The following properties hold upon exit:*
T is an integer. (int/1)
- *The following properties hold globally:*
Indicates the type of test that a predicate performs. Required by the nonfailure analysis. (test_type/2)

Usage: `int(T)`

- *Description:* T is an integer.
- *The following properties hold globally:*
This predicate is understood natively by CiaoPP. (native/1)

nnegint/1: REGTYPE

The type of non-negative integers, i.e., natural numbers.

General properties: `nnegint(T)`

- *The following properties hold globally:*
`nnegint(T)` is side-effect free. (sideeff/2)

`nnegint(T)`

- *If the following properties hold at call time:*
T is currently a term which is not a free variable. (nonvar/1)
then the following properties hold globally:
`nnegint(T)` is evaluable at compile-time. (eval/1)

`nnegint(T)`

- *The following properties hold upon exit:*
T is a non-negative integer. (nnegint/1)

- *The following properties hold globally:*

Indicates the type of test that a predicate performs. Required by the nonfailure analysis. (`test_type/2`)

Usage: `nnegint(T)`

- *Description:* `T` is a non-negative integer.

- *The following properties hold globally:*

This predicate is understood natively by CiaoPP. (`native/1`)

flt/1:

REGTYPE

The type of floating-point numbers. The range of floats is the one provided by the C `double` type, typically `[4.9e-324, 1.8e+308]` (plus or minus). There are also three special values: Infinity, either positive or negative, represented as `1.0e1000` and `-1.0e1000`; and Not-a-number, which arises as the result of indeterminate operations, represented as `0.Nan`

General properties: `flt(T)`

- *The following properties hold globally:*

`flt(T)` is side-effect free. (`sideff/2`)

`flt(T)`

- *If the following properties hold at call time:*

`T` is currently a term which is not a free variable. (`nonvar/1`)

then the following properties hold globally:

`flt(T)` is evaluable at compile-time. (`eval/1`)

All calls of the form `flt(T)` are deterministic. (`is_det/1`)

`flt(T)`

- *The following properties hold upon exit:*

`T` is a float. (`flt/1`)

- *The following properties hold globally:*

Indicates the type of test that a predicate performs. Required by the nonfailure analysis. (`test_type/2`)

Usage: `flt(T)`

- *Description:* `T` is a float.

- *The following properties hold globally:*

This predicate is understood natively by CiaoPP. (`native/1`)

num/1:

REGTYPE

The type of numbers, that is, integer or floating-point.

General properties: `num(T)`

- *The following properties hold globally:*

`num(T)` is side-effect free. (`sideff/2`)

`num(T)` is binding insensitive. (`bind_ins/1`)

`num(T)`

- *If the following properties hold at call time:*
T is currently a term which is not a free variable. (nonvar/1)
then the following properties hold globally:
num(T) is evaluable at compile-time. (eval/1)
All calls of the form num(T) are deterministic. (is_det/1)

num(T)

- *The following properties hold upon exit:*
T is a number. (num/1)
- *The following properties hold globally:*
Indicates the type of test that a predicate performs. Required by the nonfailure analysis. (test_type/2)

Usage: num(T)

- *Description:* T is a number.
- *The following properties hold globally:*
This predicate is understood natively by CiaoPP. (native/1)

atm/1: REGTYPE

The type of atoms, or non-numeric constants. The size of atoms is unbound.

General properties: atm(T)

- *The following properties hold globally:*
atm(T) is side-effect free. (sideff/2)

atm(T)

- *If the following properties hold at call time:*
T is currently a term which is not a free variable. (nonvar/1)
then the following properties hold globally:
atm(T) is evaluable at compile-time. (eval/1)
All calls of the form atm(T) are deterministic. (is_det/1)

atm(T)

- *The following properties hold upon exit:*
T is an atom. (atm/1)
- *The following properties hold globally:*
Indicates the type of test that a predicate performs. Required by the nonfailure analysis. (test_type/2)

Usage: atm(T)

- *Description:* T is an atom.
- *The following properties hold globally:*
This predicate is understood natively by CiaoPP. (native/1)

struct/1: REGTYPE

The type of compound terms, or terms with non-zeroary functors. By now there is a limit of 255 arguments.

General properties: struct(T)

- *The following properties hold globally:*
struct(T) is side-effect free. (sideeff/2)
- struct(T)**
- *If the following properties hold at call time:*
T is currently a term which is not a free variable. (nonvar/1)
then the following properties hold globally:
struct(T) is evaluable at compile-time. (eval/1)
- struct(T)**
- *The following properties hold upon exit:*
T is a compound term. (struct/1)
- Usage: struct(T)**
- *Description:* T is a compound term.
 - *The following properties hold globally:*
This predicate is understood natively by CiaoPP. (native/1)
-
- gnd/1:** REGTYPE
- The type of all terms without variables.
- General properties: gnd(T)**
- *The following properties hold globally:*
gnd(T) is side-effect free. (sideeff/2)
- gnd(T)**
- *If the following properties hold at call time:*
T is currently ground (it contains no variables). (ground/1)
then the following properties hold globally:
gnd(T) is evaluable at compile-time. (eval/1)
All calls of the form **gnd(T)** are deterministic. (is_det/1)
- gnd(T)**
- *The following properties hold upon exit:*
T is ground. (gnd/1)
 - *The following properties hold globally:*
Indicates the type of test that a predicate performs. Required by the nonfailure analysis. (test_type/2)
- Usage: gnd(T)**
- *Description:* T is ground.
 - *The following properties hold globally:*
This predicate is understood natively by CiaoPP. (native/1)
-
- gndstr/1:** REGTYPE
- General properties: gndstr(T)**
- *The following properties hold globally:*
gndstr(T) is side-effect free. (sideeff/2)

`gndstr(T)`

- *If the following properties hold at call time:*
T is currently ground (it contains no variables). (`ground/1`)
then the following properties hold globally:
`gndstr(T)` is evaluable at compile-time. (`eval/1`)
All calls of the form `gndstr(T)` are deterministic. (`is_det/1`)

`gndstr(T)`

- *The following properties hold upon exit:*
T is a ground compound term. (`gndstr/1`)

Usage: `gndstr(T)`

- *Description:* T is a ground compound term.
- *The following properties hold globally:*
 This predicate is understood natively by CiaoPP. (`native/1`)

constant/1:

REGTYPE

General properties: `constant(T)`

- *The following properties hold globally:*
`constant(T)` is side-effect free. (`sideff/2`)

`constant(T)`

- *If the following properties hold at call time:*
T is currently a term which is not a free variable. (`nonvar/1`)
then the following properties hold globally:
`constant(T)` is evaluable at compile-time. (`eval/1`)
All calls of the form `constant(T)` are deterministic. (`is_det/1`)

`constant(T)`

- *The following properties hold upon exit:*
T is an atomic term (an atom or a number). (`constant/1`)

Usage: `constant(T)`

- *Description:* T is an atomic term (an atom or a number).

callable/1:

REGTYPE

General properties: `callable(T)`

- *The following properties hold globally:*
`callable(T)` is side-effect free. (`sideff/2`)

`callable(T)`

- *If the following properties hold at call time:*
T is currently a term which is not a free variable. (`nonvar/1`)
then the following properties hold globally:
`callable(T)` is evaluable at compile-time. (`eval/1`)
All calls of the form `callable(T)` are deterministic. (`is_det/1`)

`callable(T)`

– *The following properties hold upon exit:*

T is currently a term which is not a free variable. (nonvar/1)

Usage: callable(T)

– *Description:* T is a term which represents a goal, i.e., an atom or a structure.

operator_specifier/1:

REGTYPE

The type and associativity of an operator is described by the following mnemonic atoms:

xfx	Infix, non-associative: it is a requirement that both of the two subexpressions which are the arguments of the operator must be of <i>lower</i> precedence than the operator itself.
xfy	Infix, right-associative: only the first (left-hand) subexpression must be of lower precedence; the right-hand subexpression can be of the <i>same</i> precedence as the main operator.
yfx	Infix, left-associative: same as above, but the other way around.
fx	Prefix, non-associative: the subexpression must be of <i>lower</i> precedence than the operator.
fy	Prefix, associative: the subexpression can be of the <i>same</i> precedence as the operator.
xf	Postfix, non-associative: the subexpression must be of <i>lower</i> precedence than the operator.
yf	Postfix, associative: the subexpression can be of the <i>same</i> precedence as the operator.

General properties: operator_specifier(X)

– *The following properties hold globally:*

operator_specifier(X) is side-effect free. (sideeff/2)

operator_specifier(X)

– *If the following properties hold at call time:*

X is currently a term which is not a free variable. (nonvar/1)

then the following properties hold globally:

operator_specifier(X) is evaluable at compile-time. (eval/1)

All calls of the form operator_specifier(X) are deterministic. (is_det/1)

Goal operator_specifier(X) produces 7 solutions. (relations/2)

operator_specifier(T)

– *The following properties hold upon exit:*

T specifies the type and associativity of an operator. (operator_specifier/1)

Usage: operator_specifier(X)

– *Description:* X specifies the type and associativity of an operator.

list/1:

REGTYPE

A list is formed with successive applications of the functor '.'/2, and its end is the atom []. Defined as

```
list([]).
list([_1|L]) :-
    list(L).
```

General properties: list(L)

- *The following properties hold globally:*

list(L) is side-effect free. (sideff/2)

list(L)

- *If the following properties hold at call time:*

L is currently ground (it contains no variables). (ground/1)

then the following properties hold globally:

list(L) is evaluable at compile-time. (eval/1)

All calls of the form list(L) are deterministic. (is_det/1)

list(T)

- *The following properties hold upon exit:*

T is a list. (list/1)

Usage: list(L)

- *Description:* L is a list.

list/2:

REGTYPE

```
list(L,T)
```

L is a list, and for all its elements, T holds.

Meta-predicate with arguments: list(?, (pred 1)).

General properties: list(L,T)

- *The following properties hold globally:*

list(L,T) is side-effect free. (sideff/2)

list(L,T)

- *If the following properties hold at call time:*

L is currently ground (it contains no variables). (ground/1)

T is currently ground (it contains no variables). (ground/1)

then the following properties hold globally:

list(L,T) is evaluable at compile-time. (eval/1)

list(X,T)

- *The following properties hold upon exit:*

X is a list. (list/1)

Usage: list(L,T)

- *Description:* L is a list of Ts.

nlist/2:

REGTYPE

Meta-predicate with arguments: nlist(?, (pred 1)).

General properties: nlist(L,T)

– *The following properties hold globally:*

`nlist(L,T)` is side-effect free. (`sideff/2`)

`nlist(L,T)`

– *If the following properties hold at call time:*

L is currently ground (it contains no variables). (`ground/1`)

T is currently ground (it contains no variables). (`ground/1`)

then the following properties hold globally:

`nlist(L,T)` is evaluable at compile-time. (`eval/1`)

`nlist(X,T)`

– *The following properties hold upon exit:*

X is any term. (`term/1`)

Usage: `nlist(L,T)`

– *Description:* L is T or a nested list of Ts. Note that if T is term, this type is equivalent to term, this fact explain why we do not have a `nlist/1` type

member/2:

PROPERTY

General properties: `member(X,L)`

– *The following properties hold globally:*

`member(X,L)` is side-effect free. (`sideff/2`)

`member(X,L)` is binding insensitive. (`bind_ins/1`)

`member(X,L)`

– *If the following properties hold at call time:*

L is a list. (`list/1`)

then the following properties hold globally:

`member(X,L)` is evaluable at compile-time. (`eval/1`)

`member(_X,L)`

– *The following properties hold upon exit:*

L is a list. (`list/1`)

`member(X,L)`

– *If the following properties hold at call time:*

L is currently ground (it contains no variables). (`ground/1`)

then the following properties hold upon exit:

X is currently ground (it contains no variables). (`ground/1`)

Usage: `member(X,L)`

– *Description:* X is an element of L.

sequence/2:

REGTYPE

A sequence is formed with zero, one or more occurrences of the operator `' , ' / 2`. For example, `a, b, c` is a sequence of three atoms, `a` is a sequence of one atom.

Meta-predicate with arguments: `sequence(?, (pred 1))`.

General properties: `sequence(S,T)`

<ul style="list-style-type: none"> – <i>The following properties hold globally:</i> <code>sequence(S,T)</code> is side-effect free. (<code>sideff/2</code>) 	
<code>sequence(S,T)</code>	
<ul style="list-style-type: none"> – <i>If the following properties hold at call time:</i> <code>S</code> is currently ground (it contains no variables). (<code>ground/1</code>) <code>T</code> is currently ground (it contains no variables). (<code>ground/1</code>) <i>then the following properties hold globally:</i> <code>sequence(S,T)</code> is evaluable at compile-time. (<code>eval/1</code>) 	
<code>sequence(E,T)</code>	
<ul style="list-style-type: none"> – <i>The following properties hold upon exit:</i> <code>E</code> is currently a term which is not a free variable. (<code>nonvar/1</code>) <code>T</code> is currently ground (it contains no variables). (<code>ground/1</code>) 	
Usage: <code>sequence(S,T)</code>	
<ul style="list-style-type: none"> – <i>Description:</i> <code>S</code> is a sequence of <code>Ts</code>. 	
sequence_or_list/2:	REGTYPE
<i>Meta-predicate</i> with arguments: <code>sequence_or_list(?,(pred 1))</code> .	
General properties: <code>sequence_or_list(S,T)</code>	
<ul style="list-style-type: none"> – <i>The following properties hold globally:</i> <code>sequence_or_list(S,T)</code> is side-effect free. (<code>sideff/2</code>) 	
<code>sequence_or_list(S,T)</code>	
<ul style="list-style-type: none"> – <i>If the following properties hold at call time:</i> <code>S</code> is currently ground (it contains no variables). (<code>ground/1</code>) <code>T</code> is currently ground (it contains no variables). (<code>ground/1</code>) <i>then the following properties hold globally:</i> <code>sequence_or_list(S,T)</code> is evaluable at compile-time. (<code>eval/1</code>) 	
<code>sequence_or_list(E,T)</code>	
<ul style="list-style-type: none"> – <i>The following properties hold upon exit:</i> <code>E</code> is currently a term which is not a free variable. (<code>nonvar/1</code>) <code>T</code> is currently ground (it contains no variables). (<code>ground/1</code>) 	
Usage: <code>sequence_or_list(S,T)</code>	
<ul style="list-style-type: none"> – <i>Description:</i> <code>S</code> is a sequence or list of <code>Ts</code>. 	
character_code/1:	REGTYPE
General properties: <code>character_code(T)</code>	
<ul style="list-style-type: none"> – <i>The following properties hold globally:</i> <code>character_code(T)</code> is side-effect free. (<code>sideff/2</code>) 	
<code>character_code(T)</code>	
<ul style="list-style-type: none"> – <i>If the following properties hold at call time:</i> <code>T</code> is currently a term which is not a free variable. (<code>nonvar/1</code>) <i>then the following properties hold globally:</i> <code>character_code(T)</code> is evaluable at compile-time. (<code>eval/1</code>) 	

`character_code(I)`

- *The following properties hold upon exit:*

I is an integer which is a character code.

(`character_code/1`)

Usage: `character_code(T)`

- *Description:* T is an integer which is a character code.

string/1:

REGTYPE

A string is a list of character codes. The usual syntax for strings "string" is allowed, which is equivalent to `[0's,0't,0'r,0'i,0'n,0'g]` or `[115,116,114,105,110,103]`. There is also a special Ciao syntax when the list is not complete: `"st"|R` is equivalent to `[0's,0't|R]`.

General properties: `string(T)`

- *The following properties hold globally:*

`string(T)` is side-effect free.

(`sideff/2`)

`string(T)`

- *If the following properties hold at call time:*

T is currently ground (it contains no variables).

(`ground/1`)

then the following properties hold globally:

`string(T)` is evaluable at compile-time.

(`eval/1`)

`string(T)`

- *The following properties hold upon exit:*

T is a string (a list of character codes).

(`string/1`)

Usage: `string(T)`

- *Description:* T is a string (a list of character codes).

num_code/1:

REGTYPE

These are the ASCII codes which can appear in decimal representation of floating point and integer numbers, including scientific notation and fractionary part.

predname/1:

REGTYPE

General properties: `predname(P)`

- *The following properties hold globally:*

`predname(P)` is side-effect free.

(`sideff/2`)

`predname(P)`

- *If the following properties hold at call time:*

P is currently ground (it contains no variables).

(`ground/1`)

then the following properties hold globally:

`predname(P)` is evaluable at compile-time.

(`eval/1`)

`predname(P)`

- *The following properties hold upon exit:*

P is a Name/Arity structure denoting a predicate name:

```

predname(P/A) :-
    atm(P),
    nnegint(A).

```

(predname/1)

Usage: predname(P)

- *Description:* P is a Name/Arity structure denoting a predicate name:

```

predname(P/A) :-
    atm(P),
    nnegint(A).

```

atm_or_atm_list/1:

REGTYPE

General properties: atm_or_atm_list(T)

- *The following properties hold globally:*

atm_or_atm_list(T) is side-effect free.

(sideff/2)

atm_or_atm_list(T)

- *If the following properties hold at call time:*

T is currently ground (it contains no variables).

(ground/1)

then the following properties hold globally:

atm_or_atm_list(T) is evaluable at compile-time.

(eval/1)

atm_or_atm_list(T)

- *The following properties hold upon exit:*

T is an atom or a list of atoms.

(atm_or_atm_list/1)

Usage: atm_or_atm_list(T)

- *Description:* T is an atom or a list of atoms.

compat/2:

PROPERTY

This property captures the notion of type or property compatibility. The instantiation or constraint state of the term is compatible with the given property, in the sense that assuming that imposing that property on the term does not render the store inconsistent. For example, terms X (i.e., a free variable), $[Y|Z]$, and $[Y,Z]$ are all compatible with the regular type `list/1`, whereas the terms $f(a)$ and $[1|2]$ are not.

Meta-predicate with arguments: compat(?,(pred 1)).**General properties:** compat(Term,Prop)

- *If the following properties hold at call time:*

Term is currently ground (it contains no variables).

(ground/1)

Prop is currently ground (it contains no variables).

(ground/1)

then the following properties hold globally:

compat(Term,Prop) is evaluable at compile-time.

(eval/1)

Usage: compat(Term,Prop)

- *Description:* Term is compatible with Prop

- inst/2:** PROPERTY
- Meta-predicate* with arguments: `inst(?,(pred 1))`.
- General properties:** `inst(Term,Prop)`
- *The following properties hold globally:*
- `inst(Term,Prop)` is side-effect free. (`sideff/2`)
- `inst(Term,Prop)`
- *If the following properties hold at call time:*
- `Term` is currently ground (it contains no variables). (`ground/1`)
- `Prop` is currently ground (it contains no variables). (`ground/1`)
- then the following properties hold globally:*
- `inst(Term,Prop)` is evaluable at compile-time. (`eval/1`)
- Usage:** `inst(Term,Prop)`
- *Description:* `Term` is instantiated enough to satisfy `Prop`.
-
- iso/1:** PROPERTY
- Meta-predicate* with arguments: `iso(goal)`.
- General properties:** `iso(G)`
- *The following properties hold globally:*
- `iso(G)` is side-effect free. (`sideff/2`)
- Usage:** `iso(G)`
- *Description:* *Complies with the ISO-Prolog standard.*
-
- deprecated/1:** PROPERTY
- Specifies that the predicate marked with this global property has been deprecated, i.e., its use is not recommended any more since it will be deleted at a future date. Typically this is done because its functionality has been superseded by another predicate.
- Meta-predicate* with arguments: `deprecated(goal)`.
- General properties:** `deprecated(G)`
- *The following properties hold globally:*
- `deprecated(G)` is side-effect free. (`sideff/2`)
- Usage:** `deprecated(G)`
- *Description:* **DEPRECATED.**
-
- not_further_inst/2:** PROPERTY
- Meta-predicate* with arguments: `not_further_inst(goal,?)`.
- General properties:** `not_further_inst(G,V)`
- *The following properties hold globally:*
- `not_further_inst(G,V)` is side-effect free. (`sideff/2`)
- Usage:** `not_further_inst(G,V)`
- *Description:* `V` is not further instantiated.

- sideff/2:** PROPERTY
sideff(G,X)
 Declares that **G** is side-effect free (if its execution has no observable result other than its success, its failure, or its abortion), soft (if its execution may have other observable results which, however, do not affect subsequent execution, e.g., input/output), or hard (e.g., assert/retract).
Meta-predicate with arguments: **sideff(goal,?)**.
General properties: sideff(G,X)
 – *The following properties hold globally:*
 This predicate is understood natively by CiaoPP. (native/1)
sideff(G,X) is side-effect free. (sideff/2)
Usage: sideff(G,X)
 – *Description:* **G** is side-effect **X**.
 – *If the following properties hold at call time:*
X is an element of [**free,soft,hard**]. (member/2)
- regtype/1:** PROPERTY
Meta-predicate with arguments: **regtype goal**.
General properties: regtype G
 – *The following properties hold globally:*
regtype G is side-effect free. (sideff/2)
Usage: regtype G
 – *Description:* Defines a regular type.
- native/1:** PROPERTY
Meta-predicate with arguments: **native(goal)**.
General properties: native(P)
 – *The following properties hold globally:*
native(P) is side-effect free. (sideff/2)
Usage: native(Pred)
 – *Description:* This predicate is understood natively by CiaoPP.
- native/2:** PROPERTY
Meta-predicate with arguments: **native(goal,?)**.
General properties: native(P,K)
 – *The following properties hold globally:*
native(P,K) is side-effect free. (sideff/2)
Usage: native(Pred,Key)
 – *Description:* This predicate is understood natively by CiaoPP as **Key**.

- no_rtcheck/1:** PROPERTY
Meta-predicate with arguments: `no_rtcheck(goal)`.
General properties: `no_rtcheck(G)`
 – *The following properties hold globally:*
 `no_rtcheck(G)` is side-effect free. (`sideff/2`)
Usage: `no_rtcheck(G)`
 – *Description:* Declares that the assertion in which this comp property appears must not be checked at run-time.
- eval/1:** PROPERTY
Meta-predicate with arguments: `eval(goal)`.
Usage: `eval(Goal)`
 – *Description:* `Goal` is evaluable at compile-time.
- equiv/2:** PROPERTY
Meta-predicate with arguments: `equiv(goal,goal)`.
Usage: `equiv(Goal1,Goal2)`
 – *Description:* `Goal1` is equivalent to `Goal2`.
- bind_ins/1:** PROPERTY
Meta-predicate with arguments: `bind_ins(goal)`.
Usage: `bind_ins(Goal)`
 – *Description:* `Goal` is binding insensitive.
- error_free/1:** PROPERTY
Meta-predicate with arguments: `error_free(goal)`.
Usage: `error_free(Goal)`
 – *Description:* `Goal` is error free.
- memo/1:** PROPERTY
Meta-predicate with arguments: `memo(goal)`.
Usage: `memo(Goal)`
 – *Description:* `Goal` should be memoized (not unfolded).
- filter/2:** PROPERTY
Usage: `filter(Vars,Goal)`
 – *Description:* `Vars` should be filtered during global control).

flag_values/1: REGTYPE

Usage: flag_values(X)

- *Description:* Define the valid flag values

pe_type/1: PROPERTY

Meta-predicate with arguments: pe_type(goal).

Usage: pe_type(Goal)

- *Description:* Goal will be filtered in partial evaluation time according to the PE types defined in the assertion.

8 Properties which are native to analyzers

Author(s): Francisco Bueno, Manuel Hermenegildo, Pedro López, Edison Mera.

This library contains a set of properties which are natively understood by the different program analyzers of `ciaopp`. They are used by `ciaopp` on output and they can also be used as properties in assertions.

8.1 Usage and interface (`native_props`)

- **Library usage:**

```
:- use_module(library(assertions(native_props)))
```

or also as a package `:- use_package(nativeprops).`

Note the different names of the library and the package.

- **Exports:**

- *Properties:*

```
clique/1,
clique_1/1, constraint/1, covered/1, covered/2, exception/1, exception/2,
fails/1, finite_solutions/1, have_choicepoints/1, indep/1, indep/2, is_det/1,
linear/1, mshare/1, mut_exclusive/1, no_choicepoints/1, no_exception/1, no_
exception/2, no_signal/1, no_signal/2, non_det/1, nonground/1, not_covered/1,
not_fails/1, not_mut_exclusive/1, num_solutions/2, solutions/2, possibly_
fails/1, possibly_nondet/1, relations/2, sideff_hard/1, sideff_pure/1,
sideff_soft/1, signal/1, signal/2, signals/2, size/2, size/3, size_lb/2, size_
o/2, size_ub/2, size_metric/3, size_metric/4, steps/2, steps_lb/2, steps_o/2,
steps_ub/2, tau/1, terminates/1, test_type/2, throws/2, user_output/2.
```

- **Other modules used:**

- *System library modules:*

```
terms_check, terms_vars, sort, lists, streams, file_utils, system.
```

- *Internal (engine) modules:*

```
term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,
data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,
system_info, term_compare, term_typing, hiord_rt, debugger_support,
internals.
```

8.2 Documentation on exports (`native_props`)

`clique/1:`

PROPERTY

```
clique(X)
```

`X` is a set of variables of interest, much the same as a sharing group but `X` represents all the sharing groups in the powerset of those variables. Similar to a sharing group, a clique is often translated to `ground/1`, `indep/1`, and `indep/2` properties.

Usage: `clique(X)`

- *Description:* The clique pattern is `X`.

- *The following properties should hold globally:*

This predicate is understood natively by CiaoPP as `clique(X)`. (`native/2`)

- clique_1/1:** PROPERTY
`clique_1(X)`
 X is a set of variables of interest, much the same as a sharing group but X represents all the sharing groups in the powerset of those variables but disregarding the singletons. Similar to a sharing group, a clique_1 is often translated to `ground/1`, `indep/1`, and `indep/2` properties.
Usage: `clique_1(X)`
 – *Description:* The 1-clique pattern is X.
 – *The following properties should hold globally:*
 This predicate is understood natively by CiaoPP as `clique_1(X)`. (native/2)
- constraint/1:** PROPERTY
`constraint(C)`
 C contains a list of linear (in)equalities that relate variables and `int` values. For example, `[A < B + 4]` is a constraint while `[A < BC + 4]` or `[A = 3.4, B >= C]` are not.
Usage: `constraint(C)`
 – *Description:* C is a list of linear equations
 – *The following properties hold globally:*
 This predicate is understood natively by CiaoPP. (native/1)
- covered/1:** PROPERTY
`covered(X)`
 For any call of the form X there is at least one clause whose test succeeds (i.e., all the calls of the form X are covered) [DLGH97].
Usage: `covered(X)`
 – *Description:* All the calls of the form X are covered.
- covered/2:** PROPERTY
`covered(X,Y)`
 All variables occurring in X occur also in Y.
Usage: `covered(X,Y)`
 – *Description:* X is covered by Y.
 – *The following properties hold globally:*
 This predicate is understood natively by CiaoPP. (native/1)
- exception/1:** PROPERTY
Meta-predicate with arguments: `exception(goal)`.
Usage: `exception(Goal)`
 – *Description:* Calls of the form Goal throw an exception.

- exception/2:** PROPERTY
Meta-predicate with arguments: `exception(goal,?)`.
Usage: `exception(Goal,E)`
 – *Description:* Calls of the form `Goal` throw an exception that unifies with `E`.
- fails/1:** PROPERTY
`fails(X)`
 Calls of the form `X` fail.
Meta-predicate with arguments: `fails(goal)`.
Usage: `fails(X)`
 – *Description:* Calls of the form `X` fail.
 – *The following properties hold globally:*
 This predicate is understood natively by CiaoPP. (`native/1`)
- finite_solutions/1:** PROPERTY
`finite_solutions(X)`
 Calls of the form `X` produce a finite number of solutions [DLGH97].
Meta-predicate with arguments: `finite_solutions(goal)`.
Usage: `finite_solutions(X)`
 – *Description:* All the calls of the form `X` have a finite number of solutions.
- have_choicepoints/1:** PROPERTY
Meta-predicate with arguments: `have_choicepoints(goal)`.
Usage: `have_choicepoints(X)`
 – *Description:* A call to `X` creates choicepoints.
- indep/1:** PROPERTY
Usage: `indep(X)`
 – *Description:* The variables in pairs in `X` are pairwise independent.
 – *The following properties hold globally:*
 This predicate is understood natively by CiaoPP as `indep(X)`. (`native/2`)
- indep/2:** PROPERTY
Usage: `indep(X,Y)`
 – *Description:* `X` and `Y` do not have variables in common.
 – *The following properties hold globally:*
 This predicate is understood natively by CiaoPP as `indep([[X,Y]])`. (`native/2`)

is_det/1: PROPERTY`is_det(X)`

All calls of the form `X` are deterministic, i.e., produce at most one solution, or do not terminate. In other words, if `X` succeeds, it can only succeed once. It can still leave choice points after its execution, but when backtracking into these, it can only fail or go into an infinite loop.

Meta-predicate with arguments: `is_det(goal)`.

Usage: `is_det(X)`

- *Description:* All calls of the form `X` are deterministic.

linear/1: PROPERTY`linear(X)`

`X` is bound to a term which is linear, i.e., if it contains any variables, such variables appear only once in the term. For example, `[1,2,3]` and `f(A,B)` are linear terms, while `f(A,A)` is not.

Usage: `linear(X)`

- *Description:* `X` is instantiated to a linear term.
- *The following properties hold globally:*
This predicate is understood natively by CiaoPP. (`native/1`)

mshare/1: PROPERTY`mshare(X)`

`X` contains all *sharing sets* [JL88,MH89] which specify the possible variable occurrences in the terms to which the variables involved in the clause may be bound. Sharing sets are a compact way of representing groundness of variables and dependencies between variables. This representation is however generally difficult to read for humans. For this reason, this information is often translated to `ground/1`, `indep/1` and `indep/2` properties, which are easier to read.

Usage: `mshare(X)`

- *Description:* The sharing pattern is `X`.
- *The following properties should hold globally:*
This predicate is understood natively by CiaoPP as `sharing(X)`. (`native/2`)

mut_exclusive/1: PROPERTY`mut_exclusive(X)`

For any call of the form `X` at most one clause succeeds, i.e., clauses are pairwise exclusive.

Meta-predicate with arguments: `mut_exclusive(goal)`.

Usage: `mut_exclusive(X)`

- *Description:* For any call of the form `X` at most one clause succeeds.

no_choicepoints/1: PROPERTY

Meta-predicate with arguments: `no_choicepoints(goal)`.

Usage: `no_choicepoints(X)`

- *Description:* A call to `X` does not create choicepoints.

<p>no_exception/1: <i>Meta-predicate</i> with arguments: <code>no_exception(goal)</code>. Usage: <code>no_exception(Goal)</code> – <i>Description:</i> Calls of the form <code>Goal</code> do not throw any exception.</p>	PROPERTY
<p>no_exception/2: <i>Meta-predicate</i> with arguments: <code>no_exception(goal,?)</code>. Usage: <code>no_exception(Goal,E)</code> – <i>Description:</i> Calls of the form <code>Goal</code> do not throw exception <code>E</code>.</p>	PROPERTY
<p>no_signal/1: <i>Meta-predicate</i> with arguments: <code>no_signal(goal)</code>. Usage: <code>no_signal(Goal)</code> – <i>Description:</i> Calls of the form <code>Goal</code> do not send any signal.</p>	PROPERTY
<p>no_signal/2: <i>Meta-predicate</i> with arguments: <code>no_signal(goal,?)</code>. Usage: <code>no_signal(Goal,E)</code> – <i>Description:</i> Calls of the form <code>Goal</code> do not send the signal <code>E</code>.</p>	PROPERTY
<p>non_det/1: <code>non_det(X)</code> All calls of the form <code>X</code> are non-deterministic, i.e., produce several solutions. <i>Meta-predicate</i> with arguments: <code>non_det(goal)</code>. Usage: <code>non_det(X)</code> – <i>Description:</i> All calls of the form <code>X</code> are non-deterministic.</p>	PROPERTY
<p>nonground/1: Usage: <code>nonground(X)</code> – <i>Description:</i> <code>X</code> is not ground. – <i>The following properties should hold globally:</i> This predicate is understood natively by CiaoPP as <code>not_ground(X)</code>. (<code>native/2</code>)</p>	PROPERTY
<p>not_covered/1: <code>not_covered(X)</code> There is some call of the form <code>X</code> for which there is no clause whose test succeeds [DLGH97]. Usage: <code>not_covered(X)</code> – <i>Description:</i> Not all of the calls of the form <code>X</code> are covered.</p>	PROPERTY

- not_fails/1:** PROPERTY
 not_fails(X)
 Calls of the form X produce at least one solution, or do not terminate [DLGH97].
Meta-predicate with arguments: not_fails(goal).
Usage: not_fails(X)
 – *Description:* All the calls of the form X do not fail.
 – *The following properties hold globally:*
 This predicate is understood natively by CiaoPP. (native/1)
- not_mut_exclusive/1:** PROPERTY
 not_mut_exclusive(X)
 For calls of the form X more than one clause may succeed. I.e., clauses are not disjoint for some call.
Meta-predicate with arguments: not_mut_exclusive(goal).
Usage: not_mut_exclusive(X)
 – *Description:* For some calls of the form X more than one clause may succeed.
- num_solutions/2:** PROPERTY
Usage 1: num_solutions(X,N)
 – *Description:* All the calls of the form X have N solutions.
 – *If the following properties should hold at call time:*
 X is a term which represents a goal, i.e., an atom or a structure. (callable/1)
 N is an integer. (int/1)
Usage 2: num_solutions(Goal,Check)
 – *Description:* For a call to Goal, Check(X) succeeds, where X is the number of solutions.
 – *If the following properties should hold at call time:*
 Goal is a term which represents a goal, i.e., an atom or a structure. (callable/1)
 Check is a term which represents a goal, i.e., an atom or a structure. (callable/1)
- solutions/2:** PROPERTY
Usage: solutions(Goal,Sols)
 – *Description:* Goal Goal produces the solutions listed in Sols.
 – *If the following properties should hold at call time:*
 Goal is a term which represents a goal, i.e., an atom or a structure. (callable/1)
 Sols is a list. (list/1)
- possibly_fails/1:** PROPERTY
 possibly_fails(X)
 Non-failure is not ensured for any call of the form X [DLGH97]. In other words, nothing can be ensured about non-failure nor termination of such calls.
Meta-predicate with arguments: possibly_fails(goal).
Usage: possibly_fails(X)
 – *Description:* Non-failure is not ensured for calls of the form X.

- possibly_nondet/1:** PROPERTY
 possibly_nondet(X)
 Non-determinism is not ensured for all calls of the form X. In other words, nothing can be ensured about determinacy nor termination of such calls.
Usage: possibly_nondet(X)
 – *Description:* Non-determinism is not ensured for calls of the form X.
- relations/2:** PROPERTY
 relations(X,N)
 The goal X produces N solutions. In other words, N is the cardinality of the solution set of X.
Meta-predicate with arguments: relations(goal,?).
Usage: relations(X,N)
 – *Description:* Goal X produces N solutions.
- sideff_hard/1:** PROPERTY
Meta-predicate with arguments: sideff_hard(goal).
Usage: sideff_hard(X)
 – *Description:* X has *hard side-effects*, i.e., those that might affect program execution (e.g., assert/retract).
- sideff_pure/1:** PROPERTY
Meta-predicate with arguments: sideff_pure(goal).
Usage: sideff_pure(X)
 – *Description:* X is pure, i.e., has no side-effects.
- sideff_soft/1:** PROPERTY
Meta-predicate with arguments: sideff_soft(goal).
Usage: sideff_soft(X)
 – *Description:* X has *soft side-effects*, i.e., those not affecting program execution (e.g., input/output).
- signal/1:** PROPERTY
Meta-predicate with arguments: signal(goal).
Usage: signal(Goal)
 – *Description:* Calls of the form Goal throw a signal.
- signal/2:** PROPERTY
Meta-predicate with arguments: signal(goal,?).
Usage: signal(Goal,E)
 – *Description:* A call to Goal sends a signal that unifies with E.

- signals/2:** PROPERTY
Meta-predicate with arguments: `signals(goal,?)`.
Usage: `signals(Goal,Es)`
 – *Description:* Calls of the form `Goal` can generate only the signals that unify with the terms listed in `Es`.
- size/2:** PROPERTY
Usage: `size(X,Y)`
 – *Description:* `Y` is the size of argument `X`, for any approximation.
- size/3:** PROPERTY
Usage: `size(A,X,Y)`
 – *Description:* `Y` is the size of argument `X`, for the approximation `A`.
- size_lb/2:** PROPERTY
`size_lb(X,Y)`
 The minimum size of the terms to which the argument `Y` is bound is given by the expression `Y`. Various measures can be used to determine the size of an argument, e.g., list-length, term-size, term-depth, integer-value, etc. [DL93,LGHD96].
Usage: `size_lb(X,Y)`
 – *Description:* `Y` is a lower bound on the size of argument `X`.
- size_o/2:** PROPERTY
Usage: `size_o(X,Y)`
 – *Description:* The size of argument `X` is in the order of `Y`.
- size_ub/2:** PROPERTY
`size_ub(X,Y)`
 The maximum size of the terms to which the argument `Y` is bound is given by the expression `Y`. Various measures can be used to determine the size of an argument, e.g., list-length, term-size, term-depth, integer-value, etc. [DL93,LGHD96].
Usage: `size_ub(X,Y)`
 – *Description:* `Y` is an upper bound on the size of argument `X`.
- size_metric/3:** PROPERTY
Meta-predicate with arguments: `size_metric(goal,?,?)`.
Usage: `size_metric(Head,Var,Metric)`
 – *Description:* `Metric` is the metric of the variable `Var`, for any approximation.

- size_metric/4:** PROPERTY
Meta-predicate with arguments: `size_metric(goal,?,?,?)`.
Usage: `size_metric(Head,Approx,Var,Metric)`
 – *Description:* `Metric` is the metric of the variable `Var`, for the approximation `Approx`.
 Currently, `Metric` can be: `int/1`, `size/1`, `length/1`, `depth/2`, and `void/1`.
- steps/2:** PROPERTY
`steps(X,Y)`
 The time (in resolution steps) spent by any call of the form `X` is given by the expression `Y`
Meta-predicate with arguments: `steps(goal,?)`.
Usage: `steps(X,Y)`
 – *Description:* `Y` is the cost (number of resolution steps) of any call of the form `X`.
- steps_lb/2:** PROPERTY
`steps_lb(X,Y)`
 The minimum computation time (in resolution steps) spent by any call of the form `X` is
 given by the expression `Y` [DLGHL97,LGHD96]
Meta-predicate with arguments: `steps_lb(goal,?)`.
Usage: `steps_lb(X,Y)`
 – *Description:* `Y` is a lower bound on the cost of any call of the form `X`.
- steps_o/2:** PROPERTY
Meta-predicate with arguments: `steps_o(goal,?)`.
Usage: `steps_o(X,Y)`
 – *Description:* `Y` is the complexity order of the cost of any call of the form `X`.
- steps_ub/2:** PROPERTY
`steps_ub(X,Y)`
 The maximum computation time (in resolution steps) spent by any call of the form `X` is
 given by the expression `Y` [DL93,LGHD96].
Meta-predicate with arguments: `steps_ub(goal,?)`.
Usage: `steps_ub(X,Y)`
 – *Description:* `Y` is an upper bound on the cost of any call of the form `X`.
- tau/1:** PROPERTY
`tau(Types)`
`Types` contains a list with the type associations for each variable, in the form
`V/[T1,...,TN]`. Note that `tau` is used in object-oriented programs only
Usage: `tau(TypeInfo)`
 – *Description:* `Types` is a list of associations between variables and list of types
 – *The following properties hold globally:*
 This predicate is understood natively by CiaoPP. (native/1)

- terminates/1:** PROPERTY
- `terminates(X)`
 Calls of the form `X` always terminate [DLGH97].
Meta-predicate with arguments: `terminates(goal)`.
Usage: `terminates(X)`
 – *Description:* All calls of the form `X` terminate.
- test_type/2:** PROPERTY
- Meta-predicate* with arguments: `test_type(goal,?)`.
Usage: `test_type(X,T)`
 – *Description:* Indicates the type of test that a predicate performs. Required by the nonfailure analysis.
- throws/2:** PROPERTY
- Meta-predicate* with arguments: `throws(goal,?)`.
Usage: `throws(Goal,Es)`
 – *Description:* Calls of the form `Goal` can throw only the exceptions that unify with the terms listed in `Es`.
- user_output/2:** PROPERTY
- Meta-predicate* with arguments: `user_output(goal,?)`.
Usage: `user_output(Goal,S)`
 – *Description:* Calls of the form `Goal` write `S` to standard output.
- instance/2:** PROPERTY
- Usage:** `instance(Term1,Term2)`
 – *Description:* `Term1` is an instance of `Term2`.
 – *The following properties hold globally:*
 This predicate is understood natively by CiaoPP. (`native/1`)

9 Meta-properties

Author(s): Francisco Bueno.

This library allows the use of some meta-constructs which provide for specifying properties of terms which are unknown at the time of the specification, or expressed with a shorthand for the property definition, i.e., without really defining it.

An example of such use is an assertion which specifies that any property holding upon call will also hold upon exit:

```
:- pred p(X) : Prop(X) => Prop(X).
```

Another example is using shorthands for properties when documenting:

```
:- pred p(X) : regtype(X, (^ (list;list);list)).
```

(See below for an explanation of such a regular type.)

9.1 Usage and interface (meta_props)

- **Library usage:**

```
:- use_module(library(assertions(meta_props)))
```

 or also as a package

```
:- use_package(metaprops).
```


 Note the different names of the library and the package.
- **Exports:**
 - *Properties:*
 call/2, prop/2, regtype/2.
 - *Multifiles:*
 callme/2.
- **Other modules used:**
 - *Internal (engine) modules:*
 term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,
 data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,
 system_info, term_compare, term_typing, hiord_rt, debugger_support.

9.2 Documentation on exports (meta_props)

call/2:

PROPERTY

call(P,A)

A has property P (provided that P is a property). Equivalent to P(A).

Usage: call(P,A)

– *Description:* A has property P.

– *If the following properties hold at call time:*

P is a term which represents a goal, i.e., an atom or a structure. (callable/1)

prop/2: PROPERTY
Usage: A prop P
 – *Description:* A has property P.
 – *If the following properties hold at call time:*
 P has property $\hat{\ }((\text{prop})/2)$

regtype/2: PROPERTY
Usage: A regtype T
 – *Description:* A is of type T.
 – *If the following properties hold at call time:*
 T has property $\hat{\ }((\text{regtype});\text{prop_abs})$. ((prop)/2)

9.3 Documentation on multifiles (meta_props)

callme/2: PREDICATE
 (User defined.) A hook predicate you have to define as `callme(P,X):- P(X), !.` in the program that uses this library. This is done automatically if the package is used instead of the library module (but then you *should not* define `callme/2` in your program).
 The predicate is *multifile*.
Usage: `callme(A,B)`
 – *The following properties should hold at call time:*
 A is a term which represents a goal, i.e., an atom or a structure. (callable/1)

9.4 Documentation on internals (meta_props)

prop_abs/1: PROPERTY
`prop_abs(Prop)`
 Prop is a *property abstraction*, i.e., a *parametric property*, or a term formed of property abstractions, where the functors used in the term are escaped by $\hat{\ }$.
 One particular case of property abstractions are *parametric regular type abstractions*, i.e., a parametric type functor or a $\hat{\ }$ -escaped term formed of regular type abstractions.
 Such abstractions are a short-hand for a corresponding regular type (correspondingly, property). For example, the following abstraction:
 $\hat{\ }(\text{list};\text{list});\text{list}$

denotes terms of the form `(X;Y)` where `list(X)` and `list(Y)` hold and also terms T such that `list(T)` holds. It is equivalent to the regular type:

```
abstract_type((X;Y):- list(X), list(Y).
abstract_type(T):- list(T).
```

Usage: `prop_abs(Prop)`
 – *Description:* Prop is a property abstraction.

10 An Example - Documenting a Library Module

Author(s): Manuel Hermenegildo.

A simple example of the use of `lpdoc` is this manual, which can be built in the `doc` directory of the `lpdoc` distribution. Other examples of manuals generated using `lpdoc` can be found in the `Ciao` system and preprocessor `doc` directories (i.e., most of the `Ciao` manuals are generated using `lpdoc`). Some simpler examples can be found in the `examples` directory of the `lpdoc` distribution. In particular, the chapter following this one contains the documentation generated automatically for the module defined by file `examples/example_module.pl` (which for simplicity contains only assertions, i.e., no actual code) and which is included in source form below. Comparing this code with the output in the following chapter illustrates the use and some of the capabilities of `lpdoc`:

```
%% The module headers produce documentation on the module interface
%% Exported predicates (+ properties and types) are documented by default
:- module(example_module,
           [bar/1,baz/1,aorb/1,tree_of/2,list_or_aorb/2,q/2,r/1, p/1, p/5, u/3,
           long/1, w/1, mytype/1, t/5, s/1, q/1],
           [assertions,basicmodes,fsyntax,regtypes,hiord,nativeprops]).

%% We import two types: list/1 and list/2 (now in basic_props, which is
%% exported by default from assertions).

%% We reexport list/1
:- reexport(library(engine(basic_props)), [ list/1 ]).

:- use_module(library(lists), [length/2]).
%:- use_module(bar).
:- ensure_loaded(foo).

%% "doc" declarations provide additional information
:- doc(title,"Auto Documenter Output for the Example Module").

:- doc(author,"Anonymous Author 1").
:- doc(author,"Anonymous Author 2").

:- doc(summary,"This is a brief summary description of the module
or file. In this case the file is a library.").

:- doc(module,"This is where general comments on the file go. In
this case the file is a library which contains some assertion examples
for testing the @em{automatic documentation system}. ").

%% An example of a comment documenting a bug
:- doc(bug,"Library is hard to execute: no actual code!").

%% Standard declarations are documented with the corresponding predicate
:- data r/1.
:- dynamic q/2.
:- multifile p/3.
:- dynamic p/3.
:- meta_predicate p(?,:,:?).
```

```

%% Uncommenting this would make these not appear in the documentation
%% :- doc(hide,[bar/1,baz/1]).

%% This is a type definition in Prolog syntax: declaration and code
:- true regtype bar(X) # "@var{X} is an acceptable kind of bar.".

bar(night).
bar(day).

%% This is another type definition in Prolog syntax, with no comment.
:- true regtype baz/1.

baz(a).
baz(b).

%% Two type definitions in 'typedef' syntax (will be expanded to code as above)
%% :- typedef aorb ::= ^a;^b.
%% :- typedef listof_or_aorb(X) ::= list(X);aorb.

%% Using functional notation:
:- regtype aorb/1.

aorb := a.
aorb := b.

%% Should use the other function syntax which uses *first argument* for return
:- regtype tree_of/2.

tree_of(_) := void.
tree_of(T) := tree(~call(T),~tree_of(T),~tree_of(T)).

%% tree_of(_, void).
%% tree_of(T, tree(X,L,R)) :-
%%     T(X),
%%     tree_of(T,L),
%%     tree_of(T,R).

:- regtype list_or_aorb/2.

list_or_aorb(T) := ~list(T).
list_or_aorb(_T) := ~aorb.

%% This is a property definition
%% This comment appears only in the place where the property itself
%% is documented.
:- doc(long/1,"This is a property, describing a list that is longish.
The definition is:

@includedef{long/1}

```

```

    ").

%% The comment here will be used to document any predicate which has an
%% assertion which uses the property
:- prop long(L) # "@var{L} is rather long.".

long(L) :-
    length(L,N),
    N>100.

%% Now, a series of assertions:
%%
%% This declares the entry mode of this exported predicate (i.e.,
%% how it is called from outside).
:- entry p/3 : gnd * var * var.

%% This describes all the calls
:- calls p/3 : foo * bar * baz.

foo(_).

%% This describes the successes (for a given type of calls)
:- success p/3 : int * int * var => int * int * gnd.

%% This describes a global property (for a given type of calls)
:- comp p/3 : int * int * var + not_fails.

:- doc(p/3,"A @bf{general comment} on the predicate." ).
%% Documenting some typical usages of the predicate
:- pred p/3
    : int * int * var
    => int * int * list
    + (iso,not_fails)
    # "This mode is nice.".
:- pred p(Preds,Value,Assoc)
    : var * var * list
    => int * int * list
    + not_fails # "This mode is also nice.".
:- pred p/3
    => list * int * list
    + (not_fails,not_fails)
    # "Just playing around.".

:- pred q(A)
    : list(A)
    => (list(A),gnd(A))
    + not_fails
    # "Foo".
:- pred q(A)
    # "Not a bad use at all.".

```

```

:- pred q/2
    : var * {gnd,int}
    => {gnd,int} * int.
:- pred q/2
    :: int * list
    # "Non-moded types are best used this way.".

q(_).

:- pred p/1 : var => list.

p(_).

:- pred r(A)
    : list(A)
    => (list(A,int),gnd(A))
    + not_fails
    # "This uses parametric types".

:- doc(doinclude,s/1). %% Forces documentation even if not exported
:- pred s(A)
    : list(A)
    => (list(A),gnd(A))
    + not_fails.

s(_).

:- doc(doinclude,[list/2,list/1]). %% Forces (local) documentation even if
                                   %% not exported

:- modedef og(A)
    => gnd(A)
    # "This is a @em{mode} definition: the output is ground.".

:- doc(doinclude,og/2).

:- modedef og(A,T)
    :: T(A)
    => gnd(A)
    # "This is a @em{parametric mode definition}.".

:- pred t(+A,-B,?C,@D,og(E))
    :: list * list * int * int * list
    : long(B)
    => (gnd(C),gnd(A))
    + not_fails
    # "This predicate uses @em{modes} extensively.".

t(_, _, _, _, _).

%% Some other miscellaneous assertions:

```

```
%% Check is default assertion status anyway...
:- check pred u(+,-,og).
:- check pred u(int,list(mytype),int).

u(_, _, _).

%% ‘‘true’’ status is normally compiler output
:- true pred w(+list(mytype)).

mytype(_).

w(_).

:- doc(doinclude,is/2).

:- trust pred is(Num,Expr) : arithexpression(Expr) => num(Num)
   # "Typical way to describe/document an external predicate (e.g.,
     written in C)".

:- doc(doinclude,p/5).
:- pred p(og(int),in,@list(int),-,+A) + steps_lb(1+length(A)).

p(_, _, _, _, _) :- _ is 1.

%% Version information. The ciao.el emacs mode allows automatic maintenance
```


11 Auto Documenter Output for the Example Module

Author(s): Anonymous Author 1, Anonymous Author 2.

This is where general comments on the file go. In this case the file is a library which contains some assertion examples for testing the *automatic documentation system*.

11.1 Usage and interface (example_module)

- **Library usage:**
 - :- use_module(library(example_module)).
- **Exports:**
 - *Predicates:*
q/2, r/1, p/1, p/5, u/3, w/1, mytype/1, t/5, s/1, q/1.
 - *Properties:*
long/1.
 - *Regular Types:*
bar/1, baz/1, aorb/1, tree_of/2, list_or_aorb/2.
 - *Multifiles:*
p/3.
- **Other modules used:**
 - *Files of module user:*
foo.
 - *System library modules:*
assertions/native_props, engine/basic_props, lists.
 - *Internal (engine) modules:*
term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol, data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic, system_info, term_compare, term_typing, hiord_rt, debugger_support.

11.2 Documentation on exports (example_module)

bar/1: REGTYPE
 Usage: bar(X)
 – *Description:* X is an acceptable kind of bar.

baz/1: REGTYPE
 A regular type, defined as follows:
 baz(a).
 baz(b).

aorb/1:	A regular type, defined as follows: <pre>aorb(a). aorb(b).</pre>	REGTYPE
tree_of/2:	A regular type, defined as follows: <pre>tree_of(_1,void). tree_of(T,tree(_1,_2,_3)) :- call(T,_1), tree_of(T,_2), tree_of(T,_3).</pre>	REGTYPE
list_or_aorb/2:	A regular type, defined as follows: <pre>list_or_aorb(T,_1) :- list(T,_1). list_or_aorb(_T,_1) :- aorb(_1).</pre>	REGTYPE
q/2:	The predicate is of type <i>dynamic</i> . Usage 1: <ul style="list-style-type: none"> – <i>The following properties should hold at call time:</i> Arg1 is a free variable. (var/1) Arg2 is ground. (gnd/1) Arg2 is an integer. (int/1) – <i>The following properties should hold upon exit:</i> Arg1 is ground. (gnd/1) Arg1 is an integer. (int/1) Arg2 is an integer. (int/1) Usage 2: <ul style="list-style-type: none"> – <i>Description:</i> Non-moded types are best used this way. – <i>Call and exit should be compatible with:</i> Arg1 is an integer. (int/1) Arg2 is a list. (list/1) 	PREDICATE
r/1:	The predicate is of type <i>data</i> . Usage: r(A) <ul style="list-style-type: none"> – <i>Description:</i> This uses parametric types 	PREDICATE

–	<i>The following properties should hold at call time:</i>	
	A is a list.	(list/1)
–	<i>The following properties should hold upon exit:</i>	
	A is a list of ints.	(list/2)
	A is ground.	(gnd/1)
–	<i>The following properties should hold globally:</i>	
	All the calls of the form <code>r(A)</code> do not fail.	(not_fails/1)
p/1:		PREDICATE
	Usage:	
–	<i>The following properties should hold at call time:</i>	
	Arg1 is a free variable.	(var/1)
–	<i>The following properties should hold upon exit:</i>	
	Arg1 is a list.	(list/1)
p/5:		PREDICATE
	Usage: <code>p(Arg1,Arg2,Arg3,Arg4,A)</code>	
–	<i>Call and exit should be compatible with:</i>	
	Arg1 is an integer.	(int/1)
	Arg3 is a list of ints.	(list/2)
–	<i>The following properties should hold at call time:</i>	
	Arg2 is currently ground (it contains no variables).	(ground/1)
	Arg4 is a free variable.	(var/1)
	A is currently a term which is not a free variable.	(nonvar/1)
–	<i>The following properties should hold upon exit:</i>	
	Arg1 is ground.	(gnd/1)
	Arg2 is currently ground (it contains no variables).	(ground/1)
–	<i>The following properties should hold globally:</i>	
	Arg3 is not further instantiated.	(not_further_inst/2)
	<code>1+length(A)</code> is a lower bound on the cost of any call of the form <code>p(Arg1,Arg2,Arg3,Arg4,A)</code> .	(steps_lb/2)
u/3:		PREDICATE
	Usage 1:	
–	<i>The following properties should hold at call time:</i>	
	Arg1 is currently a term which is not a free variable.	(nonvar/1)
	Arg2 is a free variable.	(var/1)
–	<i>The following properties should hold upon exit:</i>	
	Arg3 is ground.	(gnd/1)

long/1:		PROPERTY
This is a property, describing a list that is longish. The definition is:		
<pre>long(L) :- length(L,N), N>100.</pre>		
Usage: long(L)		
– <i>Description:</i> L is rather long.		
w/1:		PREDICATE
Usage:		
– <i>Calls should, and exit will be compatible with:</i>		
Arg1 is a list of mytypes.		(list/2)
– <i>The following properties should hold at call time:</i>		
Arg1 is currently a term which is not a free variable.		(nonvar/1)
mytype/1:		PREDICATE
No further documentation available for this predicate.		
t/5:		PREDICATE
Usage: t(A,B,C,D,E)		
– <i>Description:</i> This predicate uses <i>modes</i> extensively.		
– <i>Call and exit should be compatible with:</i>		
A is a list.		(list/1)
B is a list.		(list/1)
C is an integer.		(int/1)
D is an integer.		(int/1)
E is a list.		(list/1)
– <i>The following properties should hold at call time:</i>		
A is currently a term which is not a free variable.		(nonvar/1)
B is a free variable.		(var/1)
B is rather long.		(long/1)
– <i>The following properties should hold upon exit:</i>		
E is ground.		(gnd/1)
C is ground.		(gnd/1)
A is ground.		(gnd/1)
– <i>The following properties should hold globally:</i>		
D is not further instantiated.		(not_further_inst/2)
All the calls of the form t(A,B,C,D,E) do not fail.		(not_fails/1)

s/1:		PREDICATE
Usage: s(A)		
– <i>The following properties should hold at call time:</i>		
A is a list.		(list/1)
– <i>The following properties should hold upon exit:</i>		
A is a list.		(list/1)
A is ground.		(gnd/1)
– <i>The following properties should hold globally:</i>		
All the calls of the form s(A) do not fail.		(not_fails/1)
q/1:		PREDICATE
Usage 1: q(A)		
– <i>Description:</i> Foo		
– <i>The following properties should hold at call time:</i>		
A is a list.		(list/1)
– <i>The following properties should hold upon exit:</i>		
A is a list.		(list/1)
A is ground.		(gnd/1)
– <i>The following properties should hold globally:</i>		
All the calls of the form q(A) do not fail.		(not_fails/1)
Usage 2: q(A)		
– <i>Description:</i> Not a bad use at all.		
list/1:		REGTYPE
General properties: list(L)		
– <i>The following properties hold globally:</i>		
list(L) is side-effect free.		(sideff/2)
list(L)		
– <i>If the following properties hold at call time:</i>		
L is currently ground (it contains no variables).		(ground/1)
<i>then the following properties hold globally:</i>		
list(L) is evaluable at compile-time.		(eval/1)
All calls of the form list(L) are deterministic.		(is_det/1)
list(T)		
– <i>The following properties hold upon exit:</i>		
T is a list.		(list/1)
Usage: list(L)		
– <i>Description:</i> L is a list.		

11.3 Documentation on multifiles (example_module)

p/3:

PREDICATE

A **general comment** on the predicate.

The predicate is *multifile*.

The predicate is of type *dynamic*.

General properties:

- *If the following properties hold at call time:*

Arg1 is ground. (gnd/1)

Arg2 is a free variable. (var/1)

Arg3 is a free variable. (var/1)

- *The following properties should hold at call time:*

foo(Arg1) (undefined property)

Arg2 is an acceptable kind of bar. (bar/1)

baz(Arg3) (baz/1)

- *If the following properties hold at call time:*

Arg1 is an integer. (int/1)

Arg2 is an integer. (int/1)

Arg3 is a free variable. (var/1)

then the following properties should hold upon exit:

Arg1 is an integer. (int/1)

Arg2 is an integer. (int/1)

Arg3 is ground. (gnd/1)

- *If the following properties hold at call time:*

Arg1 is an integer. (int/1)

Arg2 is an integer. (int/1)

Arg3 is a free variable. (var/1)

then the following properties should hold globally:

All the calls of the form p(Arg1,Arg2,Arg3) do not fail. (not_fails/1)

Usage 1:

◻ ISO ◻

- *Description:* This mode is nice.

- *The following properties should hold at call time:*

Arg1 is an integer. (int/1)

Arg2 is an integer. (int/1)

Arg3 is a free variable. (var/1)

- *The following properties should hold upon exit:*

Arg1 is an integer. (int/1)

Arg2 is an integer. (int/1)

Arg3 is a list. (list/1)

- *The following properties should hold globally:*

Complies with the ISO-Prolog standard. (iso/1)

All the calls of the form p(Arg1,Arg2,Arg3) do not fail. (not_fails/1)

Usage 2: p(Preds,Value,Assoc)

- *Description:* This mode is also nice.
- *The following properties should hold at call time:*
 - Preds is a free variable. (var/1)
 - Value is a free variable. (var/1)
 - Assoc is a list. (list/1)
- *The following properties should hold upon exit:*
 - Preds is an integer. (int/1)
 - Value is an integer. (int/1)
 - Assoc is a list. (list/1)
- *The following properties should hold globally:*
 - All the calls of the form p(Preds,Value,Assoc) do not fail. (not_fails/1)

Usage 3:

- *Description:* Just playing around.
- *The following properties should hold upon exit:*
 - Arg1 is a list. (list/1)
 - Arg2 is an integer. (int/1)
 - Arg3 is a list. (list/1)
- *The following properties should hold globally:*
 - All the calls of the form p(Arg1,Arg2,Arg3) do not fail. (not_fails/1)
 - All the calls of the form p(Arg1,Arg2,Arg3) do not fail. (not_fails/1)

11.4 Documentation on internals (example_module)

list/2:

REGTYPE

General properties: list(L,T)

- *The following properties hold globally:*
 - list(L,T) is side-effect free. (sideff/2)

list(L,T)

- *If the following properties hold at call time:*
 - L is currently ground (it contains no variables). (ground/1)
 - T is currently ground (it contains no variables). (ground/1)
- then the following properties hold globally:*
 - list(L,T) is evaluable at compile-time. (eval/1)

list(X,T)

- *The following properties hold upon exit:*
 - X is a list. (list/1)

Usage: list(L,T)

- *Description:* L is a list of Ts.

- og/2:** MODE
- Usage:** `og(A,T)`
- *Description:* This is a *parametric mode definition*.
 - *Call and exit are compatible with:*
`call(T,A)` (undefined property)
 - *The following properties are added upon exit:*
A is ground. (`gnd/1`)
-
- is/2:** PREDICATE
- Usage:** `Num is Expr`
- *Description:* Typical way to describe/document an external predicate (e.g., written in C).
 - *The following properties should hold at call time:*
`Expr` is an arithmetic expression. (`arithexpression/1`)
 - *The following properties hold upon exit:*
`Num` is a number. (`num/1`)

12 Run-time checking of assertions

Author(s): Edison Mera.

This package provides a complete implementation of run-time checks of predicate assertions. The program is instrumented to check such assertions at run time, and in case a property does not hold, the error is reported. Note that there is also an older package called `rtchecks`, by David Trallero. The advantage of this one is that it can be used independently of CiaoPP and also has updated functionality.

There are two main applications of run-time checks:

- To improve debugging of certain predicates, specifying some expected behavior that is checked at run-time with the assertions.
- To avoid manual implementation of run-time checks that should be done in some predicates, leaving the code clean and understandable.

The run-time checks can be configured using prolog flags. Below we itemize the valid prolog flags with its values and a brief explanation of the meaning:

- `rtchecks_level`
 - `exports`: Only use `rtchecks` for external calls of the exported predicates.
 - `inner` : Use also `rtchecks` for internal calls. Default.
- `rtchecks_trust`
 - `no` : Disable `rtchecks` for trust assertions.
 - `yes` : Enable `rtchecks` for trust assertions. Default.
- `rtchecks_entry`
 - `no` : Disable `rtchecks` for entry assertions.
 - `yes` : Enable `rtchecks` for entry assertions. Default.
- `rtchecks_exit`
 - `no` : Disable `rtchecks` for exit assertions.
 - `yes` : Enable `rtchecks` for exit assertions. Default.
- `rtchecks_test`
 - `no` : Disable `rtchecks` for test assertions. Default.
 - `yes` : Enable `rtchecks` for test assertions. Used for debugging purposes, but is better to use the `unittest` library.
- `rtchecks_inline`
 - `no` : Instrument `rtchecks` using call to library predicates present in `rtchecks_rt.pl`, `nativeprops.pl` and `basic_props.pl`. In this way, space is saved, but sacrificing performance due to usage of meta calls and external methods in the libraries. Default.
 - `yes` : Expand library predicates inline as far as possible. In this way, the code is faster, because its avoids metacalls and usage of external methods, but the final executable could be bigger.
- `rtchecks_asrloc` Controls the usage of locators for the assertions in the error messages. The locator says the file and lines that contains the assertion that had failed. Valid values are:
 - `no` : Disabled.
 - `yes` : Enabled. Default.
- `rtchecks_predloc` Controls the usage of locators for the predicate that caused the run-time check error. The locator says the first clause of the predicate that the violated assertion refers to.
 - `no` : Disabled.

- `yes` : Enabled, Default.
- `rtchecks_callloc`
 - `no` : Do not show the stack of predicates that caused the failure
 - `predicate` : Show the stack of predicates that caused the failure. Instrument it in the predicate. Default.
 - `literal` : Show the stack of predicates that caused the failure. Instrument it in the literal. This mode provides more information, because reports also the literal in the body of the predicate.
- `rtchecks_namefmt`
 - `long` : Show the name of predicates, properties and the values of the variables
 - `short` : Only show the name of the predicate in a reduced format. Default.

12.1 Usage and interface (`rtchecks_doc`)

- **Library usage:**

```
:- use_package(rtchecks).
```

or

```
:- module(...,[rtchecks]).
```
- **Other modules used:**
 - *Internal (engine) modules:*

```
term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,
data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,
system_info, term_compare, term_typing, hiord_rt, debugger_support.
```

13 Unit Testing Library

Author(s): Edison Mera.

This library provides an extension of the Ciao assertion language which allows writing *unit tests*. The central idea is to use the assertion language to provide specifications of test cases for a given predicate. The package also provides some special properties that are convenient when specifying unit tests and the required run-time libraries.

In general, a *test assertion* is written as follows:

```
:- test predicate(A1, A2, ..., An)
   : <Precondition>
   => <Postcondition>
   + <Global properties>
   # <Comment>.
```

Where the fields of the test assertion have the usual meaning in Ciao assertions, i.e., they contain conjunctions of properties which must hold at certain points in the execution. Here we give a somewhat more operational (“test oriented”), reading to these fields: **predicate/n** is the predicate to be tested. **Precondition** is a goal that is called before the predicate being tested, and can be used to generate values of the input parameters. **Postcondition** is a goal that should succeed after **predicate/n** has been called. The idea appears to be simple, but note that due to the non-determinism of logic programs, the test engine needs to test all the solutions that can be tested up to given limits (for example, a maximum number of solutions, or a given time-out). **Properties** specifies some global properties that the predicate should meet, for example, **not_fails** means that the program does not fail, **exception(error(a,b))** means that the program should throw the exception **error(a,b)**, and so on. But there are some specific properties that only applies to testing specified in the module `unittest_props.pl`, for example **times(N)** specifies that the given test should be executed N times, **try_sols(N)** specifies that the first N solutions of the predicate **predicate/n** are tested. **Comment** is a string that document the test.

A convenient way to run these tests is by selecting options in the CiaoDbg menu within the development environment:

1. **Run tests in current module:** execute only the tests specified in the current module.
2. **Run tests in all related modules:** execute the tests specified in the module and in all the modules being used by this.
3. **Show untested predicates:** show the *exported* predicates that do not have any test assertion.

13.1 Additional notes

1. The test assertions allow performing *unit* testing, i.e., in Ciao, performing tests *at the predicate level*.
2. The tests currently can only be applied to exported predicates.
3. If you need to write tests for predicates that are spread over several modules, but work together, then it is best to create a separate module, and reexport to the predicates required to build the test. This allows performing *integration testing*, using the same syntax of the unit tests.
4. The Ciao system includes a good (and growing) number of unit tests. To run all the tests among the other standard tests within the CiaoDE run the following (at the top level of the source tree):

```
./ciaosetup runtests
```

13.2 Usage and interface (unittest_doc)

- **Library usage:**
 - :- use_module(library(unittest)).
- **Other modules used:**
 - *Internal (engine) modules:*
term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,
data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,
system_info, term_compare, term_typing, hiord_rt, debugger_support.

14 Installing lpdoc

Author(s): Manuel Hermenegildo.

This documentation is outdated.

The source distribution contains all the source code and libraries and can be compiled on a supported Prolog system (lpdoc is developed using Ciao Prolog). The latest publically distributed version of lpdoc is available from <http://www.clip.dia.fi.upm.es/Software/Ciao>. A newer version in Beta test is often available in <http://www.clip.dia.fi.upm.es/Software/Beta/Ciao>.

14.1 Installing the source distribution (lpdoc)

- Before installing lpdoc, you may want to read Section 14.2 [Other software packages required (lpdoc)], page 107. Make sure that emacs is installed in your system
- Uncompress (using gunzip) and unpackage (using tar -xpf) the distribution in a suitable directory. This will create a new directory called lpdoc as well as a link lpdoc-X.Y to this directory, where X.Y is the version number of the distribution. The -p option in the tar command ensures that the relative dates of the files in the package are preserved, which is needed for correct operation of the Makefiles.
- Enter the newly created directory and if needed edit the file LPDOCSETTINGS.pl in a text editor, but in general the default options works well (edit the one in that directory, not the ones in the subdirectories).
 - Decide which Prolog/CLP system you will use for compiling lpdoc (actually, currently only Ciao is supported – but porting to, e.g., SICStus Prolog should not be too difficult) and modify the first part of the LPDOCSETTINGS.pl file accordingly. The DOCDIR directory should not be an existing info directory, since this will overwrite the dir file in that directory.
 - Select the directories in which you want the lpdoc binaries, libraries, and documents installed, by setting the corresponding variables in LPDOCSETTINGS.pl.
- Type `lpmake all`. This should create the lpdoc executable and compile related libraries.
- Type `lpmake install`. This should install it in the BINDIR directory, install the lpdoc library in a separate directory in the LIBDIR directory, and install the lpdoc documentation in the DOCDIR directory.
- In order for the lpdoc documentation to be available to users automatically, certain environment variables have to be set. The installation leaves files suitable for inclusion in initialization scripts (e.g., DOTcshrc for csh) in the lpdoc library.

14.2 Other software packages required (lpdoc)

The most basic functionality of lpdoc (generating manuals in .texi format, short manual entries in .man1 format, generating index files) is essentially self contained. However, using the full capabilities of lpdoc requires having several other software packages installed in the system. Fortunately, all of these packages are public domain software and they will normally be already installed in, e.g., a standard Linux distribution. It should be relatively easy to get and install the required packages in other Unix-like packages or even in Windows, under the Cygwin environment.

- **Basic requirements:** the Makefiles used by lpdoc require GNU Make (gmake), and for now have only been designed for UN*X-like operating systems.

- **Generating .dvi files:** lpdoc normally generates .texi files (actually, a number of .texic files). From the .texi files, .dvi files are generated using the standard tex package directly. The .dvi files can also be generated with the GNU Texinfo package, which provides, among others, the texi2dvi command. However, Texinfo itself requires the standard tex document processing package. In order to use texi2dvi instead of tex when processing documents you should change the variable TEX in the Makefile.skel file in the lib directory before installing lpdoc. Generating the .dvi file requires that the texinfo.tex file (containing the relevant macros) be available to tex. This file is normally included with modern tex distributions, although it may be obsolete. An appropriate and up-to-date one for lpdoc is provided with the lpdoc distribution, stored in the lpdoc library during installation, and used automatically when lpdoc runs tex. The texindex package is required in order to process the indices. If you use references in your manual, then the bibtex package is also needed. texindex and bibtex are included with most tex distributions.
- **Generating .ps files:** .ps files are generated from the .dvi files using the dvips command (this, again, can be changed in the Makefile.skel file in the lib directory). This command is included with standard tex distributions.
- **Generating .pdf files:** .pdf files are currently generated from the .texi file using the pdftex command (this, again, can be changed in the Makefile.skel file in the lib directory). This command is included in current Linux distributions.
- **Generating .html files:** .html files are generated directly from the .texi file using the texi2html command (this, again, can be changed in the Makefile.skel file in the lib directory). This command is a perl script and is included with the lpdoc distribution, and installed in the library (so that it does not overwrite other existing versions). It is also typically included in the Texinfo distribution. A required intermediate step is to resolve the link references which appear in the .texi file (the .texi file includes all the .texic files and has all references resolved). This is done using the emacs editor in batch mode, calling functions in the emacs-library.el file included in the lib directory of the lpdoc distribution. Thus, a recent version of emacs is required for this purpose.
- **Generating .info files:** .info files are also generated directly from the .texi file using the makeinfo command (this, again, can be changed in the Makefile.skel file in the lib directory). This command is included in the Texinfo distribution. Resolving the link references in the .texi file is also required as above.
- If pictures are used in the manual, and html output is selected, the commands pstogif and cjpeg are also required, in order to convert the figures from .eps to .jpg format.

PART II - LPdoc Internals Manual



15 Documentation Generation Library

Author(s): Manuel Hermenegildo, Jose F. Morales.

This library provides some predicates which generate documentation automatically for a given module or application, using the declarations and assertions used in the module itself as input (see the `assertions` library). By default, only the exported predicates of the module appear in the documentation. The predicates will be documented in the order in which they appear in the `module/1` or `module/2` declaration.

The idea of this package is on one hand to reuse the information present in the assertions and on the other to help ensure that code and documentation are kept as coherent as possible. Hopefully, keeping them close together should help in this always difficult task. The resulting documentation is somewhat rigidly structured, but generally sufficient for a *reference* manual, provided a little effort is put into the assertions and comments. The end product understandably depends heavily on how much work is put into adding additional comments to the source. Some documentation will be generated in any case, but it is recommended that, at the minimum, a module title and a comment for each of the exported predicates be provided.

Note: This part is obsolete. – JFMC

The output format in which the documentation is generated is defined by the backend modules (`autodoc_texinfo`, `autodoc_html`, `autodoc_man`, etc.).

The main output format supported is `texinfo` (see The GNU Texinfo Documentation System manual for more info), from which printed manuals and several other printing and on-line formats can be easily generated automatically (including `info`, `html`, etc.). There is also some limited support for direct output in unix `man` format and direct `html` (but note that `html` can also be generated in a better way by first generating `texinfo` and then using one of the available converters). For `texinfo`, the documentation for a module is a `texinfo` chapter, suitable for inclusion in a wrapper “main” document file. A simple example of the use of this library for generating a `texinfo` reference manual (including a driver script, useful Makefiles, etc.) is included with the library source code. Other examples can be found in the Ciao documentation directory (i.e., the Ciao manuals themselves).

A simple example of the use of this library for generating a `texinfo` reference manual (including a driver script, useful Makefiles, etc.) is included with the library source code. Other examples can be found in the Ciao documentation directory (i.e., the Ciao manuals themselves).

15.1 Usage and interface (autodoc)

- **Library usage:**
 :- use_module(library(autodoc)).
- **Exports:**
 - *Predicates:*
 index_comment/2, reset_output_dir_db/0, ensure_output_dir_prepared/2,
 get_autodoc_opts/3, autodoc_gen_doctree/5, fmt_infodir_entry/3, autodoc_
 compute_grefs/3, autodoc_translate_doctree/3, autodoc_finish/1, autodoc_
 gen_alternative/2.
 - *Multifiles:*
 autodoc_finish_hook/1, autodoc_gen_alternative_hook/2.
- **Other modules used:**
 - *Application modules:*
 lpdocsrc(src(autodoc_state)), lpdocsrc(src(autodoc_settings)),
 lpdocsrc(src(autodoc_filesystem)), lpdocsrc(src(autodoc_structure)),
 lpdocsrc(src(autodoc_doctree)), lpdocsrc(src(autodoc_refsdb)),
 lpdocsrc(src(autodoc_parse)), lpdocsrc(src(autodoc_
 index))), lpdocsrc(src(comments)), lpdocsrc(src(autodoc_html_resources)),
 lpdocsrc(src(autodoc_texinfo)).
 - *System library modules:*
 format, ttyout, aggregates, read,
 make/make_rt, dict, compiler/compiler, assertions/assrt_lib, compiler/c_itf,
 assertions/assertions_props, messages, filenames, lists, terms, make/system_
 extra, system.
 - *Internal (engine) modules:*
 term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,
 data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,
 system_info, term_compare, term_typing, hiord_rt, debugger_support.

15.2 Documentation on exports (autodoc)

- index_comment/2:** PREDICATE
 Usage: index_comment(Index,Text)
- *Description:* Type is a type of index which is supported. Text describes the index contents.
 - *The following properties should hold upon exit:*
 - Index is currently instantiated to an atom. (atom/1)
 - Text is a string (a list of character codes). (string/1)
- reset_output_dir_db/0:** PREDICATE
 No further documentation available for this predicate.

ensure_output_dir_prepared/2: PREDICATEUsage: `ensure_output_dir_prepared(Backend, Opts)`

- *Description:* Ensure that the output directories for backend `Backend` are prepared.

get_autodoc_opts/3: PREDICATEUsage: `get_autodoc_opts(Backend, Mod, Opts)`

- *Description:* Get the list of documentation options `Opts` for the `FileBase` file.
- *The following properties should hold at call time:*

`Backend` is an atom. (`atom/1`)
`Mod` is an atom. (`atom/1`)
`Opts` is a list of `supported_options`. (`list/2`)

autodoc_gen_doctree/5: PREDICATEUsage: `autodoc_gen_doctree(Backend, FileBase, SourceSuffix, Opts, Mod)`

- *Description:* `FileBase` is the module specifier of the source file being documented (without extension, `SourceSuffix` is the suffix of the source). The output is a file whose contents document the main file, based on any assertions present in that file. The documentation is produced in the format given by `Backend` (the name of the output file also depends on `Backend`). The formats supported are given by `backend_id/1`.
- *Call and exit should be compatible with:*

`Backend` is a supported backend. (`backend_id/1`)
`FileBase` is the base name of a file (without extension). (`basename/1`)
`SourceSuffix` is an atom. (`atom/1`)
`Opts` is a list of `supported_options`. (`list/2`)
`Mod` is an atom. (`atom/1`)

fmt_infodir_entry/3: PREDICATEUsage: `fmt_infodir_entry(DocSt, Version, Mod)`

- *Description:* Generates a one line description (ASCII) of the application or library in a file for the directory of `emacs info` manuals.
- *The following properties should hold at call time:*

`docstate(DocSt)` (`docstate/1`)
`Version` is any term. (`term/1`)
`Mod` is the base name of a file (without extension). (`basename/1`)

autodoc_compute_grefs/3: PREDICATE

Usage:

- *Description:* Compute the globally resolved references (including bibliography)

autodoc_translate_doctree/3: PREDICATE
Usage:
– *Description:* Translate the doctree using the specific backend

autodoc_finish/1: PREDICATE
No further documentation available for this predicate.

autodoc_gen_alternative/2: PREDICATE
No further documentation available for this predicate.

15.3 Documentation on multifiles (autodoc)

autodoc_finish_hook/1: PREDICATE
No further documentation available for this predicate.
The predicate is *multifile*.

autodoc_gen_alternative_hook/2: PREDICATE
No further documentation available for this predicate.
The predicate is *multifile*.

16 Internal State for Documentation Generation

Author(s): Manuel Hermenegildo, Jose F. Morales.

This module defines the internal state of the documentation generation (for a single module).

16.1 Usage and interface (autodoc_state)

- **Library usage:**
 - :- use_module(library(autodoc_state)).
- **Exports:**
 - *Predicates:*
 - option_comment/2, backend_ignores_components/1, backend_alt_format/2, top_suffix/2, docst_backend/2, docst_currmod/2, docst_set_currmod/3, docst_opts/2, docst_set_opts/3, docst_inputfile/2, docst_new_no_src/4, docst_new_with_src/6, docst_new_sub/3, docst_message/2, docst_message/3, docst_opt/2, docst_currmod_is_main/1, docst_no_components/1, docst_modname/2, labgen_init/1, labgen_clean/1, labgen_get/2, docst_mvar_lookup/3, docst_mvar_replace/4, docst_mvar_get/3, docst_mdata_clean/1, docst_mdata_assertz/2, docst_mdata_save/1, docst_gdata/3, docst_gdata_query/2, docst_gdata_query/3, docst_gdata_restore/1, docst_gdata_clean/1, docst_gvar_save/2, docst_gvar_restore/2, docst_has_index/2, all_indices/2, get_doc/4, get_doc_field/3, get_doc_field_dict/3, bind_dict_varnames/1, get_mod_doc/3, docst_modtype/2, get_first_loc_for_pred/3.
 - *Properties:*
 - supported_option/1.
 - *Regular Types:*
 - backend_id/1, docstate/1, modtype/1.
- **Other modules used:**
 - *Application modules:*
 - lpdocsrc(src(autodoc_settings)), lpdocsrc(src(autodoc_filesystem)), lpdocsrc(src(autodoc_structure)), lpdocsrc(src(autodoc_doctree)), lpdocsrc(src(autodoc_refsdb)), lpdocsrc(src(autodoc_parse)), lpdocsrc(src(autodoc_index)), lpdocsrc(src(comments)).
 - *System library modules:*
 - make/make_rt, dict, compiler/compiler, assertions/assrt_lib, compiler/c_itf, assertions/assertions_props, messages, filenames, lists, terms, make/system_extra, write, read, system, aggregates.
 - *Internal (engine) modules:*
 - term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol, data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic, system_info, term_compare, term_typing, hiord_rt, debugger_support.

16.2 Documentation on exports (autodoc_state)

supported_option/1:
Usage: supported_option(Option)

PROPERTY

- *Description:* Option is a supported documentation option.

option_comment/2:

PREDICATE

Usage: option_comment(Option,Text)

- *Description:* Option is a documentation option which is supported. Text describes the effect of selecting that option. Currently supported options are:

```

option_comment(verbose,"Verbose output (good for debugging).           ").
option_comment(no_bugs,"Do not include information on bugs.           ").
option_comment(no_authors,"Do not include author names.              ").
option_comment(no_stability,"Do not include stability comment.       ").
option_comment(no_version,"Do not include version information.        ").
option_comment(no_versioned_output,"Do not include version in the output nam
option_comment(no_changelog,"Do not include change log.              ").
option_comment(no_patches,"Do not include comments for patches.      ").
option_comment(modes,"Do not translate modes and their arguments
                        (except for properties)
option_comment(head_props,"Do not move head properties to body.      ").
option_comment(literal_props,"Do not use text to document properties. ").
option_comment(no_propnames,"Do not include property names in prop text. ").
option_comment(no_undefined,"Do not signal undefined properties in text. ").
option_comment(no_propsepln,"Do not put each property in a separate line. ").
option_comment(no_biblio,"Do not include a bibliographical 'References' appe
option_comment(no_sysmods,"Do not include system modules in list of
                        libraries used. ").
option_comment(no_engmods,"Do not include system engine modules in list
                        of libraries used. ").
option_comment(no_isoline,"Do not include *textual* description that a
                        given usage conforms to the ISO standard. ").
option_comment(propmods,"Include module name to which props belong. ").
option_comment(no_propuses,"Do not Include property uses (from assertions) i
option_comment(shorttoc,"Produce shorter table of contents (no entries
                        for individual defs of preds, props, etc.).'
option_comment(regtype_props,"Include in the doc for regtypes the global
                        prop stating that they are indeed regtypes.'
option_comment(onesided,"For printing on one side (default is two). ").
option_comment(no_math,"Disable mathematical environments. ").

```

- *The following properties should hold upon exit:*

```

Option is a supported documentation option.           ( supported_option/1)
Text is a string (a list of character codes).         ( string/1)

```

backend_id/1:

REGTYPE

Usage: backend_id(Id)

- *Description:* Id is a supported backend.

backend_ignores_components/1:

PREDICATE

Usage: backend_ignores_components(Id)

- *Description:* Id does not take into account components (only documents the *mainfile*)

- backend_alt_format/2:** PREDICATE
 Usage: backend_alt_format(Id,Ext)
 – *Description:* Ext is an alternative file format that can be generated by the backend Id
- top_suffix/2:** PREDICATE
 Usage: top_suffix(FileFormat,PrincipalExt)
 – *Description:* PrincipalExt is extension of the target file that will generate the file with FileFormat extension.
- docstate/1:** REGTYPE
 A regular type, defined as follows:

```
docstate(docstate(Backend,Name,Opts,MVarDic,I)) :-
    backend_id(Backend),
    atom(Name),
    list(Opts,supported_option),
    dictionary(MVarDic),
    filename(I).
```
- docst_backend/2:** PREDICATE
 No further documentation available for this predicate.
- docst_currmod/2:** PREDICATE
 No further documentation available for this predicate.
- docst_set_currmod/3:** PREDICATE
 No further documentation available for this predicate.
- docst_opts/2:** PREDICATE
 No further documentation available for this predicate.
- docst_set_opts/3:** PREDICATE
 No further documentation available for this predicate.
- docst_inputfile/2:** PREDICATE
 No further documentation available for this predicate.

docst_new_no_src/4: No further documentation available for this predicate.	PREDICATE
docst_new_with_src/6: No further documentation available for this predicate.	PREDICATE
docst_new_sub/3: No further documentation available for this predicate.	PREDICATE
docst_message/2: No further documentation available for this predicate.	PREDICATE
docst_message/3: No further documentation available for this predicate.	PREDICATE
docst_opt/2: No further documentation available for this predicate.	PREDICATE
docst_currmod_is_main/1: No further documentation available for this predicate.	PREDICATE
docst_no_components/1: Usage: <code>docst_no_components(DocSt)</code> – <i>Description:</i> <code>DocSt</code> specify an empty list of components	PREDICATE
docst_modname/2: Usage: <code>docst_modname(DocSt,ModName)</code> – <i>Description:</i> <code>ModName</code> is the name of the module that we are documenting.	PREDICATE
labgen_init/1: No further documentation available for this predicate.	PREDICATE
labgen_clean/1: No further documentation available for this predicate.	PREDICATE

labgen_get/2: No further documentation available for this predicate.	PREDICATE
docst_mvar_lookup/3: No further documentation available for this predicate.	PREDICATE
docst_mvar_replace/4: No further documentation available for this predicate.	PREDICATE
docst_mvar_get/3: No further documentation available for this predicate.	PREDICATE
docst_mdata_clean/1: No further documentation available for this predicate.	PREDICATE
docst_mdata_assertz/2: No further documentation available for this predicate.	PREDICATE
docst_mdata_save/1: No further documentation available for this predicate.	PREDICATE
docst_gdata/3: No further documentation available for this predicate. The predicate is of type <i>data</i> .	PREDICATE
docst_gdata_query/2: No further documentation available for this predicate.	PREDICATE
docst_gdata_query/3: No further documentation available for this predicate.	PREDICATE
docst_gdata_restore/1: No further documentation available for this predicate.	PREDICATE
docst_gdata_clean/1: No further documentation available for this predicate.	PREDICATE

docst_gvar_save/2: No further documentation available for this predicate.	PREDICATE
docst_gvar_restore/2: No further documentation available for this predicate.	PREDICATE
docst_has_index/2: No further documentation available for this predicate.	PREDICATE
all_indices/2: No further documentation available for this predicate.	PREDICATE
get_doc/4: No further documentation available for this predicate.	PREDICATE
get_doc_field/3: No further documentation available for this predicate.	PREDICATE
get_doc_field_dict/3: No further documentation available for this predicate.	PREDICATE
bind_dict_varnames/1: Usage: <code>bind_dict_varnames(Dict)</code> – <i>Description:</i> Binds the variables in <code>Dict</code> to the corresponding names (i.e., the names that appeared in the source during read).	PREDICATE
get_mod_doc/3: No further documentation available for this predicate.	PREDICATE
modtype/1: <code>modtype(part).</code> <code>modtype(application).</code> <code>modtype(documentation).</code> <code>modtype(module).</code> <code>modtype(user).</code> <code>modtype(include).</code> <code>modtype(package).</code> Usage: – <i>Description:</i> Represents the type of file being documented.	REGTYPE

docst_modtype/2:

No further documentation available for this predicate.

PREDICATE

get_first_loc_for_pred/3:

No further documentation available for this predicate.

PREDICATE

17 Documentation Abstract Syntax Tree

Author(s): Manuel Hermenegildo (original version), Jose F. Morales.

This module defines the intermediate tree representation `doctree/1` for documentation and its related operations.

Note: This part needs better documentation. – JFMC

17.1 Usage and interface (`autodoc_doctree`)

- **Library usage:**
 - `:- use_module(library(autodoc_doctree)).`
- **Exports:**
 - *Predicates:*
 - `cmd_type/1`, `doctree_is_empty/1`, `is_nonempty_doctree/1`, `empty_doctree/1`,
`doctree_insert_end/3`, `doctree_insert_before_section/3`, `doctree_concat/3`,
`doclink_at/2`, `doclink_is_local/1`, `section_prop/2`, `section_select_prop/3`,
`doctree_save/2`, `doctree_restore/2`, `doctree_simplify/2`, `doctree_putvars/5`,
`doctree_scan_and_save_refs/2`, `doctree_prepare_docst_translate_and_write/3`,
`doctree_to_rawtext/3`, `doctree_translate_and_write/3`, `escape_string/4`,
`is_version/1`, `version_patch/2`, `version_date/2`, `version_numstr/2`,
`version_string/2`, `insert_show_toc/3`.
 - *Regular Types:*
 - `doctree/1`, `doclink/1`, `doclabel/1`, `doctokens/1`.
 - *Multifiles:*
 - `autodoc_rw_command_hook/4`, `autodoc_escape_string_hook/5`.
- **Other modules used:**
 - *Application modules:*
 - `lpdocsrc(src(autodoc_state))`, `lpdocsrc(src(autodoc_refsdb))`,
`lpdocsrc(src(autodoc_index))`, `lpdocsrc(src(autodoc_structure))`,
`lpdocsrc(src(autodoc_filesystem))`, `lpdocsrc(src(autodoc_settings))`,
`lpdocsrc(src(comments))`, `lpdocsrc(src(autodoc_texinfo))`,
`lpdocsrc(src(autodoc_man))`, `lpdocsrc(src(autodoc_html))`.
 - *System library modules:*
 - `write`, `operators`, `format`, `lists`, `make/system_extra`, `read`, `terms`,
`make/make_rt`.
 - *Internal (engine) modules:*
 - `term_basic`, `arithmetic`, `atomic_basic`, `attributes`, `basic_props`,
`basiccontrol`, `data_facts`, `exceptions`, `io_aux`, `io_basic`, `prolog_flags`,
`streams_basic`, `system_info`, `term_compare`, `term_typing`,
`hiord_rt`, `debugger_support`.

17.2 Documentation on exports (`autodoc_doctree`)

`cmd_type/1:`

No further documentation available for this predicate.

PREDICATE

doctree/1:	REGTYPE
Usage:	
– <i>Description:</i> Intermediate tree representation for documentation	
doctree_is_empty/1:	PREDICATE
Usage: <code>doctree_is_empty(+R)</code>	
– <i>Description:</i> Emptiness test	
– <i>The following properties should hold at call time:</i>	
Intermediate tree representation for documentation	(<code>doctree/1</code>)
is_nonempty_doctree/1:	PREDICATE
Usage: <code>is_nonempty_doctree(+R)</code>	
– <i>Description:</i> Not empty test	
– <i>The following properties should hold at call time:</i>	
Intermediate tree representation for documentation	(<code>doctree/1</code>)
empty_doctree/1:	PREDICATE
Usage: <code>empty_doctree(-R)</code>	
– <i>Description:</i> Empty	
– <i>The following properties should hold at call time:</i>	
Intermediate tree representation for documentation	(<code>doctree/1</code>)
doctree_insert_end/3:	PREDICATE
Usage: <code>doctree_insert_end(A0,Elem,A)</code>	
– <i>Description:</i> Insert <code>Elem</code> in <code>A0</code> at the end, obtaining <code>A</code>	
– <i>Call and exit should be compatible with:</i>	
Intermediate tree representation for documentation	(<code>doctree/1</code>)
Intermediate tree representation for documentation	(<code>doctree/1</code>)
Intermediate tree representation for documentation	(<code>doctree/1</code>)
doctree_insert_before_section/3:	PREDICATE
Usage: <code>doctree_insert_before_section(A0,Elem,A)</code>	
– <i>Description:</i> Insert <code>Elem</code> in <code>A0</code> before the first section, obtaining <code>A</code>	
– <i>Call and exit should be compatible with:</i>	
Intermediate tree representation for documentation	(<code>doctree/1</code>)
Intermediate tree representation for documentation	(<code>doctree/1</code>)
Intermediate tree representation for documentation	(<code>doctree/1</code>)
doctree_concat/3:	PREDICATE
No further documentation available for this predicate.	

doclink/1:	REGTYPE
Usage:	
– <i>Description:</i> A link to a document label	
doclabel/1:	REGTYPE
Usage:	
– <i>Description:</i> An internal label	
doclink_at/2:	PREDICATE
No further documentation available for this predicate.	
doclink_is_local/1:	PREDICATE
No further documentation available for this predicate.	
doctokens/1:	REGTYPE
Usage:	
– <i>Description:</i> Primitive doctree subset (ready for output, not further reducible)	
section_prop/2:	PREDICATE
No further documentation available for this predicate.	
section_select_prop/3:	PREDICATE
No further documentation available for this predicate.	
doctree_save/2:	PREDICATE
doctree_restore/2:	PREDICATE
doctree_simplify/2:	PREDICATE
No further documentation available for this predicate.	
doctree_putvars/5:	PREDICATE
Usage: <code>doctree_putvars(R0,DocSt,PDict,VarDict,R)</code>	
– <i>Description:</i> Traverse <code>R0</code> and replace each <code>var(Name)</code> doctree item with a fresh variable <code>B</code> . For each replacement, the term <code>B=Var</code> is introduced in <code>VarDict</code> , where <code>Var</code> is the associated value to <code>Name</code> in the dictionary <code>PDict</code> .	

- *The following properties should hold at call time:*
Intermediate tree representation for documentation (doctree/1)
docstate(DocSt) (docstate/1)
 - *The following properties should hold upon exit:*
Intermediate tree representation for documentation (doctree/1)
- doctree_scan_and_save_refs/2:** PREDICATE
Usage: doctree_scan_and_save_refs(R,DocSt)
– *Description:* Scan and save the references of the doctree
– *The following properties should hold at call time:*
Intermediate tree representation for documentation (doctree/1)
docstate(DocSt) (docstate/1)
- doctree_prepare_docst_translate_and_write/3:** PREDICATE
No further documentation available for this predicate.
- doctree_to_rawtext/3:** PREDICATE
Usage: doctree_to_rawtext(X,DocSt,Y)
– *Description:* Y is a simplified raw text representation of the X
– *Call and exit should be compatible with:*
Intermediate tree representation for documentation (doctree/1)
docstate(DocSt) (docstate/1)
Y is a string (a list of character codes). (string/1)
- doctree_translate_and_write/3:** PREDICATE
No further documentation available for this predicate.
- escape_string/4:** PREDICATE
Usage:
– *Description:* Escapes needed characters in input string as needed for the target format.
– *The following properties should hold upon exit:*
Arg1 is currently instantiated to an atom. (atom/1)
Arg2 is a string (a list of character codes). (string/1)
docstate(Arg3) (docstate/1)
Arg4 is a string (a list of character codes). (string/1)
- is_version/1:** PREDICATE
No further documentation available for this predicate.

version_patch/2: PREDICATE
No further documentation available for this predicate.

version_date/2: PREDICATE
No further documentation available for this predicate.

version_numstr/2: PREDICATE
Usage: `version_numstr(Version,Str)`
– *Description:* Obtain the string `Str` representation of version `Version` (except date)

version_string/2: PREDICATE
Usage: `version_string(Version,Str)`
– *Description:* Obtain the string `Str` representation of version `Version` (including date)

insert_show_toc/3: PREDICATE
Usage: `insert_show_toc(R0,DocSt,R)`
– *Description:* Insert the command to show the table of contents in a given `doctree/1`.
The right place may be different depending on the chosen backend.

17.3 Documentation on multifiles (autodoc_doctree)

autodoc_rw_command_hook/4: PREDICATE
No further documentation available for this predicate.
The predicate is *multifile*.

autodoc_escape_string_hook/5: PREDICATE
No further documentation available for this predicate.
The predicate is *multifile*.

18 Handling the Document Structure

Author(s): Jose F. Morales.

18.1 Usage and interface (autodoc_structure)

- **Library usage:**
`:- use_module(library(autodoc_structure)).`
- **Exports:**
 - *Predicates:*
`docstr_node/4, clean_docstr/0, parse_structure/0, standalone_docstr/1, get_mainmod/1, get_mainmod_spec/1, all_component_specs/1.`
- **Other modules used:**
 - *Application modules:*
`lpdocsrc(src(autodoc_settings)).`
 - *System library modules:*
`filenames, aggregates, terms, make/make_rt.`
 - *Internal (engine) modules:*
`term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol, data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic, system_info, term_compare, term_typing, hiord_rt, debugger_support.`

18.2 Documentation on exports (autodoc_structure)

docstr_node/4: No further documentation available for this predicate. The predicate is of type <i>data</i> .	PREDICATE
clean_docstr/0: No further documentation available for this predicate.	PREDICATE
parse_structure/0: No further documentation available for this predicate.	PREDICATE
standalone_docstr/1: No further documentation available for this predicate.	PREDICATE
get_mainmod/1: No further documentation available for this predicate.	PREDICATE

get_mainmod_spec/1:

PREDICATE

No further documentation available for this predicate.

all_component_specs/1:

PREDICATE

No further documentation available for this predicate.

19 Access to Default Settings

Author(s): Jose F. Morales.

This module defines the setting values with some default values.

Note: This part needs better documentation. – JFMC

19.1 Usage and interface (autodoc_settings)

- **Library usage:**
 - :- use_module(library(autodoc_settings)).
- **Exports:**
 - *Predicates:*
 - lpdoc_option/1, verify_settings/0, check_setting/1, setting_value_or_default/2, setting_value_or_default/3, setting_value/2, all_setting_values/2, get_command_option/1, requested_file_formats/1, load_vpaths/0, viewer/3, xdvi/1, xdvisize/1, pdfview/1, psview/1, htmlview/1, bibtex/1, tex/1, texindex/1, dvips/1, ps2pdf/1, makeinfo/1, makertf/1, rtftohlp/1, convertc/1.
- **Other modules used:**
 - *System library modules:*
 - make/system_extra, make/make_rt, aggregates, distutils/distutils.
 - *Internal (engine) modules:*
 - term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol, data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic, system_info, term_compare, term_typing, hiord_rt, debugger_support.

19.2 Documentation on exports (autodoc_settings)

lpdoc_option/1: Defines the global options of lpdoc. The predicate is of type <i>data</i> .	PREDICATE
verify_settings/0: No further documentation available for this predicate.	PREDICATE
check_setting/1: No further documentation available for this predicate.	PREDICATE
setting_value_or_default/2: Usage: setting_value_or_default(Var, Value)	PREDICATE

- *Description:* Returns in **Value** the value of the variable **Var**. In case this variable does not exists, it returns a default value. If there is no default value for the variable **Var** it fails.

setting_value_or_default/3:	PREDICATE
No further documentation available for this predicate.	
setting_value/2:	PREDICATE
No further documentation available for this predicate.	
all_setting_values/2:	PREDICATE
No further documentation available for this predicate.	
get_command_option/1:	PREDICATE
No further documentation available for this predicate.	
requested_file_formats/1:	PREDICATE
Usage: <code>requested_file_formats(F)</code>	
– <i>Description:</i> <code>F</code> is a requested file format	
load_vpaths/0:	PREDICATE
No further documentation available for this predicate.	
viewer/3:	PREDICATE
No further documentation available for this predicate.	
xdvi/1:	PREDICATE
No further documentation available for this predicate.	
xdvisize/1:	PREDICATE
No further documentation available for this predicate.	
pdfview/1:	PREDICATE
No further documentation available for this predicate.	

psview/1: No further documentation available for this predicate.	PREDICATE
htmlview/1: No further documentation available for this predicate.	PREDICATE
bibtex/1: No further documentation available for this predicate.	PREDICATE
tex/1: No further documentation available for this predicate.	PREDICATE
texindex/1: No further documentation available for this predicate.	PREDICATE
dvips/1: No further documentation available for this predicate.	PREDICATE
ps2pdf/1: No further documentation available for this predicate.	PREDICATE
makeinfo/1: No further documentation available for this predicate.	PREDICATE
makertf/1: No further documentation available for this predicate.	PREDICATE
rtfthlp/1: No further documentation available for this predicate.	PREDICATE
convertc/1: No further documentation available for this predicate.	PREDICATE

LPdoc Backends



20 Texinfo Backend

Author(s): Manuel Hermenegildo, Jose F. Morales.

20.1 Usage and interface (autodoc_texinfo)

- **Library usage:**
`:- use_module(library(autodoc_texinfo)).`
- **Exports:**
 - *Predicates:*
`infodir_base/2.`
 - *Multifiles:*
`autodoc_escape_string_hook/5, autodoc_rw_command_hook/4, autodoc_finish_hook/1, autodoc_gen_alternative_hook/2.`
- **Other modules used:**
 - *Application modules:*
`lpdocsrc(src(autodoc_state)), lpdocsrc(src(autodoc_filesystem)),
lpdocsrc(src(autodoc_structure)), lpdocsrc(src(autodoc_index)),
lpdocsrc(src(autodoc_doctree)), lpdocsrc(src(autodoc_images)),
lpdocsrc(src(autodoc_settings)), fastformat, lpdocsrc(src(comments)),
ciaodesrc(makedir(ConfigValues)), lpdocsrc(src(autodoc_aux)).`
 - *System library modules:*
`lists, terms, format, messages, system, make/make_rt, file_utils, make/system_extra.`
 - *Internal (engine) modules:*
`term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,
data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,
system_info, term_compare, term_typing, hiord_rt, debugger_support.`

20.2 Documentation on exports (autodoc_texinfo)

infodir_base/2: PREDICATE
No further documentation available for this predicate.

20.3 Documentation on multifiles (autodoc_texinfo)

autodoc_escape_string_hook/5: PREDICATE
No further documentation available for this predicate.
The predicate is *multifile*.

autodoc_rw_command_hook/4: PREDICATE
The predicate is *multifile*.
Usage: `autodoc_rw_command_hook(Backend, DocSt, Command, NewCommand)`

– *The following properties should hold at call time:*

`Backend` is a supported backend.

(`backend_id/1`)

`docstate(DocSt)`

(`docstate/1`)

Intermediate tree representation for documentation

(`doctree/1`)

Intermediate tree representation for documentation

(`doctree/1`)

`autodoc_finish_hook/1:`

PREDICATE

No further documentation available for this predicate.

The predicate is *multifile*.

`autodoc_gen_alternative_hook/2:`

PREDICATE

No further documentation available for this predicate.

The predicate is *multifile*.

21 HTML Backend

Author(s): Jose F. Morales.

21.1 Usage and interface (autodoc_html)

- **Library usage:**
`:- use_module(library(autodoc_html)).`
- **Other modules used:**
 - *Application modules:*
`lpdocsrc(src(autodoc_state)), lpdocsrc(src(autodoc_structure)),
lpdocsrc(src(autodoc_filesystem)), lpdocsrc(src(autodoc_doctree)),
lpdocsrc(src(autodoc_index)), lpdocsrc(src(autodoc_refsdbs)),
lpdocsrc(src(autodoc_images)), lpdocsrc(src(autodoc_settings)),
lpdocsrc(src(comments)), fastformat, lpdocsrc(src(autodoc_html_template)),
lpdocsrc(src(distpkg_download)), lpdocsrc(src(autodoc_html_resources)).`
 - *System library modules:*
`lists, dict, system, file_utils.`
 - *Internal (engine) modules:*
`term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,
data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,
system_info, term_compare, term_typing, hiord_rt, debugger_support.`

21.2 Documentation on multifiles (autodoc_html)

- autodoc_escape_string_hook/5:** PREDICATE
 No further documentation available for this predicate.
 The predicate is *multifile*.
- autodoc_rw_command_hook/4:** PREDICATE
 The predicate is *multifile*.
Usage: `autodoc_rw_command_hook(Backend, DocSt, Command, NewCommand)`
- *The following properties should hold at call time:*
- | | |
|--|-----------------|
| Backend is a supported backend. | (backend_id/1) |
| <code>docstate(DocSt)</code> | (docstate/1) |
| Intermediate tree representation for documentation | (doctree/1) |
| Intermediate tree representation for documentation | (doctree/1) |
- autodoc_finish_hook/1:** PREDICATE
 No further documentation available for this predicate.
 The predicate is *multifile*.

autodoc_gen_alternative_hook/2:

PREDICATE

No further documentation available for this predicate.

The predicate is *multifile*.

22 Resource Handling for the HTML Backend

Author(s): Jose F. Morales.

22.1 Usage and interface (autodoc_html_resources)

- **Library usage:**
`:- use_module(library(autodoc_html_resources)).`
- **Exports:**
 - *Predicates:*
`prepare_web_skel/1, prepare_mathjax/0, using_mathjax/1.`
- **Other modules used:**
 - *Application modules:*
`lpdocsrc(src(autodoc)), lpdocsrc(src(autodoc_settings)),
lpdocsrc(src(autodoc_filesystem)).`
 - *System library modules:*
`messages, file_utils, make/system_extra, distutils/dirutils, terms.`
 - *Internal (engine) modules:*
`term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,
data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,
system_info, term_compare, term_typing, hiord_rt, debugger_support.`

22.2 Documentation on exports (autodoc_html_resources)

- | | |
|--|-----------|
| prepare_web_skel/1:
No further documentation available for this predicate. | PREDICATE |
| prepare_mathjax/0:
No further documentation available for this predicate. | PREDICATE |
| using_mathjax/1:
No further documentation available for this predicate. | PREDICATE |

23 Template Support for the HTML Backend

Author(s): Jose F. Morales.

23.1 Usage and interface (autodoc_html_template)

- **Library usage:**
`:- use_module(library(autodoc_html_template)).`
- **Exports:**
 - *Predicates:*
`img_url/2, fmt_html_template/3.`
- **Other modules used:**
 - *Application modules:*
`lpdocsrc(src(autodoc_settings)).`
 - *System library modules:*
`component_registry/component_registry, messages, aggregates, system, file_utils, make/system_extra, distutils/dirutils, lists, terms, make/make_rt, pillow/html.`
 - *Internal (engine) modules:*
`term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol, data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic, system_info, term_compare, term_typing, hiord_rt, debugger_support.`

23.2 Documentation on exports (autodoc_html_template)

img_url/2: PREDICATE

Usage: `img_url(Name,Url)`

- *Description:* Obtain the URL where image `Name` is or will be found.
- *Call and exit should be compatible with:*

`Name` is an atom.

(`atom/1`)

`Url` is a string (a list of character codes).

(`string/1`)

fmt_html_template/3:

PREDICATE

No further documentation available for this predicate.

24 Man Pages (man) Backend

Author(s): Jose F. Morales, Manuel Hermenegildo.

24.1 Usage and interface (autodoc_man)

- **Library usage:**
 :- use_module(library(autodoc_man)).
- **Other modules used:**
 - *Application modules:*
 lpdocsrc(src(autodoc_state)), lpdocsrc(src(autodoc_doctree)), lpdocsrc(src(autodoc_images)),
 lpdocsrc(src(autodoc_aux)), lpdocsrc(src(comments)), fastformat.
 - *System library modules:*
 lists.
 - *Internal (engine) modules:*
 term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,
 data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,
 system_info, term_compare, term_typing, hiord_rt, debugger_support.

24.2 Documentation on multifiles (autodoc_man)

autodoc_rw_command_hook/4: PREDICATE

The predicate is *multifile*.

Usage: autodoc_rw_command_hook(Backend, DocSt, Command, NewCommand)

- *The following properties should hold at call time:*

Backend is a supported backend.	(backend_id/1)
docstate(DocSt)	(docstate/1)
Intermediate tree representation for documentation	(doctree/1)
Intermediate tree representation for documentation	(doctree/1)

autodoc_finish_hook/1: PREDICATE

No further documentation available for this predicate.

The predicate is *multifile*.

autodoc_gen_alternative_hook/2: PREDICATE

No further documentation available for this predicate.

The predicate is *multifile*.

25 Filesystem Abstraction

Author(s): Jose F. Morales.

This module provides definitions to assign unique file-system paths and names for each of the intermediate and final results of documentation generation.

25.1 Usage and interface (autodoc_filesystem)

- **Library usage:**
 - :- use_module(library(autodoc_filesystem)).
- **Exports:**
 - *Predicates:*
 - file_format_name/2,
 - supported_file_format/1, file_format_provided_by_backend/3, clean_fs_db/0,
 - get_output_dir/2, get_cache_dir/2, ensure_output_dir/1, ensure_cache_dir/1,
 - main_absfile_in_format/2, main_absfile_for_subtarget/3, absfile_for_aux/3,
 - absfile_for_subtarget/4, main_output_name/2, get_subbase/3, absfile_to_relfile/3,
 - clean_all/0, clean_docs_no_texi/0, clean_all_temporal/0, clean_intermediate/0,
 - clean_tex_intermediate/0.
 - *Regular Types:*
 - filename/1, basename/1, subtarget/1.
- **Other modules used:**
 - *Application modules:*
 - lpdocsrc(src(autodoc_settings)), lpdocsrc(src(autodoc_structure)),
 - lpdocsrc(src(autodoc_state)), lpdocsrc(src(component_versions)).
 - *System library modules:*
 - aggregates, make/system_extra, terms, distutils/dirutils, system, component_registry/component_registry.
 - *Internal (engine) modules:*
 - term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,
 - data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,
 - system_info, term_compare, term_typing, hiord_rt, debugger_support.

25.2 Documentation on exports (autodoc_filesystem)

filename/1: REGTYPE

Usage: filename(X)

- *Description:* X is the name of a file.

basename/1: REGTYPE

Usage: basename(X)

- *Description:* X is the base name of a file (without extension).

subtarget/1:	REGTYPE
Usage:	
– <i>Description:</i> The kind of intermediate/final results for a single documentation processing unit (module).	
file_format_name/2:	PREDICATE
No further documentation available for this predicate.	
supported_file_format/1:	PREDICATE
No further documentation available for this predicate.	
file_format_provided_by_backend/3:	PREDICATE
Usage: <code>file_format_provided_by_backend(Ext,Backend,Subtarget)</code>	
– <i>Description:</i> Backend is the backend that generates files with format Ext	
– <i>Call and exit should be compatible with:</i>	
Ext is an atom.	(atm/1)
Backend is a supported backend.	(backend_id/1)
Subtarget is an atom.	(atm/1)
clean_fs_db/0:	PREDICATE
Usage:	
– <i>Description:</i> Clean the cached information for the filesystem mapping of the documentation generation.	
get_output_dir/2:	PREDICATE
Usage: <code>get_output_dir(Backend,Dir)</code>	
– <i>Description:</i> Obtain the Dir directory where final documentation files will be stored	
get_cache_dir/2:	PREDICATE
Usage: <code>get_cache_dir(Backend,Dir)</code>	
– <i>Description:</i> Obtain the Dir directory where final documentation files will be stored	
ensure_output_dir/1:	PREDICATE
No further documentation available for this predicate.	
ensure_cache_dir/1:	PREDICATE
No further documentation available for this predicate.	

- main_absfile_in_format/2:** PREDICATE
 Usage: `main_absfile_in_format(Ext,File)`
 – *Description:* `File` is the absolute file name for the documentation in `Ext` format of the `main` module
- main_absfile_for_subtarget/3:** PREDICATE
 No further documentation available for this predicate.
- absfile_for_aux/3:** PREDICATE
 Usage: `absfile_for_aux(AuxName,Backend,AbsFile)`
 – *Description:* Absolute file for an auxiliary output file (e.g. CSS, images, etc.)
- absfile_for_subtarget/4:** PREDICATE
 No further documentation available for this predicate.
- main_output_name/2:** PREDICATE
 No further documentation available for this predicate.
- get_subbase/3:** PREDICATE
 Usage: `get_subbase(Base,Sub,SubBase)`
 – *Description:* `SubBase` is the name for the sub-file (`Sub`) associated with `Base`
 – *The following properties should hold upon exit:*
 `Base` is the base name of a file (without extension). (`basename/1`)
 `Sub` is an atom. (`atom/1`)
 `SubBase` is the base name of a file (without extension). (`basename/1`)
- absfile_to_relfie/3:** PREDICATE
 Usage: `absfile_to_relfie(A,Backend,B)`
 – *Description:* Obtain the relative path, w.r.t. the output directory, of an absolute file. This is useful, e.g., for URLs.
- clean_all/0:** PREDICATE
 No further documentation available for this predicate.
- clean_docs_no_texi/0:** PREDICATE
 No further documentation available for this predicate.

clean_all_temporal/0:

No further documentation available for this predicate.

PREDICATE

clean_intermediate/0:

No further documentation available for this predicate.

PREDICATE

clean_tex_intermediate/0:

No further documentation available for this predicate.

PREDICATE

26 Indexing Commands (Definition and Formatting)

Author(s): Jose F. Morales.

This module defines index commands and formatting.

Note: This part needs better documentation. – JFMC

26.1 Usage and interface (autodoc_index)

- **Library usage:**
`:- use_module(library(autodoc_index)).`
- **Exports:**
 - *Predicates:*
`get_idxsub/2, get_idxbase/3, typeindex/5, idx_get_indices/3, is_index_cmd/1, codetype/1, normalize_index_cmd/3, fmt_idx_env/7, fmt_index/3.`
- **Other modules used:**
 - *Application modules:*
`lpdocsrc(src(autodoc_state)), lpdocsrc(src(autodoc_filesystem)),
lpdocsrc(src(autodoc_doctree)), lpdocsrc(src(autodoc_structure)),
lpdocsrc(src(autodoc_refsdb)).`
 - *System library modules:*
`dict, lists, aggregates.`
 - *Internal (engine) modules:*
`term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,
data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,
system_info, term_compare, term_typing, hiord_rt, debugger_support.`

26.2 Documentation on exports (autodoc_index)

get_idxsub/2: PREDICATE
No further documentation available for this predicate.

get_idxbase/3: PREDICATE
No further documentation available for this predicate.

typeindex/5: PREDICATE
Usage: `typeindex(Type, Index, IType, Name, Comment)`
– *Description:* `Index` is the (info) index name in which objects of type `Type` go. `Name` is the title of the index in the documentation. `IType` is the type of index; an empty string means normal. `codeComment` is a comment to include before the index.

– *The following properties should hold upon exit:*

Type is currently instantiated to an atom.	(atom/1)
Index is an atom.	(atm/1)
IType is a string (a list of character codes).	(string/1)
Name is a string (a list of character codes).	(string/1)
Intermediate tree representation for documentation	(doctree/1)

idx_get_indices/3: PREDICATE

No further documentation available for this predicate.

is_index_cmd/1: PREDICATE

No further documentation available for this predicate.

codetype/1: PREDICATE

No further documentation available for this predicate.

normalize_index_cmd/3: PREDICATE

No further documentation available for this predicate.

fmt_idx_env/7: PREDICATE

No further documentation available for this predicate.

fmt_index/3: PREDICATE

No further documentation available for this predicate.

- *Description:* Clean the data stored by `prepare_current_refs/1`.
- *Call and exit should be compatible with:*
`docstate(Arg1)` (`docstate/1`)

secttree/1: REGTYPE
Usage:

- *Description:* A tree of sections

secttree_resolve/3: PREDICATE

Usage: `secttree_resolve(LabelName,Tree,Link)`

- *Description:* Locate in the section tree `Tree` the section with label name `LabelName` and return the `Link` to the section.
- *Call and exit should be compatible with:*
`LabelName` is a string (a list of character codes). (`string/1`)
Intermediate tree representation for documentation (`doctree/1`)
A link to a document label (`doclink/1`)

28 Error Messages

Author(s): Manuel Hermenegildo.

28.1 Usage and interface (autodoc_errors)

- **Library usage:**
 - `:- use_module(library(autodoc_errors)).`
- **Exports:**
 - *Predicates:*
 - `error_text/3.`
- **Other modules used:**
 - *Internal (engine) modules:*
 - `term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol, data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic, system_info, term_compare, term_typing, hiord_rt, debugger_support.`

28.2 Documentation on exports (autodoc_errors)

error_text/3:

No further documentation available for this predicate.

PREDICATE

29 Resolution of Bibliographical References

Author(s): Manuel Hermenegildo (original version), Jose F. Morales.

This module provides a predicate to resolve the bibliographical references found during the generation of documentation.

29.1 Usage and interface (autodoc_bibrefs)

- **Library usage:**
`:- use_module(library(autodoc_bibrefs)).`
- **Exports:**
 - *Predicates:*
`resolve_bibliography/1.`
- **Other modules used:**
 - *Application modules:*
`lpdocsrc(src(autodoc_state)), lpdocsrc(src(autodoc_`
`doctree)), lpdocsrc(src(autodoc_refsdb)), lpdocsrc(src(autodoc_aux)),`
`lpdocsrc(src(autodoc_settings)), lpdocsrc(src(autodoc_parse)).`
 - *System library modules:*
`dict, aggregates, terms, file_utils, lists, format, make/make_rt, make/system_`
`extra.`
 - *Internal (engine) modules:*
`term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,`
`data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,`
`system_info, term_compare, term_typing, hiord_rt, debugger_support.`

29.2 Documentation on exports (autodoc_bibrefs)

resolve_bibliography/1:

PREDICATE

Usage: `resolve_bibliography(DocSt)`

- *Description:* This predicate resolves bibliographical references. The algorithm is as follows:
 - Write all the bibliographical references to a `.aux` file.
 - Invoke BibTeX with a customized `.bst` file that generates a pseudo-docstring.
 - Load the docstring and fix its syntax.
 - Parse the docstring as a doctree.
 - Extract `(Label,Ref)` pairs from `bibitem` commands.

Both the docstring and label/reference pairs are kept in the `DocSt`, and used later to map symbolic references to textual labels.

- *The following properties should hold at call time:*

`docstate(DocSt)`

`(docstate/1)`

30 Auxiliary Definitions

Author(s): Manuel Hermenegildo, Jose F. Morales.

30.1 Usage and interface (autodoc_aux)

- **Library usage:**
`:- use_module(library(autodoc_aux)).`
- **Exports:**
 - *Predicates:*
`read_file/2, ascii_blank_lines/2, sh_exec/2.`
- **Other modules used:**
 - *Application modules:*
`lpdocsrc(src(autodoc_settings)).`
 - *System library modules:*
`messages, system, make/system_extra, lists.`
 - *Internal (engine) modules:*
`term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,
data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,
system_info, term_compare, term_typing, hiord_rt, debugger_support.`

30.2 Documentation on exports (autodoc_aux)

read_file/2: No further documentation available for this predicate.	PREDICATE
ascii_blank_lines/2: No further documentation available for this predicate.	PREDICATE
sh_exec/2: No further documentation available for this predicate.	PREDICATE

31 Image Handling

Author(s): Jose F. Morales.

This module defines the handling of image commands. It defines predicates to locate and convert images in the different formats required for documentation.

Note: This part needs better documentation. – JFMC

31.1 Usage and interface (autodoc_images)

- **Library usage:**
:- use_module(library(autodoc_images)).
- **Exports:**
 - *Predicates:*
locate_and_convert_image/4, clean_image_cache/0.
- **Other modules used:**
 - *Application modules:*
lpdocsrc(src(autodoc_state)), lpdocsrc(src(autodoc_filesystem)),
lpdocsrc(src(autodoc_settings)), lpdocsrc(src(autodoc_aux)).
 - *System library modules:*
terms, make/make_rt, make/system_extra, system, errhandle, messages, format.
 - *Internal (engine) modules:*
term_basic, arithmetic, atomic_basic, attributes, basic_props, basiccontrol,
data_facts, exceptions, io_aux, io_basic, prolog_flags, streams_basic,
system_info, term_compare, term_typing, hiord_rt, debugger_support.

31.2 Documentation on exports (autodoc_images)

locate_and_convert_image/4: PREDICATE

Usage:
locate_and_convert_image(SrcSpecS, AcceptedFormats, DocSt, TargetFileS)

- *Description:* The image at SrcSpecS is located (as one of the known formats known_format/1) and converted to one of the AcceptedFormats. The target file is called TargetFileS
- *Call and exit should be compatible with:*

SrcSpecS is a string (a list of character codes).	(string/1)
AcceptedFormats is a list of atoms.	(list/2)
docstate(DocSt)	(docstate/1)
TargetFileS is a string (a list of character codes).	(string/1)

clean_image_cache/0: PREDICATE

Usage:

- *Description:* Clean the cache for image copy/conversions.

References

- [Bue95] F. Bueno.
The CIAO Multiparadigm Compiler: A User's Manual.
Technical Report CLIP8/95.0, Facultad de Informática, UPM, June 1995.
- [Bue98] F. Bueno.
Using Assertions for Static Debugging of CLP: A Manual.
Technical Report CLIP1/98.0, DISCIPL Project/CLIP Group, UPM, June 1998.
- [DEDC96] P. Deransart, A. Ed-Dbali, and L. Cervoni.
Prolog: The Standard.
Springer-Verlag, 1996.
- [DL93] S. K. Debray and N. W. Lin.
Cost Analysis of Logic Programs.
ACM Transactions on Programming Languages and Systems, 15(5):826–875, November 1993.
- [DLGH97] S.K. Debray, P. López-García, and M. Hermenegildo.
Non-Failure Analysis for Logic Programs.
In *1997 International Conference on Logic Programming*, pages 48–62, Cambridge, MA, June 1997. MIT Press, Cambridge, MA.
- [DLGHL97] S. K. Debray, P. López-García, M. Hermenegildo, and N.-W. Lin.
Lower Bound Cost Estimation for Logic Programs.
In *1997 International Logic Programming Symposium*, pages 291–305. MIT Press, Cambridge, MA, October 1997.
- [Her99] M. Hermenegildo.
A Documentation Generator for Logic Programming Systems.
Technical Report CLIP10/99.0, Facultad de Informática, UPM, September 1999.
- [Her00] M. Hermenegildo.
A Documentation Generator for (C)LP Systems.
In *International Conference on Computational Logic, CL2000*, number 1861 in LNAI, pages 1345–1361. Springer-Verlag, July 2000.
- [JL88] D. Jacobs and A. Langen.
Compilation of Logic Programs for Restricted And-Parallelism.
In *European Symposium on Programming*, pages 284–297, 1988.
- [JM94] J. Jaffar and M.J. Maher.
Constraint Logic Programming: A Survey.
Journal of Logic Programming, 19/20:503–581, 1994.
- [Knu84] D. Knuth.
Literate programming.
Computer Journal, 27:97–111, 1984.
- [LGHD96] P. López-García, M. Hermenegildo, and S. K. Debray.
A Methodology for Granularity Based Control of Parallelism in Logic Programs.
Journal of Symbolic Computation, Special Issue on Parallel Symbolic Computation, 21(4–6):715–734, 1996.
- [MH89] K. Muthukumar and M. Hermenegildo.
Determination of Variable Dependence Information at Compile-Time Through Abstract Interpretation.
In *1989 North American Conference on Logic Programming*, pages 166–189. MIT Press, October 1989.

- [PBH97] G. Puebla, F. Bueno, and M. Hermenegildo.
An Assertion Language for Debugging of Constraint Logic Programs.
Technical Report CLIP2/97.1, Facultad de Informática, UPM, July 1997.
- [PBH98] G. Puebla, F. Bueno, and M. Hermenegildo.
A Framework for Assertion-based Debugging in Constraint Logic Programming.
In *Proceedings of the JICSLP'98 Workshop on Types for CLP*, pages 3–15, Manchester, UK, June 1998.
- [PBH00] G. Puebla, F. Bueno, and M. Hermenegildo.
An Assertion Language for Constraint Logic Programs.
In P. Deransart, M. Hermenegildo, and J. Maluszynski, editors, *Analysis and Visualization Tools for Constraint Programming*, number 1870 in LNCS, pages 23–61. Springer-Verlag, September 2000.

Library/Module Index

A

assertions	41
assertions_props	51
autodoc	111
autodoc_aux	159
autodoc_bibrefs	157
autodoc_doctree	123
autodoc_errors	155
autodoc_filesystem	147
autodoc_html	139
autodoc_html_resources	141
autodoc_html_template	143
autodoc_images	161
autodoc_index	151
autodoc_man	145
autodoc_refsdb	153
autodoc_settings	131
autodoc_state	115
autodoc_structure	129
autodoc_texinfo	137

B

basic_props	61
-------------	----

C

comments	25
----------	----

E

example_module	95
----------------	----

G

Generating	15
------------	----

L

lpdoc_examples	89
lpdoc_install	107

M

meta_props	87
------------	----

N

native_props	77
--------------	----

R

regtypes	57
rtchecks	103

U

unittest	105
----------	-----

Predicate/Method Index

A

absfile_for_aux/3	149
absfile_for_subtarget/4	149
absfile_to_relfile/3	149
all_component_specs/1	130
all_indices/2	120
all_setting_values/2	132
ascii_blank_lines/2	159
autodoc_compute_grefs/3	113
autodoc_escape_string_hook/5	127, 137, 139
autodoc_finish/1	114
autodoc_finish_hook/1	114, 138, 139, 145
autodoc_gen_alternative/2	114
autodoc_gen_alternative_hook/2	114, 138, 140, 145
autodoc_gen_doctree/5	113
autodoc_rw_command_hook/4	127, 137, 139, 145
autodoc_translate_doctree/3	113

B

backend_alt_format/2	117
backend_ignores_components/1	116
bibtex/1	133
bind_dict_varnames/1	120

C

callme/2	88
check/1	48
check_setting/1	131
clean_all/0	149
clean_all_temporal/0	149
clean_current_refs/1	153
clean_docs_no_texi/0	149
clean_docstr/0	129
clean_fs_db/0	148
clean_image_cache/0	161
clean_intermediate/0	150
clean_tex_intermediate/0	150
cmd_type/1	123
codetype/1	152
compute_refs_and_biblio/1	153
convertc/1	133

D

doc_id_type/3	32
doclink_at/2	125
doclink_is_local/1	125
docst_backend/2	117
docst_currmod/2	117
docst_currmod_is_main/1	118
docst_gdata/3	119
docst_gdata_clean/1	119
docst_gdata_query/2	119
docst_gdata_query/3	119
docst_gdata_restore/1	119
docst_gvar_restore/2	120
docst_gvar_save/2	120
docst_has_index/2	120
docst_inputfile/2	117
docst_mdata_assertz/2	119
docst_mdata_clean/1	119
docst_mdata_save/1	119
docst_message/2	118
docst_message/3	118
docst_modname/2	118
docst_modtype/2	121
docst_mvar_get/3	119
docst_mvar_lookup/3	119
docst_mvar_replace/4	119
docst_new_no_src/4	117
docst_new_sub/3	118
docst_new_with_src/6	118
docst_no_components/1	118
docst_opt/2	118
docst_opts/2	117
docst_set_currmod/3	117
docst_set_opts/3	117
docstr_node/4	129
doctree_concat/3	124
doctree_insert_before_section/3	124
doctree_insert_end/3	124
doctree_is_empty/1	124
doctree_prepare_docst_translate_and_write/3	126
doctree_putvars/5	125
doctree_restore/2	125
doctree_save/2	125
doctree_scan_and_save_refs/2	126
doctree_simplify/2	125
doctree_to_rawtext/3	126
doctree_translate_and_write/3	126
dvips/1	133

E

empty_doctree/1	124
ensure_cache_dir/1	148
ensure_output_dir/1	148
ensure_output_dir_prepared/2	112
error_text/3	155
escape_string/4	126

F

false/1	49
file_format_name/2	148
file_format_provided_by_backend/3	148
fmt_html_template/3	143
fmt_idx_env/7	152
fmt_index/3	152
fmt_infodir_entry/3	113

G

get_autodoc_opts/3	113
get_cache_dir/2	148
get_command_option/1	132
get_doc/4	120
get_doc_field/3	120
get_doc_field_dict/3	120
get_first_loc_for_pred/3	121
get_idxbase/3	151
get_idxsub/2	151
get_mainmod/1	129
get_mainmod_spec/1	130
get_mod_doc/3	120
get_output_dir/2	148
get_subbase/3	149

H

htmlview/1	133
------------	-----

I

idx_get_indices/3	152
img_url/2	143
index_comment/2	112
infodir_base/2	137
insert_show_toc/3	127
is/2	102
is_index_cmd/1	152
is_nonempty_doctree/1	124
is_version/1	126

L

labgen_clean/1	118
labgen_get/2	118
labgen_init/1	118
load_vpaths/0	132
locate_and_convert_image/4	161
lpdoc_option/1	131

M

main_absfile_for_subtarget/3	149
main_absfile_in_format/2	148
main_output_name/2	149
makeinfo/1	133
makertf/1	133
mytype/1	98

N

normalize_index_cmd/3	152
-----------------------	-----

O

option_comment/2	116
------------------	-----

P

p/1	97
p/3	100
p/5	97
parse_structure/0	129
pdfview/1	132
prepare_current_refs/1	153
prepare_mathjax/0	141
prepare_web_skel/1	141
ps2pdf/1	133
psview/1	132

Q

q/1	99
q/2	96

R

r/1	96
read_file/2	159
requested_file_formats/1	132
reset_output_dir_db/0	112
resolve_bibliography/1	157

rtftohlp/1..... 133

S

s/1..... 98
 section_prop/2..... 125
 section_select_prop/3..... 125
 secttree_resolve/3..... 154
 setting_value/2..... 132
 setting_value_or_default/2..... 131
 setting_value_or_default/3..... 132
 sh_exec/2..... 159
 standalone_docstr/1..... 129
 supported_file_format/1..... 148

T

t/5..... 98
 tex/1..... 133
 texindex/1..... 133
 top_suffix/2..... 117
 true/1..... 49
 trust/1..... 48
 typeindex/5..... 151

U

u/3..... 97
 using_mathjax/1..... 141

V

verify_settings/0..... 131
 version_date/2..... 127
 version_numstr/2..... 127
 version_patch/2..... 127
 version_string/2..... 127
 viewer/3..... 132

W

w/1..... 98

X

xdvi/1..... 132
 xdvisize/1..... 132

Property Index

B

bind_ins/1 75

C

call/2 87
 clique/1 77
 clique_1/1 78
 compat/2 72
 constraint/1 78
 covered/1 78
 covered/2 78

D

deprecated/1 73
 docstring/1 25, 56

E

equiv/2 75
 error_free/1 75
 eval/1 75
 exception/1 78
 exception/2 78

F

fails/1 79
 filter/2 75
 finite_solutions/1 79

H

have_choicepoints/1 79
 head_pattern/1 52

I

indep/1 79
 indep/2 79
 inst/2 72
 instance/2 86
 is_det/1 79
 iso/1 73

L

linear/1 80
 long/1 97

M

member/2 69
 memo/1 75
 mshare/1 80
 mut_exclusive/1 80

N

nabody/1 54
 native/1 74
 native/2 74
 no_choicepoints/1 80
 no_exception/1 81
 no_exception/2 81
 no_rtcheck/1 74
 no_signal/1 81
 no_signal/2 81
 non_det/1 81
 nonground/1 81
 not_covered/1 81
 not_fails/1 81
 not_further_inst/2 73
 not_mut_exclusive/1 82
 num_solutions/2 82

P

pe_type/1 76
 possibly_fails/1 82
 possibly_nondet/1 83
 prop/2 87
 prop_abs/1 88

R

regtype/1 74
 regtype/2 88
 relations/2 83

S

sideff/2.....	74
sideff_hard/1.....	83
sideff_pure/1.....	83
sideff_soft/1.....	83
signal/1.....	83
signal/2.....	83
signals/2.....	84
size/2.....	84
size/3.....	84
size_lb/2.....	84
size_metric/3.....	84
size_metric/4.....	84
size_o/2.....	84
size_ub/2.....	84
solutions/2.....	82

steps/2.....	85
steps_lb/2.....	85
steps_o/2.....	85
steps_ub/2.....	85
stringcommand/1.....	26
supported_option/1.....	115

T

tau/1.....	85
terminates/1.....	86
test_type/2.....	86
throws/2.....	86

U

user_output/2.....	86
--------------------	----

Regular Type Index

A

aorb/1.....	95
assrt_body/1.....	51
assrt_status/1.....	56
assrt_type/1.....	56
atm/1.....	64
atm_or_atm_list/1.....	72

B

backend_id/1.....	116
bar/1.....	95
basename/1.....	147
baz/1.....	95

C

c_assrt_body/1.....	54
callable/1.....	66
character_code/1.....	70
complex_arg_property/1.....	52
complex_goal_property/1.....	53
constant/1.....	66

D

dictionary/1.....	54
doclabel/1.....	125
doclink/1.....	125
docstate/1.....	117
doctokens/1.....	125
doctree/1.....	124

F

filename/1.....	147
filetype/1.....	32
flag_values/1.....	75
flt/1.....	63

G

g_assrt_body/1.....	55
gnd/1.....	65
gndstr/1.....	65

I

int/1.....	62
------------	----

Y

ymd_date/1.....	38
-----------------	----

L

list/1.....	67, 99
list/2.....	68, 101
list_or_aorb/2.....	96

M

modtype/1.....	120
----------------	-----

N

nlist/2.....	68
nnegint/1.....	62
num/1.....	63
num_code/1.....	71

O

operator_specifier/1.....	67
---------------------------	----

P

predfunctor/1.....	56
predname/1.....	71
property_conjunction/1.....	53
property_starterm/1.....	53
propfunctor/1.....	56

S

s_assrt_body/1.....	54
secttree/1.....	154
sequence/2.....	69
sequence_or_list/2.....	70
string/1.....	71
struct/1.....	64
subtarget/1.....	147

T

term/1.....	61
time_struct/1.....	39
tree_of/2.....	96

V

version_descriptor/1.....	32
version_maintenance_type/1.....	39
version_number/1.....	38

Declaration Index

C

calls/1	43
calls/2	43
comment/2	48
comp/1	45
comp/2	45

D

decl/1	47
decl/2	47
doc/2	32, 47

E

entry/1	46
exit/1	46
exit/2	47

M

modedef/1	47
-----------------	----

P

pred/1	42
pred/2	43
prop/1	45
prop/2	46

R

regtype/1	60
regtype/2	60

S

success/1	44
success/2	44

T

test/1	44
test/2	44
texec/1	43
texec/2	43

Concept Index

- , 6
-
- .bib files 16, 29
- @**
- @! command 31
- @' command 31
- @. command 31
- @.. command 31
- @= command 31
- @? command 31
- @' command 31
- @~ command 31
- @" command 31
- @^ command 31
- @aa command 31
- @AA command 31
- @ae command 31
- @AE command 31
- @apl command 28
- @author command 29
- @b command 31
- @begin{alert} command 27
- @begin{cartouche} command 27
- @begin{description} command 26
- @begin{displaymath} command 30
- @begin{enumerate} command 26
- @begin{itemize} command 26
- @begin{verbatim} command 27
- @bf command 27
- @bullet command 31
- @c command 31
- @cindex command 28
- @cite command 29
- @comment command 26
- @concept command 28
- @copyright command 31
- @d command 31
- @decl command 28
- @defmathcmd/2 command 30
- @defmathcmd/3 command 30
- @em command 27
- @email command 29
- @end{alert} command 27
- @end{cartouche} command 27
- @end{description} command 27
- @end{displaymath} command 30
- @end{enumerate} command 26
- @end{itemize} command 26
- @end{verbatim} command 27
- @file command 29
- @footnote command 27
- @H command 31
- @hfill command 27
- @i command 31
- @image command 30
- @include command 30
- @includedef command 30
- @includefact command 30
- @includeverbatim command 30
- @index command 28
- @iso command 31
- @item command 26, 27
- @j command 31
- @key command 27
- @l command 31
- @L command 31
- @lib command 28
- @math command 29
- @noindent command 27
- @o command 31
- @O command 31
- @oe command 31
- @OE command 31
- @op command 28
- @p command 27
- @pred command 28
- @ref command 29
- @result command 31
- @section command 27
- @sp command 27
- @ss command 31
- @subsection command 27
- @t command 31
- @today command 29
- @tt command 27
- @u command 31
- @uref command 29
- @v command 31
- @var command 29
- @version command 29

A

A4 paper	17
abstract	34
accents	30
acceptable modes	52
acknowledgements	34
address	33
appendix	34
application	4
assertion body syntax	51, 54, 55
assertions	25
author	33
automatic documentation	111
automatic documentation library	111
avoiding indentation	27

B

bibliographic citations	29
bibliographic entries	16
bibliographic entry	29
bibtex	16, 29
blank lines	27
bold face	27
bug	36

C

calls assertion	43, 44
check assertion	48
Ciao	15
comment	26
comment assertion	48
comments, machine readable	41
comp assertion	45
compatibility properties	57
component files	4
contents area	18
copyright	34

D

date	29
decl assertion	47
description list	26
document structure	16
documentation format	111
documentation strings	32

E

emacs Ciao mode	36
Emacs, accessing info files	19
Emacs, generating manuals from	15
Emacs, LPdoc mode	15
email address	29
email addresses	29
emphasis face	27
encapsulated postscript	30
entry assertion	46
enumerated list	26
escape sequences	26
example of lpdoc use	89
exit assertion	46

F

false assertion	49
fixed format text	27
fixed-width font	27
footnote	27
formatting commands	25, 41
framed box	27

G

generating from Emacs	15
generating manuals	15

H

hard side-effects	83
html index page	18

I

image file	30
images, inserting	30
images, scaling	30
including a predicate definition	30
including an image	30
including code	30
including files	30
including images	30
including or not authors	16
including or not bug info	16
including or not changelog	16
including or not versions, patches	16
indentation, avoiding	27
index pages out of order	18

info path list 20
 installation 3
 installation, of manuals 18
 instantiation properties 57
 internals manual 22
 introduction 34
 italics face 27
 item in an itemized list 26
 itemized list 26

K

keyboard key 27

L

LaTeX notation 29
 letter size paper 17
 library 3
 literate programming 19
 log of changes 36

M

machine readable comments 32
 main body 34
 main file 4
 Makefile 107
 module comment 34
 module declaration 111

N

new item in description list 27

O

one-sided printing 16

P

page numbering, changing 16
 page size, changing 17
 page style, changing 17
 paragraph break 27
 parametric property 88
 parametric regular type abstractions 88
 parametric type functor 60
 parts in a large document 23
 parts in large documents 38

planned improvement 36
 pred assertion 42, 43
 program section 35
 program subsection 35
 Prolog, Ciao 15
 prop assertion 45, 46
 properties of computations 57
 properties of execution states 57
 properties, basic 61
 properties, native 77
 property abstraction 88

R

references 29
 regtype assertion 60
 regular type expression 60
 running unit tests 105

S

section 27
 sections 29
 SETTINGS.pl 15
 sharing pieces of text 30
 sharing sets 80
 soft side-effects 83
 space, extra lines 27
 spcae, horizontal fill 27
 special characters 30
 strong face 27
 subsection 27
 subtitle 33
 success assertion 44
 supported documentation formats 113
 synopsis section of the man page 16
 syntax of formatting commands 26
 system modules 16

T

test assertion 44, 45, 105
 texec assertion 43
 texinfo 111
 texinfo files 4
 textual comments 25
 thesis-like style 17
 title 32, 33
 true assertion 49
 trust assertion 48

two-sided 16
typewriter-like font 27

U

unit tests 105
Universal Resource Locator 29
URL 29
urls 29
usage of a command 30
usage of the application 16

V

verbatim text 27
version 29
version maintenance mode for packages 37
version number 36

W

WWW address 29

Author Index

A

Anonymous Author 1 95
Anonymous Author 2 95

D

Daniel Cabeza 61

E

Edison Mera 77, 103, 105

F

Francisco Bueno 41, 57, 77, 87

G

German Puebla 41

J

Jose F. Morales 111, 115, 123, 129, 131, 137, 139,
141, 143, 145, 147, 151, 153, 157, 159, 161

M

Manuel Hermenegildo . . 15, 25, 41, 51, 57, 61, 77, 89,
107, 111, 115, 123, 137, 145, 155, 157, 159

P

Pedro Lopez 57, 77

Global Index

This is a global index containing pointers to places where concepts, predicates, modes, properties, types, applications, etc., are referred to in the text of the document.

..... 6	@apl command..... 28
,	@author command..... 29
,',/2..... 69	@b command..... 31
(@begin{alert} command..... 27
(prop)/2..... 88	@begin{cartouche} command..... 27
*	@begin{description} command..... 26
*/2..... 53	@begin{displaymath} command..... 30
.	@begin{enumerate} command..... 26
.(autodoc_structure)..... 153	@begin{itemize} command..... 26
.bib files..... 16, 29	@begin{verbatim} command..... 27
.cshrc..... 18	@bf command..... 27
.profile..... 18	@bullet command..... 31
:	@c command..... 31
::/2..... 42	@cindex command..... 28
=	@cite command..... 16, 29
= /2..... 32, 33, 34, 35, 36, 37, 38	@comment command..... 26
=>/2..... 42	@concept command..... 28
@	@copyright command..... 31
@! command..... 31	@d command..... 31
@' command..... 31	@decl command..... 28
@. command..... 31	@defmathcmd/2 command..... 30
@.. command..... 31	@defmathcmd/3 command..... 30
@= command..... 31	@em command..... 27
@? command..... 31	@email command..... 29
@' command..... 31	@end{alert} command..... 27
@~ command..... 31	@end{cartouche} command..... 27
@" command..... 31	@end{description} command..... 27
@^ command..... 31	@end{displaymath} command..... 30
@aa command..... 31	@end{enumerate} command..... 26
@AA command..... 31	@end{itemize} command..... 26
@ae command..... 31	@end{verbatim} command..... 27
@AE command..... 31	@file command..... 29
	@footnote command..... 27
	@H command..... 31
	@hfill command..... 27
	@i command..... 31
	@image command..... 30
	@include command..... 30
	@includedef command..... 30
	@includefact command..... 30
	@includeverbatim command..... 30
	@index command..... 28
	@iso command..... 31
	@item command..... 26, 27
	@j command..... 31
	@key command..... 27
	@l command..... 31
	@L command..... 31

@lib command	28
@math command	29
@noindent command	27
@o command	31
@O command	31
@oe command	31
@OE command	31
@op command	28
@p command	27
@pred command	28
@ref command	29
@result command	31
@section command	27
@sp command	27
@ss command	31
@subsection command	27
@t command	31
@today command	29
@tt command	27
@u command	31
@uref command	29
@v command	31
@var command	29
@version command	29
+	
+/1	52
+/2	52
A	
A4 paper	17
absfile_for_aux/3	147, 149
absfile_for_subtarget/4	147, 149
absfile_to_relfile/3	147, 149
abstract	34
accents	30
acceptable modes	52
acknowledgements	34
address	29, 33
aggregates	112, 115, 129, 131, 143, 147, 151, 153, 157
all_component_specs/1	129, 130
all_indices/2	115, 120
all_setting_values/2	131, 132
analyzer output	49
Anonymous Author 1	95
Anonymous Author 2	95
aorb/1	95
appendix	34
application	4
arithexpression/1	102
arithmetic	25, 42, 43, 51, 61, 77, 87, 95, 104, 106, 112, 115, 123, 129, 131, 137, 139, 141, 143, 145, 147, 151, 153, 155, 157, 159, 161
ascii_blank_lines/2	159
assertion body syntax	51, 54, 55
assertion status	43, 44, 45, 47
assertions	3, 22, 23, 25, 41, 42, 51, 111
assertions/assertions_props	42, 59, 112, 115
assertions/assrt_lib	112, 115
assertions/native_props	61, 95
assertions_props	51
assrt_body/1	42, 43, 46, 47, 51, 60
assrt_status/1	43, 44, 45, 46, 47, 51, 56, 60
assrt_type/1	51, 56
atm/1	38, 61, 64, 113, 143, 148, 149, 152
atm_or_atm_list/1	61, 72
atom/1	112, 126, 152
atomic_basic	25, 42, 51, 61, 77, 87, 95, 104, 106, 112, 115, 123, 129, 131, 137, 139, 141, 143, 145, 147, 151, 153, 155, 157, 159, 161
attributes	25, 42, 51, 61, 77, 87, 95, 104, 106, 112, 115, 123, 129, 131, 137, 139, 141, 143, 145, 147, 151, 153, 155, 157, 159, 161
author	33
author indexing	33
autodoc	3, 16, 111
autodoc_aux	159
autodoc_bibrefs	157
autodoc_compute_grefs/3	112, 113
autodoc_doctree	123
autodoc_errors	155
autodoc_escape_string_hook/5	123, 127, 137, 139
autodoc_filesystem	147
autodoc_finish/1	112, 114
autodoc_finish_hook/1	112, 114, 137, 138, 139, 145
autodoc_gen_alternative/2	112, 114
autodoc_gen_alternative_hook/2	112, 114, 137, 138, 140, 145
autodoc_gen_doctree/5	112, 113
autodoc_html	111, 139
autodoc_html_resources	141
autodoc_html_template	143

autodoc_images 161
 autodoc_index 151
 autodoc_man 111, 145
 autodoc_refsdbs 153
 autodoc_rw_command_hook/4 123, 127, 137, 139,
 145
 autodoc_settings 131
 autodoc_state 115
 autodoc_structure 129
 autodoc_texinfo 111, 137
 autodoc_translate_doctree/3 112, 113
 autodocformats 3
 automatic documentation 111
 automatic documentation library 3, 111
 avoiding indentation 27

B

backend_alt_format/2 115, 117
 backend_id/1 113, 115, 116, 138, 139, 145, 148
 backend_ignores_components/1 115, 116
 bar/1 95, 100
 basename/1 113, 147, 149
 bash 18
 basic_props .. 3, 25, 42, 51, 61, 77, 87, 95, 104, 106,
 112, 115, 123, 129, 131, 137, 139, 141, 143, 145,
 147, 151, 153, 155, 157, 159, 161
 basic_props.pl 103
 basic_props:regtype/1 57
 basiccontrol 25, 42, 51, 61, 77, 87, 95, 104, 106,
 112, 115, 123, 129, 131, 137, 139, 141, 143, 145,
 147, 151, 153, 155, 157, 159, 161
 baz(Arg3) 100
 baz/1 95, 100
 bibliographic citations 29
 bibliographic entries 16
 bibliographic entry 29
 bibtex 11, 16, 29, 108
 bibtex/1 131, 133
 bind_dict_varnames/1 115, 120
 bind_ins/1 61, 63, 69, 75
 blank lines 27
 bold face 27
 bug 36

C

c_assrt_body/1 43, 44, 46, 51, 54
 c_itf 9
 call(T,A) 102
 call/1 54
 call/2 87
 callable/1 61, 66, 82, 87, 88
 callme/2 87, 88
 calls assertion 43, 44
 calls/1 42, 43, 44, 46
 calls/2 42, 43
 character string 41
 character_code/1 61, 70, 71
 check assertion 48
 Check(X) 82
 check/1 42, 48, 49
 check_setting/1 131
 Ciao 3, 15, 19, 20, 89, 107
 Ciao Emacs mode 15
 ciaoc 8, 9
 ciaodesrc(makedir(ConfigValues)) 137
 ciaopp 77
 cjpeg 108
 clean_all/0 147, 149
 clean_all_temporal/0 147, 149
 clean_current_refs/1 153
 clean_docs_no_texi/0 147, 149
 clean_docstr/0 129
 clean_fs_db/0 147, 148
 clean_image_cache/0 161
 clean_intermediate/0 147, 150
 clean_tex_intermediate/0 147, 150
 clique/1 77
 clique_1/1 77, 78
 CLP 3
 cmd_type/1 123
 codetype/1 151, 152
 comment 26
 comment assertion 48
 comment string 52, 54, 55
 comment/2 10, 42, 48
 comments 3, 23, 25
 comments, machine readable 41
 CommentType=ack 34
 CommentType=address 33
 CommentType=appendix 35
 CommentType=author 33

CommentType=bug	36
CommentType=copyright	34
CommentType=doinclude	37
CommentType=filetype	38
CommentType=hide	37, 38
CommentType=logo	33
CommentType=module	34
CommentType=nodoc	38
CommentType=section	35
CommentType=subsection	35
CommentType=subtitle	33
CommentType=subtitle_extra	33
CommentType=summary	34
CommentType=title	32
CommentType=usage	35
CommentType=version_maintenance	37
commment/2	11
comp assertion	45
comp/1	42, 45, 55
comp/2	42, 45
compat/2	61, 72
compatibility properties	57
compatible	51
compiler/c_itf	112, 115
compiler/compiler	112, 115
complex argument property	51, 52, 53, 54, 55
complex goal property	52, 54, 55
complex_arg_property/1	51, 52, 54, 55
complex_goal_property/1	51, 52, 53, 55
component files	4
component_registry/component_registry	143, 147
compute_refs_and_biblio/1	153
constant/1	61, 66
constraint/1	77, 78
contents area	18
conversion formats	3
convertc/1	131, 133
copyright	34
covered/1	77, 78
covered/2	77, 78
csh	18, 20, 21, 107
D	
Daniel Cabeza	61
data_facts ..	25, 42, 51, 61, 77, 87, 95, 104, 106, 112, 115, 123, 129, 131, 137, 139, 141, 143, 145, 147, 151, 153, 155, 157, 159, 161
date	29
debugger_support	25, 42, 51, 61, 77, 87, 95, 104, 106, 112, 115, 123, 129, 131, 137, 139, 141, 143, 145, 147, 151, 153, 155, 157, 159, 161
decl assertion	47
decl/1	42, 47, 51
decl/2	42, 47
deprecated/1	61, 73
description list	26
dict	112, 115, 139, 151, 157
dictionary/1	51, 54
dir	20, 107
distutils/dirutils	141, 143, 147
distutils/distutils	131
doc/2	19, 22, 23, 25, 32, 36, 38, 42, 47, 48
doc_id_type/3	25, 32
doc_structure/1	16
doclabel/1	123, 125
doclink/1	123, 125, 154
doclink_at/2	123, 125
doclink_is_local/1	123, 125
docst_backend/2	115, 117
docst_currmod/2	115, 117
docst_currmod_is_main/1	115, 118
docst_gdata/3	115, 119
docst_gdata_clean/1	115, 119
docst_gdata_query/2	115, 119
docst_gdata_query/3	115, 119
docst_gdata_restore/1	115, 119
docst_gvar_restore/2	115, 120
docst_gvar_save/2	115, 120
docst_has_index/2	115, 120
docst_inputfile/2	115, 117
docst_mdata_assertz/2	115, 119
docst_mdata_clean/1	115, 119
docst_mdata_save/1	115, 119
docst_message/2	115, 118
docst_message/3	115, 118
docst_modname/2	115, 118
docst_modtype/2	115, 121
docst_mvar_get/3	115, 119
docst_mvar_lookup/3	115, 119
docst_mvar_replace/4	115, 119
docst_new_no_src/4	115, 117
docst_new_sub/3	115, 118

docst_new_with_src/6 115, 118
 docst_no_components/1 115, 118
 docst_opt/2 115, 118
 docst_opts/2 115, 117
 docst_set_currmod/3 115, 117
 docst_set_opts/3 115, 117
 docstate(Arg1) 153, 154
 docstate(Arg3) 126
 docstate(DocSt) ... 113, 126, 138, 139, 145, 157, 161
 docstate/1 ... 113, 115, 117, 126, 138, 139, 145, 153,
 154, 157, 161
 docstr_node/4 129
 docstring/1 ... 25, 32, 33, 34, 35, 36, 41, 48, 51, 52,
 54, 55, 56
 doctokens/1 123, 125
 doctree/1 ... 123, 124, 126, 127, 138, 139, 145, 152,
 154
 doctree_concat/3 123, 124
 doctree_insert_before_section/3 123, 124
 doctree_insert_end/3 123, 124
 doctree_is_empty/1 123, 124
 doctree_prepare_docst_translate_and_write/3
 123, 126
 doctree_putvars/5 123, 125
 doctree_restore/2 123, 125
 doctree_save/2 123, 125
 doctree_scan_and_save_refs/2 123, 126
 doctree_simplify/2 123, 125
 doctree_to_rawtext/3 123, 126
 doctree_translate_and_write/3 123, 126
 document structure 16
 documentation format 111
 documentation strings 32
 DOTcshrc 107
 dvips 7, 108
 dvips/1 131, 133
 dynamic/1 19

E

Edison Mera 77, 103, 105
 emacs 11, 36, 39, 107, 108
 Emacs 15, 18, 19, 20
 emacs Ciao mode 36
 Emacs, accessing info files 19
 Emacs, generating manuals from 15
 Emacs, LPdoc mode 15
 emacs-library.el 108

email address 29
 email addresses 11, 29
 emphasis face 27
 empty_doctree/1 123, 124
 encapsulated postscript 30
 engine/basic_props 95
 ensure_cache_dir/1 147, 148
 ensure_loaded/1 10, 22, 38
 ensure_output_dir/1 147, 148
 ensure_output_dir_prepared/2 112
 entry assertion 46
 entry/1 42, 46, 54
 enumerated list 26
 environment variables 107
 equiv/2 61, 75
 errhandle 161
 error(a,b) 105
 error_free/1 61, 75
 error_text/3 155
 escape sequences 26
 escape_string/4 123, 126
 eval/1 .. 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72,
 73, 75, 99, 101
 example of lpdoc use 89
 example_module 95
 exception(error(a,b)) 105
 exception/1 77, 78
 exception/2 77, 78
 exceptions .. 25, 42, 51, 61, 77, 87, 95, 104, 106, 112,
 115, 123, 129, 131, 137, 139, 141, 143, 145, 147,
 151, 153, 155, 157, 159, 161
 exit assertion 46, 47
 exit/1 42, 46, 47
 exit/2 42, 47
 exported predicates 111
 exports 103

F

fails/1 77, 79
 false assertion 49
 false/1 42, 49
 fastformat 137, 139, 145
 file_format_name/2 147, 148
 file_format_provided_by_backend/3 147, 148
 file_utils 77, 137, 139, 141, 143, 157
 filename/1 147
 filenames 112, 115, 129

filetype/1..... 25, 32, 38
 filter/2..... 61, 75
 finite_solutions/1..... 77, 79
 Firefox..... 19
 fixed format text..... 27
 fixed-width font..... 27
 flag_values/1..... 61, 75
 flt/1..... 61, 63
 fmt_html_template/3..... 143
 fmt_idx_env/7..... 151, 152
 fmt_index/3..... 151, 152
 fmt_infodir_entry/3..... 112, 113
 foo..... 95
 foo(Arg1)..... 100
 footnote..... 27
 format..... 112, 123, 137, 157, 161
 formatting commands..... 3, 25, 41
 framed box..... 27
 Francisco Bueno..... 41, 57, 77, 87
 func/1..... 55

G

g_assrt_body/1..... 45, 51, 55
 generate_html_pointer/5..... 7
 generate_html_pointer/6..... 7
 Generating..... 15
 generating from Emacs..... 15
 generating manuals..... 15
 German Puebla..... 41
 get_autodoc_opts/3..... 112, 113
 get_cache_dir/2..... 147, 148
 get_command_option/1..... 131, 132
 get_doc/4..... 115, 120
 get_doc_field/3..... 115, 120
 get_doc_field_dict/3..... 115, 120
 get_first_loc_for_pred/3..... 115, 121
 get_idxbase/3..... 151
 get_idxsub/2..... 151
 get_mainmod/1..... 129
 get_mainmod_spec/1..... 129, 130
 get_mod_doc/3..... 115, 120
 get_output_dir/2..... 147, 148
 get_subbase/3..... 147, 149
 ghostview..... 8
 gmake..... 107
 gnd/1..... 61, 65, 96, 97, 98, 99, 100, 102
 gndstr/1..... 61, 65, 66

GNU general public license..... 1
 GNU Make..... 107
 ground/1... 65, 66, 68, 69, 70, 71, 72, 73, 77, 78, 80,
 97, 99, 101
 gunzip..... 107

H

hard side-effects..... 83
 have_choicepoints/1..... 77, 79
 head pattern..... 51, 52, 55
 head_pattern/1..... 48, 51, 52, 55
 hiord_rt ... 25, 42, 51, 61, 77, 87, 95, 104, 106, 112,
 115, 123, 129, 131, 137, 139, 141, 143, 145, 147,
 151, 153, 155, 157, 159, 161
 html..... 4
 HTML..... 1
 html index page..... 18
 htmlview/1..... 131, 133

I

idx_get_indices/3..... 151, 152
 image file..... 30
 images, inserting..... 30
 images, scaling..... 30
 img_url/2..... 143
 include files..... 22, 38
 include/1..... 22, 38
 including a predicate definition..... 30
 including an image..... 30
 including code..... 30
 including files..... 30
 including images..... 30
 including or not authors..... 16
 including or not bug info..... 16
 including or not changelog..... 16
 including or not versions, patches..... 16
 indentation, avoiding..... 27
 indep/1..... 77, 78, 79, 80
 indep/2..... 77, 78, 79, 80
 index pages out of order..... 18
 index_comment/2..... 16, 112
 info..... 1, 4, 19, 20, 21, 24, 27, 107
 info path list..... 20
 infodir_base/2..... 137
 inner..... 103
 insert_show_toc/3..... 123, 127

- inserting images 11
 - inst/2 61, 72
 - installation 3
 - installation, of manuals 18
 - INSTALLATION.lpdoc 23
 - instance/2 86
 - instantiation properties 57
 - int/1 61, 62, 82, 96, 97, 98, 100, 101
 - integer/1 53
 - internals 77
 - internals manual 3, 22
 - introduction 34
 - io_aux 25, 42, 51, 61, 77, 87, 95, 104, 106, 112, 115, 123, 129, 131, 137, 139, 141, 143, 145, 147, 151, 153, 155, 157, 159, 161
 - io_basic ... 25, 42, 51, 61, 77, 87, 95, 104, 106, 112, 115, 123, 129, 131, 137, 139, 141, 143, 145, 147, 151, 153, 155, 157, 159, 161
 - is/2 102
 - is_det/1 62, 63, 64, 65, 66, 67, 68, 77, 79, 99
 - is_index_cmd/1 151, 152
 - is_nonempty_doctree/1 123, 124
 - is_version/1 123, 126
 - iso/1 10, 61, 73, 100
 - italics face 27
 - item in an itemized list 26
 - itemized list 26
- J**
- Jose F. Morales... 111, 115, 123, 129, 131, 137, 139, 141, 143, 145, 147, 151, 153, 157, 159, 161
- K**
- keyboard key 27
 - known_format/1 161
- L**
- labgen_clean/1 115, 118
 - labgen_get/2 115, 118
 - labgen_init/1 115, 118
 - LaTeX 26
 - LaTeX notation 29
 - letter size paper 17
 - library 3
 - library(basicmodes) 52
 - library(isomodes) 52
 - linear/1 77, 80
 - Linux 107, 108
 - list/1 61, 67, 68, 69, 72, 82, 96, 97, 98, 99, 100, 101
 - list/2 37, 38, 53, 61, 68, 97, 98, 101, 113, 161
 - list_or_aorb/2 95, 96
 - lists 42, 45, 77, 95, 112, 115, 123, 137, 139, 143, 145, 151, 153, 157, 159
 - literal 104
 - literate programming 19
 - load_vpaths/0 131, 132
 - locate_and_convert_image/4 161
 - log of changes 36
 - long 104
 - long/1 95, 97, 98
 - lpdoc .. 1, 3, 4, 5, 8, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 29, 37, 41, 48, 52, 56, 89, 107, 108
 - lpdoc -help 16
 - lpdoc all 16, 17, 19
 - lpdoc_examples 89
 - lpdoc_install 107
 - lpdoc_option/1 131
 - lpdocsrc(src(autodoc)) 141
 - lpdocsrc(src(autodoc_aux)) 137, 145, 157, 161
 - lpdocsrc(src(autodoc_bibrefs)) 153
 - lpdocsrc(src(autodoc_doctree)) 112, 115, 137, 139, 145, 151, 153, 157
 - lpdocsrc(src(autodoc_filesystem)) 112, 115, 123, 137, 139, 141, 151, 153, 161
 - lpdocsrc(src(autodoc_html)) 123
 - lpdocsrc(src(autodoc_html_resources)) 112, 139
 - lpdocsrc(src(autodoc_html_template)) 139
 - lpdocsrc(src(autodoc_images)) 137, 139, 145
 - lpdocsrc(src(autodoc_index)) 112, 115, 123, 137, 139
 - lpdocsrc(src(autodoc_man)) 123
 - lpdocsrc(src(autodoc_parse)) 112, 115, 157
 - lpdocsrc(src(autodoc_refsdb)) 112, 115, 123, 139, 151, 157
 - lpdocsrc(src(autodoc_settings)) .. 112, 115, 123, 129, 137, 139, 141, 143, 147, 157, 159, 161
 - lpdocsrc(src(autodoc_state)) 112, 123, 137, 139, 145, 147, 151, 153, 157, 161
 - lpdocsrc(src(autodoc_structure)) 112, 115, 123, 137, 139, 147, 151, 153
 - lpdocsrc(src(autodoc_texinfo)) 112, 123

lpdocsrc(src(comments)) .. 112, 115, 123, 137, 139, 145
 lpdocsrc(src(component_versions)) 147
 lpdocsrc(src(distpkg_download)) 139

M

machine readable comments 25, 32
 main body 34
 main file 4
 main/0 3, 4
 main/1 3, 4
 main_absfile_for_subtarget/3 147, 149
 main_absfile_in_format/2 147, 148
 main_output_name/2 147, 149
 make/make_rt 112, 115, 123, 129, 131, 137, 143, 157, 161
 make/system_extra 112, 115, 123, 131, 137, 141, 143, 147, 157, 159, 161
 Makefile 18, 107
 makeinfo 108
 makeinfo/1 131, 133
 makertf/1 131, 133
 man 19, 20
 Manuel Hermenegildo .. 15, 25, 41, 51, 57, 61, 77, 89, 107, 111, 115, 123, 137, 145, 155, 157, 159
 master index 4
 member/2 61, 69, 74
 memo/1 61, 75
 messages 112, 115, 137, 141, 143, 159, 161
 meta_predicate/1 19
 meta_props 3, 87
 mode 42, 52
 modedef/1 42, 47, 52
 modtype/1 115, 120
 module comment 34
 module declaration 111
 module/1 111
 module/2 111
 mshare/1 77, 80
 mut_exclusive/1 77, 80
 mytype/1 95, 98

N

n_assrt_body/5 54, 55
 nobody/1 51, 54

native/1 ... 61, 62, 63, 64, 65, 66, 74, 78, 79, 80, 82, 85, 86
 native/2 61, 74, 77, 78, 79, 80, 81
 native_props 3, 77
 nativeprops.pl 103
 netscape 8
 new item in description list 27
 nlist/1 69
 nlist/2 61, 68
 nnegint/1 61, 62
 no 103, 104
 no_choicepoints/1 77, 80
 no_exception/1 77, 81
 no_exception/2 77, 81
 no_rtcheck/1 61, 74
 no_signal/1 77, 81
 no_signal/2 77, 81
 non_det/1 77, 81
 nonground/1 77, 81
 nonvar/1 62, 63, 64, 65, 66, 67, 70, 97, 98
 normalize_index_cmd/3 151, 152
 not_covered/1 77, 81
 not_fails 105
 not_fails/1 77, 81, 97, 98, 99, 100, 101
 not_further_inst/1 54
 not_further_inst/2 61, 73, 97, 98
 not_mut_exclusive/1 77, 82
 num/1 61, 63, 64, 102
 num_code/1 61, 71
 num_solutions/2 77, 82

O

og/2 101
 one-sided printing 16
 op/3 19
 operator_specifier/1 61, 67
 operators 123
 option_comment/2 16, 115, 116

P

p/1 95, 97
 p/3 95, 100
 p/5 95, 97
 packages 22, 38
 page numbering, changing 16
 page size, changing 17

- page style, changing..... 17
 paragraph break..... 27
 parametric property..... 88
 parametric regular type abstractions..... 88
 parametric type functor..... 60
 parse_structure/0..... 129
 parts in a large document..... 23
 parts in large documents..... 38
 pdf generation..... 7
 pdf viewer..... 8
 pdftex..... 108
 pdfview/1..... 131, 132
 pe_type/1..... 61, 76
 Pedro Lopez..... 57, 77
 perl..... 108
 pillow/html..... 143
 planned improvement..... 36
 possibly_fails/1..... 77, 82
 possibly_nondet/1..... 77, 83
 pred assertion..... 42, 43
 pred/1..... 29, 42, 43, 44, 45, 47, 51, 55
 pred/2..... 42, 43
 predfunctor/1..... 51, 56
 predicate..... 104
 predicate/n..... 105
 predname/1..... 36, 37, 52, 61, 71, 72
 prepare_current_refs/1..... 153, 154
 prepare_mathjax/0..... 141
 prepare_web_skel/1..... 141
 program assertions..... 41
 program section..... 35
 program subsection..... 35
 Prolog..... 3, 16, 22, 107
 Prolog source files..... 3
 Prolog, Ciao..... 15
 prolog_flags.... 25, 42, 51, 61, 77, 87, 95, 104, 106,
 112, 115, 123, 129, 131, 137, 139, 141, 143, 145,
 147, 151, 153, 155, 157, 159, 161
 prop assertion..... 45, 46
 prop/1..... 42, 45, 46
 prop/2..... 42, 46, 87
 prop_abs/1..... 88
 properties..... 3
 properties of computations..... 57
 properties of execution states..... 57
 properties, basic..... 61
 properties, native..... 77
 property..... 45
 property abstraction..... 88
 property compatibility..... 72
 property_conjunction/1..... 48, 49, 51, 53
 property_starterm/1..... 51, 53
 propfunctor/1..... 51, 56
 providing information to the compiler..... 46, 49
 ps2pdf/1..... 131, 133
 pstogif..... 108
 psview/1..... 131, 132
- ## Q
- q/1..... 95, 99
 q/2..... 95, 96
- ## R
- r/1..... 95, 96
 read..... 112, 115, 123
 read_file/2..... 159
 references..... 29, 108
 regtype assertion..... 60
 regtype/1..... 59, 60, 61, 74
 regtype/2..... 59, 60, 87, 88
 regtypes..... 3, 57
 regular type..... 60
 regular type definitions..... 57
 regular type expression..... 60
 regular types..... 57
 relations/2..... 67, 77, 83
 requested_file_formats/1..... 131, 132
 reset_output_dir_db/0..... 112
 resolve_bibliography/1..... 157
 rtchecks..... 103
 rtchecks_asrloc..... 103
 rtchecks_callloc..... 104
 rtchecks_entry..... 103
 rtchecks_exit..... 103
 rtchecks_inline..... 103
 rtchecks_level..... 103
 rtchecks_namefmt..... 104
 rtchecks_predloc..... 103
 rtchecks_rt.pl..... 103
 rtchecks_test..... 103
 rtchecks_trust..... 103
 rtftohlp/1..... 131, 133
 run-time checks..... 45
 running unit tests..... 105

S

- s/1..... 95, 98
- s_assrt_body/1 44, 45, 46, 47, 51, 54
- scribe..... 26
- section..... 27
- section_prop/2..... 123, 125
- section_select_prop/3 123, 125
- sections..... 29
- sectree/1..... 153, 154
- sectree_resolve/3..... 153, 154
- sequence/2..... 61, 69
- sequence_or_list/2..... 61, 70
- setting_value/2..... 131, 132
- setting_value_or_default/2 131
- setting_value_or_default/3 131, 132
- SETTINGS..... 5, 8, 9, 29
- SETTINGS.pl 15, 16, 18, 19, 20, 21, 23
- SETTINGS.pl.generated 15
- sh_exec/2..... 159
- sharing pieces of text 30
- sharing sets 80
- short..... 104
- sideff/2 ... 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71,
72, 73, 74, 75, 99, 101
- sideff_hard/1 77, 83
- sideff_pure/1 77, 83
- sideff_soft/1 77, 83
- signal/1..... 77, 83
- signal/2..... 77, 83
- signals/2 77, 84
- size/2..... 77, 84
- size/3..... 77, 84
- size_lb/2 77, 84
- size_metric/3..... 77, 84
- size_metric/4 77, 84
- size_o/2..... 77, 84
- size_ub/2 77, 84
- soft side-effects..... 83
- solutions/2 77, 82
- sort 77
- space, extra lines 27
- spcae, horizontal fill..... 27
- special characters 30
- specifications 41
- standalone_docstr/1..... 129
- steps/2..... 77, 85
- steps_lb/2..... 77, 85, 97
- steps_o/2 77, 85
- steps_ub/2 77, 85
- streams..... 77
- streams_basic... 25, 42, 51, 61, 77, 87, 95, 104, 106,
112, 115, 123, 129, 131, 137, 139, 141, 143, 145,
147, 151, 153, 155, 157, 159, 161
- string/1 ... 61, 71, 112, 116, 126, 143, 152, 154, 161
- stringcommand/1 25, 26, 48, 52, 54, 55, 56
- strings..... 25
- strong face..... 27
- struct/1..... 61, 64, 65
- subsection..... 27
- subtarget/1..... 147
- subtitle..... 33
- success assertion..... 44
- success/1..... 42, 44, 46
- success/2 42, 44
- supported documentation formats 113
- supported_file_format/1..... 147, 148
- supported_option/1..... 115, 116
- synopsis section of the man page 16
- syntax of formatting commands 26
- system 77, 112, 115, 137, 139, 143, 147, 159, 161
- system modules..... 16
- system_info..... 25, 42, 51, 61, 77, 87, 95, 104, 106,
112, 115, 123, 129, 131, 137, 139, 141, 143, 145,
147, 151, 153, 155, 157, 159, 161

T

- t/5..... 95, 98
- tar 107
- tau/1 77, 85
- term/1 33, 61, 69, 113
- term_basic .. 25, 42, 51, 59, 61, 77, 87, 95, 104, 106,
112, 115, 123, 129, 131, 137, 139, 141, 143, 145,
147, 151, 153, 155, 157, 159, 161
- term_compare... 25, 42, 51, 61, 77, 87, 95, 104, 106,
112, 115, 123, 129, 131, 137, 139, 141, 143, 145,
147, 151, 153, 155, 157, 159, 161
- term_typing.... 25, 42, 51, 61, 77, 87, 95, 104, 106,
112, 115, 123, 129, 131, 137, 139, 141, 143, 145,
147, 151, 153, 155, 157, 159, 161
- terminates/1..... 77, 86
- terms 112, 115, 123, 129, 137, 141, 143, 147, 157,
161
- terms_check 61, 77
- terms_vars 77

test assertion..... 44, 45, 105
 test/1..... 42, 44, 45
 test/2..... 42, 44
 test_type/2..... 62, 63, 64, 65, 77, 86
 tex..... 24, 108
 TeX..... 9
 tex/1..... 131, 133
 texec assertion..... 43
 texec/1..... 42, 43
 texec/2..... 42, 43
 texi2dvi..... 108
 texi2html..... 108
 texindex..... 108
 texindex/1..... 131, 133
 texinfo..... 1, 3, 4, 16, 17, 21, 24, 111
 Texinfo..... 108
 texinfo files..... 4
 textual comments..... 25
 thesis-like style..... 17
 throws/2..... 77, 86
 time_struct/1..... 39
 times(N)..... 105
 title..... 32, 33
 top_suffix/2..... 115, 117
 tree_of/2..... 95, 96
 troubleshooting..... 15
 true assertion..... 49
 true/1..... 42, 49
 trust assertion..... 48
 trust/1..... 42, 48
 try_sols(N)..... 105
 ttyout..... 112
 two-sided..... 16
 typeindex/5..... 151
 types..... 3
 typewriter-like font..... 27

U

u/3..... 95, 97
 unit tests..... 105
 unittest..... 105
 Universal Resource Locator..... 29
 Unix..... 20
 URL..... 29
 url references..... 11
 urls..... 29
 usage..... 42
 usage of a command..... 30

usage of the application..... 16
 usage section..... 11
 usage tips..... 15
 usage_message/1..... 11, 16
 use_module/1..... 23
 use_package/1..... 22, 38
 user_output/2..... 77, 86
 using citations..... 16
 using_mathjax/1..... 141

V

var/1..... 53, 96, 97, 98, 100, 101
 variable names..... 41
 verbatim text..... 27
 verify_settings/0..... 131
 version..... 29
 version maintenance mode for packages..... 37
 version number..... 36
 version_date/2..... 123, 127
 version_descriptor/1..... 25, 32, 36
 version_maintenance_type/1..... 36, 37, 39
 version_number/1..... 38
 version_numstr/2..... 123, 127
 version_patch/2..... 123, 127
 version_string/2..... 123, 127
 viewer/3..... 131, 132

W

w/1..... 95, 98
 word-help..... 20
 word-help-setup.el..... 20
 word-help.el..... 20
 write..... 115, 123
 WWW..... 1, 19
 WWW address..... 29

X

xdvi..... 17
 xdvi/1..... 131, 132
 xdvisize/1..... 131, 132

Y

yes..... 103, 104
 ymd_date/1..... 38

